

Version #: 01 Issue date: 06-April-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier 17CAR AIR FRESHENER ICON "METAL SHADES" 42 - SANDALO BERGAMOTTO 17CAR42 Trade name or designation of the mixture **Registration number Synonyms** None Product code 17CAR42 1.2. Relevant identified uses of the substance or mixture and uses advised against **Identified uses** General Public Use Uses advised against None known 1.3. Details of the supplier of the safety data sheet Supplier Company name Home Fragrance Italia Address Via A. Tonale 26 Milano 20125 IT Division Telephone Not available. e-mail Not available. Contact person 1.4. Emergency telephone number 1.4. Emergency telephone number General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) +431 406 4343 (Available 24 hours a day. SDS/Product information may not be **Austria National Poisons** available for the Emergency Service.) Information Centre **Belgium National Poisons** 070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) **Control Centre Bulgaria National** +359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) **Toxicological Information** Centre **Czech Republic National** +420 224 919 293, or +420 224 915 402 (Hours of operation not provided. **Poisons Information** SDS/Product information may not be available for the Emergency Service.) Centre **Denmark National Poisons** +45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) **Control Centre Estonia National Poisons** 16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be **Information Centre** available for the Emergency Service.) **Finland National Poison** (09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) **Information Centre France National Poisons** ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) **Control Centre** 36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be **Hungary National** available for the Emergency Service.) **Emergency Phone Number** +370 5 236 20 52 or +37068753378 (Hours of operation not provided. Lithuania Neatidėliotina SDS/Product information may not be available for the Emergency Service.) informacija apsinuodijus

SAFETY DATA SHEET

1.4	1.4. Emergency telephone number						
	Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)					
	Netherlands National Poisons Information Centre (NVIC)	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)					
	Norway Norwegian Poison Information Centre	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)					
	Portugal Poison Centre	800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)					
	Romania Biroul RSI si Informare Toxicologica	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)					
	Slovakia National Toxicological Information Centre	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)					
	Sweden National Poison Information Centre	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)					
	Switzerland Tox Info Suisse	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)					

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

1

Skin sensitisation	Category 1B	H317 - May cause an allergic skin reaction.
Environmental hazards Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.
2.2. Label elements		
Label according to Regulation (EC) No. 1272/200 UFI:	08 as amended	
	F393-600V-GS21 F393-600V-GS21	

Bulgaria: MV74-F393-600V-GS21 Croatia: MV74-F393-600V-GS21 Cyprus: MV74-F393-600V-GS21 Czech Republic: MV74-F393-600V-GS21 Denmark: MV74-F393-600V-GS21 Estonia: MV74-F393-600V-GS21 EU: MV74-F393-600V-GS21 Finland: MV74-F393-600V-GS21 France: MV74-F393-600V-GS21 Germany: MV74-F393-600V-GS21 Great Britain: MV74-F393-600V-GS21 Greece: MV74-F393-600V-GS21 Hungary: MV74-F393-600V-GS21 Iceland: MV74-F393-600V-GS21 Ireland: MV74-F393-600V-GS21 Italy: MV74-F393-600V-GS21 Latvia: MV74-F393-600V-GS21 Lithuania: MV74-F393-600V-GS21 Luxembourg: MV74-F393-600V-GS21 Malta: MV74-F393-600V-GS21 Netherlands: MV74-F393-600V-GS21 Norway: MV74-F393-600V-GS21 Poland: MV74-F393-600V-GS21 Portugal: MV74-F393-600V-GS21 Romania: MV74-F393-600V-GS21 Slovakia: MV74-F393-600V-GS21 Slovenia: MV74-F393-600V-GS21 Spain: MV74-F393-600V-GS21 Sweden: MV74-F393-600V-GS21

Contains:

Hazard pictograms

Benzoic acid, 2,4-dihydroxy-3,6-dimethyl-, methyl ester, Benzyl salicylate, Coumarin, Cyclamen aldehyde, Isocyclemone E, Linalool, Linalyl acetate, Oils, Iavandin, Oils, Iemon, Oils, orange, sweet, Terpenes, orange oil



	\mathbf{v} \mathbf{v}
Signal word	Warning
Hazard statements	
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	
P102	Keep out of reach of children.
Response	
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P302 + P350	If on skin: Wash with plenty of water/.
Storage	Not applicable.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental label information	None.
2.3. Other hazards	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Isocyclemone E		3 - 5	54464-57-2 259-174-3	-	-	
	Classification: S	kin Irrit.	2;H315, Skin Sens. 1	3;H317, Aquatic Chronic 1;I	H410	
Linalyl acetate		3 - 5	115-95-7 204-116-4	-	-	
	Classification: S	kin Irrit.	2;H315, Eye Irrit. 2;H3	319, Skin Sens. 1B;H317		
2,6-Dimethyl-7-octen	-2-ol	1 - 3	18479-58-8 242-362-4	-	-	
	Classification: S	kin Irrit.	2;H315, Eye Irrit. 2;H3	19		
Linalool		1 - 3	78-70-6 201-134-4	-	603-235-00-2	
	Classification: S	kin Irrit.	2;H315, Eye Irrit. 2;H3	319, Skin Sens. 1B;H317		
Acetic acid ethenyl es	ster	≤1	108-05-4 203-545-4	-	607-023-00-0	#
			. 2;H225, Acute Tox. 4 3;H335, Aquatic Chro	;H332;(ATE: 11 mg/l), Caro nic 3;H412	c. 2;H351,	
AHTN		≤1	21145-77-7 244-240-6	-	-	
		cute To: hronic 1		ng/kg bw), Aquatic Acute 1;	H400, Aquatic	
Benzoic acid, 2,4-dihydroxy-3,6-dim	nethyl-, methyl	≤ 1	4707-47-5 225-193-0	-	-	
ester						
	Classification: S	kin Sen				
	Classification: S	kin Sen ≤ 1			607-754-00-5	
ester		≤ 1	s. 1B;H317 118-58-1 204-262-9	- ;H317, Aquatic Chronic 3;F		
ester		≤ 1	s. 1B;H317 118-58-1 204-262-9	- ;H317, Aquatic Chronic 3;F -		

17CAR42 Version #: 01 Issue date: 06-April-2023

Chemical name	%	CAS-No. / EC No	b. REACH Registration No.	Index No. Notes
Coumarin	≤ 1	91-64-5 202-086-7	-	-
Classi	fication: Acute Tox	. 4;H302;(ATE: 500	mg/kg bw), Skin Sens. 1B;H	317
Cyclamen aldehyde	≤ 1	103-95-7 203-161-7	-	-
Classi	fication: Skin Irrit.	2;H315, Skin Sens.	1B;H317, Aquatic Chronic 3;	H412
Oils, lavandin	≤ 1	8022-15-9 617-009-6	-	-
Classif	fication: Eye Dam. Chronic 3		. 1B;H317, Asp. Tox. 1;H304	, Aquatic
Oils, lemon	≤ 1	8008-56-8 616-925-3	-	-
Classi			2;H315, Eye Irrit. 2;H319, Ski ox. 1;H304, Aquatic Chronic	
Oils, orange, sweet	≤ 1	8008-57-9 616-926-9	-	-
Classi		2;H225, Skin Irrit. 2	2;H315, Eye Irrit. 2;H319, Ski Juatic Chronic 2;H411	n Sens.
Pentyl-2-hydroxybenzoate	≤ 1	2050-08-0 218-080-2	-	-
Classif	fication: Acute Tox Chronic 1		mg/kg bw), Aquatic Acute 1;	H400, Aquatic
Phenol,	≤ 0,3	128-37-0	-	-
2,6-bis(1,1-dimethylethyl)-4-m Classi	nethyl- fication: Aquatic A	204-881-4 cute 1;H400, Aquati	c Chronic 1;H410	
Terpenes, orange oil	≤ 0,2	68647-72-3 614-678-6	-	-
Classi			2;H315, Skin Sens. 1;H317, <i>I</i> I11	Asp. Tox.
Other components below repo	ortable 82.83	· · · ·		
List of abbreviations and symbol ATE: Acute toxicity estimate. M: M-factor PBT: persistent, bioaccumular vPvB: very persistent and ver All concentrations are in perco substance has been assigned	tive and toxic subst y bioaccumulative s ent by weight unles	ance. substance. s ingredient is a ga:	s. Gas concentrations are in	percent by volume. #: This
Composition comments	The full text for a	I H-statements is di	splayed in section 16.	
SECTION 4: First aid meas	sures			
General information			ware of the material(s) involv ated clothing before reuse.	ed, and take precautions to
4.1. Description of first aid meas	sures			
Inhalation	Move to fresh air.	Call a physician if	symptoms develop or persist	
Skin contact			ediately and wash skin with s k medical attention and take	
Eye contact	Rinse with water.	Get medical attent	on if irritation develops and p	persists.
Ingestion	Rinse mouth. Ge	t medical attention i	f symptoms occur.	
4.2. Most important symptoms and effects, both acute and delayed	May cause an all	ergic skin reaction.	Dermatitis. Rash.	
4.3. Indication of any immediate medical attention and special treatment needed	Provide general s Symptoms may b		s and treat symptomatically.	Keep victim under observation.
SECTION 5: Firefighting m	neasures			

SECTION 5: Firefighting measures

General fire hazards

No unusual fire or explosion hazards noted.

5.1. Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged For non-emergency containers or spilled material unless wearing appropriate protective clothing. personnel Keep unnecessary personnel away. Ensure adequate ventilation. Local authorities should be For emergency responders advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all 6.2. Environmental precautions environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Prevent product from entering drains. Stop the flow of material, if this is without risk. Following 6.3. Methods and material for product recovery, flush area with water. containment and cleaning up 6.4. Reference to other For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS. sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).
7.3. Specific end use(s)	Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

```
Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001
```

Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	МАК	5 mg/m3	Inhalable dust.
	STEL	10 mg/m3	Inhalable dust.
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	МАК	10 mg/m3	
Austria. TRK List, OEL Ordinance	(GwV), BGBI. II, no. 184/2001		
Components	Туре	Value	
Acetic acid ethenyl ester (CAS 108-05-4)	TWA	17,600000000 014 mg/m3	0000
		5 ppm	
Belgium. Exposure Limit Values			
Components	Туре	Value	Form
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,200000000 028 mg/m3	0000
		10 ppm	
	TWA	17,600000000 014 mg/m3	0000
		5 ppm	

	Туре	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	TWA	2 mg/m3	Vapour and aerosol.
Bulgaria. OELs. Regulation No 13 on Components	protection of workers aga Type	nst risks of exposure to cher Value	nical agents at work
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,200000000 028 mg/m3	000
	TWA	10 ppm 17,600000000 014 mg/m3	000
		5 ppm	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	STEL	50 mg/m3	
	TWA	10 mg/m3	
Croatia. Dangerous Substance Expo Components	sure Limit Values in the Wo Type	orkplace (ELVs), Annexes 1 a Value	nd 2, Narodne Novine, 13/09
Acetic acid ethenyl ester (CAS 108-05-4)	MAC	17,600000000 014 mg/m3	000
	STEL	5 ppm 35,200000000 028 mg/m3	000
		10 ppm	
Carbon black (CAS 1333-86-4)	MAC	3,5 mg/m3	
	STEL	7 mg/m3	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	MAC	10 mg/m3	
Cyprus. OELs. Control of factory atm	osphere and dangerous si	ubstances in factories regulat	
Components	Type	Value	tion, PI 311/73, as amended.
Components Acetic acid ethenyl ester			tion, PI 311/73, as amended.
Components Acetic acid ethenyl ester	TWA	Value	tion, PI 311/73, as amended.
Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS	Туре	Value 30 mg/m3	tion, PI 311/73, as amended.
Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4)	TWA TWA	Value 30 mg/m3 10 ppm	tion, PI 311/73, as amended.
Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Czech Republic. OELs. Government	TWA TWA	Value 30 mg/m3 10 ppm	tion, PI 311/73, as amended.
Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Czech Republic. OELs. Government Components Acetic acid ethenyl ester	TWA TWA TWA Decree 361	Value 30 mg/m3 10 ppm 3,5 mg/m3	
Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Czech Republic. OELs. Government Components Acetic acid ethenyl ester	Type TWA TWA Decree 361 Type	Value 30 mg/m3 10 ppm 3,5 mg/m3 Value	
Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Czech Republic. OELs. Government Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS	Type TWA TWA Decree 361 Type Ceiling	Value 30 mg/m3 10 ppm 3,5 mg/m3 Value 36 mg/m3	
Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Czech Republic. OELs. Government Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Denmark. Exposure Limit Values	Type TWA TWA Decree 361 Type Ceiling TWA	Value 30 mg/m3 10 ppm 3,5 mg/m3 Value 36 mg/m3 18 mg/m3	Form
Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Czech Republic. OELs. Government Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Denmark. Exposure Limit Values Components Acetic acid ethenyl ester	Type TWA TWA Decree 361 Type Ceiling TWA TWA	Value 30 mg/m3 10 ppm 3,5 mg/m3 Value 36 mg/m3 18 mg/m3 10 mg/m3 Value 18 mg/m3 10 mg/m3	Form
Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Czech Republic. OELs. Government Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Denmark. Exposure Limit Values Components Acetic acid ethenyl ester (CAS 108-05-4)	Type TWA TWA Decree 361 Type Ceiling TWA TWA TWA TWA	Value 30 mg/m3 10 ppm 3,5 mg/m3 Value 36 mg/m3 18 mg/m3 10 mg/m3 Value 18 mg/m3 10 mg/m3 5 ppm	Form
Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Czech Republic. OELs. Government Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Denmark. Exposure Limit Values Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Carbon black (CAS 1333-86-4)	Type TWA TWA Decree 361 Type Ceiling TWA TWA TWA TUV	Value 30 mg/m3 10 ppm 3,5 mg/m3 Value 36 mg/m3 18 mg/m3 10 mg/m3 Value 36 mg/m3 18 mg/m3 10 mg/m3 5 ppm 3,5 mg/m3	Form
Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Czech Republic. OELs. Government Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS 1333-86-4) Denmark. Exposure Limit Values Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS Components Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS	Type TWA TWA Decree 361 Type Ceiling TWA TWA TWA TWA	Value 30 mg/m3 10 ppm 3,5 mg/m3 Value 36 mg/m3 18 mg/m3 10 mg/m3 Value 18 mg/m3 10 mg/m3 5 ppm	Form

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended Value Components Туре

Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,200000000000 028 mg/m3	
		10 ppm	
	TWA	17,600000000000 014 mg/m3	
		5 ppm	
Terpenes, orange oil (CAS 68647-72-3)	STEL	300 mg/m3	
		50 ppm	
	TWA	150 mg/m3	
		25 ppm	
Finland. Workplace Exposure Lim	nits		

Finland. Workplace Exposure Lim Components	its Type	Value	
Acetic acid ethenyl ester (CAS 108-05-4) Carbon black (CAS	STEL	35 mg/m3	
		10 ppm	
	TWA	18 mg/m3	
		5 ppm	
Carbon black (CAS 1333-86-4)	STEL	7 mg/m3	
	TWA	3,5 mg/m3	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	STEL	20 mg/m3	
	TWA	10 mg/m3	

France. OELs. Occupational Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended

Components	Туре	Value	
cetic acid ethenyl ester CAS 108-05-4)	VLE	35,200000000000 028 mg/m3	
		10 ppm	
	VME	17,600000000000 014 mg/m3	
		5 ppm	

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Туре	Value
Acetic acid ethenyl ester (CAS 108-05-4)	VLE	35,20000000000 028 mg/m3
Regulatory status:	Regulatory binding (VRC)	
		10 ppm
Regulatory status:	Regulatory binding (VRC)	
	VME	17,60000000000 014 mg/m3
Regulatory status:	Regulatory binding (VRC)	
		5 ppm
Regulatory status:	Regulatory binding (VRC)	
Carbon black (CAS 1333-86-4)	VME	3,5 mg/m3
Regulatory status:	Indicative limit (VL)	
Phenol, 2,6-bis(1,1-dimethylethyl) methyl- (CAS 128-37-0)	-4-	10 mg/m3
Regulatory status:	Indicative limit (VL)	
Germany. DFG MAK List in the Work Area (DFG)	t (advisory OELs). Commission for the I	nvestigation of Health Hazards of Chemical Compounds
Components	Туре	Value Form

Components	Туре	Value Form	
Acetic acid ethenyl ester	TWA	36 mg/m3	
(CAS 108-05-4)			

Components	Туре	Value	Form
		10 ppm	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	TWA	10 mg/m3	Vapor and aerosol inhalable fraction.
Germany. TRGS 900, Limit Values in the <i>l</i> Components	Ambient Air at the Workplace Type	Value	Form
Acetic acid ethenyl ester (CAS 108-05-4)	AGW	36 mg/m3	
		10 ppm	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	AGW	10 mg/m3	Inhalable fraction.
Greece. OELs (Decree No. 90/1999, as am	ended)		
Components	Туре	Value	
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,2000000000000 028 mg/m3	
	TWA	10 ppm 17,6000000000000 014 mg/m3	
		5 ppm	
Carbon black (CAS 1333-86-4)	STEL	7 mg/m3	
	TWA	3,5 mg/m3	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	TWA	10 mg/m3	
Hungary. OELs. Joint Decree on Chemica Components	ll Safety of Workplaces Type	Value	Form
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,2000000000000 028 mg/m3	
	TWA	17,6000000000000 014 mg/m3	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable dust.
Iceland. OELs. Regulation 154/1999 on oo Components	ccupational exposure limits Type	Value	
Acetic acid ethenyl ester (CAS 108-05-4)	TWA	30 mg/m3	
		10 ppm	
Carbon black (CAS 1333-86-4)	TWA	3,5 mg/m3	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	TWA	10 mg/m3	
Ireland. Occupational Exposure Limits Components	Туре	Value	Form
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,2000000000000 028 mg/m3 10 ppm	
	TWA	17,6000000000000 014 mg/m3	
Carbon black (CAS	TWA	5 ppm 3 mg/m3	Inhalable fraction.
1333-86-4)			

Italy. Occupational Exposure Limit Components	s Type	Value Form
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,20000000000 028 mg/m3
	TWA	10 ppm 17,60000000000 014 mg/m3
		5 ppm
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3 Inhalable fraction.
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	TWA	2 mg/m3 Inhalable fraction and vapour.
Latvia. OELs. Occupational expos Components	ure limit values of chemical s Type	ubstances in work environment Value
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,20000000000 028 mg/m3
	TWA	10 ppm 17,60000000000 014 mg/m3
		5 ppm
Lithuania. OELs. Limit Values for Components	Chemical Substances, Gener Type	al Requirements Value
Acetic acid ethenyl ester	STEL	35,20000000000
(CAS 108-05-4)		028 mg/m3
		10 ppm
	TWA	17,600000000000 014 mg/m3 5 ppm
Terpenes, orange oil (CAS	STEL	300 mg/m3
68647-72-3)	0122	50 ppm
	TWA	150 mg/m3
		25 ppm
Luxembourg. Binding Occupation Components	al exposure limit values (Ann Type	ex I), Memorial A Value
Acetic acid ethenyl ester	STEL	35,20000000000
(CAS 108-05-4)	STLL	028 mg/m3 10 ppm
	TWA	17,60000000000 014 mg/m3
		5 ppm
		Occupational Health and Safaty Authority Act (CAD 4
Schedules I and V)	·	
Schedules I and V)	ire Limit Values (L.N. 227. of Type	Value
Schedules I and V) Components Acetic acid ethenyl ester	·	Value 35,20000000000 028 mg/m3
Schedules I and V) Components Acetic acid ethenyl ester	Type STEL	Value 35,200000000000 028 mg/m3 10 ppm
Schedules I and V) Components Acetic acid ethenyl ester	Туре	Value 35,20000000000 028 mg/m3 10 ppm 17,6000000000 014 mg/m3
Schedules I and V) Components Acetic acid ethenyl ester (CAS 108-05-4)	Type STEL	Value 35,200000000000 028 mg/m3 10 ppm 17,60000000000
Schedules I and V) Components Acetic acid ethenyl ester (CAS 108-05-4) Netherlands. OELs (binding)	Type STEL	Value 35,20000000000 028 mg/m3 10 ppm 17,6000000000 014 mg/m3
Malta. OELs. Occupational Exposu Schedules I and V) Components Acetic acid ethenyl ester (CAS 108-05-4) Netherlands. OELs (binding) Components Acetic acid ethenyl ester (CAS 108-05-4)	Type STEL TWA	Value 35,200000000000 028 mg/m3 10 ppm 17,60000000000 014 mg/m3 5 ppm

Norway. Administrative Norms for	r Contaminants in the Workplace
Components	Type

Components	Туре	ype Value		Type Value	
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,20000000000 028 mg/m3			
		10 ppm			
	TLV	17,600000000000 014 mg/m3			
		5 ppm			
Carbon black (CAS 1333-86-4)	TLV	3,5 mg/m3			

Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 Value Form Components Type

components	Type	value	1 Onn
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	30 mg/m3	
	TWA	10 mg/m3	
Carbon black (CAS 1333-86-4)	TWA	4 mg/m3	Inhalable fraction.
		0 ppm	Inhalable fraction.
Portugal. OELs. Decree-Law n. 29	0/2001 (Journal of the Repub	lic - 1 Series A, n.266)	
Components	Туре	Value	
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,20000000 028 mg/m3	0000
		10 ppm	
	TWA	17,60000000 014 mg/m3	0000
		5 ppm	
Portugal. VLEs. Norm on occupati	ional exposure to chemical a	gents (NP 1796)	
Components	Туре	Value	Form
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	15 ppm	
	TWA	10 ppm	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Fume.
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapour.

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Туре	Value	
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,200000000000 028 mg/m3	
		10 ppm	
	TWA	17,600000000000 014 mg/m3	
		5 ppm	

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Components Value Type

Componente	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	T dido	
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,200000000000 028 mg/m3	
		10 ppm	
	TWA	17,600000000000 014 mg/m3	
		5 ppm	
Carbon black (CAS 1333-86-4)	TWA	2 mg/m3	

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Туре	Value	Form
Acetic acid ethenyl ester (CAS 108-05-4)	TWA	17,6000000000 014 mg/m3	000
		5 ppm	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	TWA	10 mg/m3	Inhalable fraction.
Spain. Occupational Exposure Limit	ts		
Components	Туре	Value	
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,2000000000 028 mg/m3	00
		10 ppm	
	TWA	17,6000000000 014 mg/m3	000
		5 ppm	
Carbon black (CAS 1333-86-4)	TWA	3,5 mg/m3	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	TWA	10 mg/m3	

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Туре	Value	Form
Acetic acid ethenyl ester (CAS 108-05-4)	Ceiling	35 mg/m3	
		10 ppm	
	TWA	18 mg/m3	
		5 ppm	
Carbon black (CAS 1333-86-4)	TWA	5 mg/m3	Inhalable dusts and mists.
		1 mg/m3	Inhalable dust.
Terpenes, orange oil (CAS 68647-72-3)	STEL	300 mg/m3	
		50 ppm	
	TWA	150 mg/m3	
		25 ppm	
Switzerland. SUVA Grenzwerte am	Arbeitsplatz		
Components	Туре	Value	Form
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35 mg/m3	
		10 ppm	
	TWA	35 mg/m3	
		10 ppm	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	STEL	40 mg/m3	Vapor and aerosol, inhalable.
	TWA	10 mg/m3	Vapor and aerosol, inhalable.
UK. EH40 Workplace Exposure Lir			
Components	Туре	Value	
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,200000000 028 mg/m3	0000
		10 ppm	
	TWA	17,600000000 014 mg/m3	0000
		5 ppm	
Carbon black (CAS 1333-86-4)	STEL	7 mg/m3	

	TWA	3,5 mg/m3	
Phenol, 2,6-bis(1,1-dimethylethyl)-4- methyl- (CAS 128-37-0)	TWA	10 mg/m3	
EU. Indicative Exposure Li Components	mit Values in Directives 91/32 Type	22/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU Value	
Acetic acid ethenyl ester (CAS 108-05-4)	STEL	35,20000000000 028 mg/m3	
	TWA	10 ppm 17,60000000000 014 mg/m3 5 ppm	
logical limit values	No biological exposure limit	s noted for the ingredient(s).	
commended monitoring cedures	Follow standard monitoring		
ived no effect levels IELs)	Not available.		
dicted no effect icentrations (PNECs)	Not available.		
oosure guidelines			
Germany DFG MAK (advise Acetic acid ethenyl este Germany TRGS 900 Limit	r (CAS 108-05-4)	Can be absorbed through the skin.	
Acetic acid ethenyl este Malta OELs: Skin designat	, ,	Can be absorbed through the skin.	
Acetic acid ethenyl este	r (CAS 108-05-4)	Can be absorbed through the skin.	
Exposure controls			
propriate engineering htrols	Good general ventilation should be used. Ventilation rates should be matched to conditions. applicable, use process enclosures, local exhaust ventilation, or other engineering controls t maintain airborne levels below recommended exposure limits. If exposure limits have not be established, maintain airborne levels to an acceptable level.		
ividual protection measures General information	s, such as personal protective equipment Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.		
Eye/face protection	Wear safety glasses with sid	de shields (or goggles). Face shield is recommended.	
Skin protection			
- Hand protection	Wear appropriate chemical	resistant gloves.	
- Other	Wear appropriate chemical	resistant clothing. Use of an impervious apron is recommended.	
Respiratory protection Thermal hazards		ation, wear suitable respiratory equipment. rotective clothing, when necessary.	
jiene measures	and before eating, drinking,	nal hygiene measures, such as washing after handling the materia and/or smoking. Routinely wash work clothing and protective minants. Contaminated work clothing should not be allowed out of	
vironmental exposure atrols	from ventilation or work proc requirements of environmer	orm appropriate managerial or supervisory personnel of all environmental releases. Emise n ventilation or work process equipment should be checked to ensure they comply with the uirements of environmental protection legislation. Fume scrubbers, filters or engineering difications to the process equipment may be necessary to reduce emissions to acceptable els.	

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Form	Solid.
Colour	Not available.
Odour	Not available.
Melting point/freezing point	3 °C (37,4 °F) estimated

Boiling point or initial boiling point and boiling range	Not available.	
Flammability	Not available.	
Flash point	>94 °C (>201,2 °F)	
Auto-ignition temperature	Not available.	
Decomposition temperature	Not available.	
рН	Not available.	
Kinematic viscosity	Not available.	
Solubility		
Solubility (water)	Not available.	
Partition coefficient (n-octanol/water) (log value)	Not available.	
Vapour pressure	0,000125 hPa estimated	
Density and/or relative density		
Density	0,9 g/cm3 estimated	
Vapour density	Not available.	
Particle characteristics	Not available.	
9.2. Other information		
9.2.1. Information with regard to physical hazard classes	No relevant additional information available.	
9.2.2. Other safety characteristic	CS	
Specific gravity	0,90025 estimated	
SECTION 10: Stability and	•	
10.1. Reactivity	The product is stable and non-reactive under norn	nal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.	
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of	
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Cor	ntact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.	
10.6. Hazardous decomposition products	No hazardous decomposition products are known	
SECTION 11: Toxicologica	al information	
General information	Occupational exposure to the substance or mixtur	e may cause adverse effects.
Information on likely routes of e	exposure	
Inhalation	Prolonged inhalation may be harmful.	
Skin contact	May cause an allergic skin reaction.	
Eye contact	Direct contact with eyes may cause temporary irrit	ation.
Ingestion	May cause discomfort if swallowed. However, inge occupational exposure.	
Symptoms	May cause an allergic skin reaction. Dermatitis. Ra	ash.
	ses as defined in Regulation (EC) No 1272/2008	
Acute toxicity		
Components	Species	Test Results
Acetic acid ethenyl ester (CAS 10	-	
Acute		
Dermal		
LD50	Rabbit	2335 mg/kg
Oral		
LD50	Rat	2920 mg/kg
Carbon black (CAS 1333-86-4)		
Acute		
Oral		
Oral LD50	Rat	> 8000 mg/kg

Skin corrosion/irritation

Due to partial or complete lack of data the classification is not possible.

Serious eye damage/eye irritation	Due to partia	l or complete lack	of data the classification	is not possible.
Respiratory sensitisation	Due to partia	Due to partial or complete lack of data the classification is not possible.		
Skin sensitisation	May cause a	May cause an allergic skin reaction.		
Germ cell mutagenicity	Due to partia	Due to partial or complete lack of data the classification is not possible.		
Carcinogenicity	Risk of cance	er cannot be exclu	ided with prolonged expo	sure.
Hungary. 26/2000 EüM Ordi (as amended)	nance on prot	ection against ar	nd preventing risk relati	ng to exposure to carcinogens at work
Acetic acid ethenyl ester IARC Monographs. Overall	•	,		
	3-86-4)) thylethyl)-4-me is concerning	thyl- protection of wo	3 Not classifiable as to o	
(Official Gazette of the Rep		•		
Acetic acid ethenyl ester			Carcinogenic, Category	
Reproductive toxicity	•	•	of data the classification	·
Specific target organ toxicity - single exposure	Due to partia	I or complete lack	of data the classification	i is not possible.
Specific target organ toxicity - repeated exposure	Due to partia	l or complete lack	of data the classification	is not possible.
Aspiration hazard	Due to partia	l or complete lack	of data the classification	is not possible.
Mixture versus substance information	No informatio	on available.		
11.2. Information on other haza	rds			
Endocrine disrupting properties	according to		(f) or regulation (EU) 20 ²	o have endocrine disrupting properties 17/2100 or Commission Regulation (EU)
Other information	Not available	·.	•	
SECTION 12: Ecological i	nformation			
C		4: - 1: 6		
12.1. Toxicity			quatic environment, acute	available data, the classification criteria are e hazard.
Components		Species		Test Results
Acetic acid ethenyl ester (CAS 10	8-05-4)			
Aquatic				
Acute				
Fish	LC50	Fathead minno	w (Pimephales promelas)15 mg/l, 96 hours
Coumarin (CAS 91-64-5)				
Aquatic				
Acute	1.050	Cuppy (Dessili		22 100 mg/l 06 hours
<i>Acute</i> Fish	LC50	Guppy (Poecilia	a reticulata)	32 - 100 mg/l, 96 hours
<i>Acute</i> Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic			a reticulata)	32 - 100 mg/l, 96 hours
<i>Acute</i> Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic <i>Acute</i>	-4-methyl- (CA	S 128-37-0)		
<i>Acute</i> Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic <i>Acute</i> Crustacea	I-4-methyl- (CA	S 128-37-0) Water flea (Dap	ohnia pulex)	1,44 mg/l, 48 hours
Acute Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic Acute Crustacea 12.2. Persistence and degradability	-4-methyl- (CA EC50 No data is av	S 128-37-0) Water flea (Dap		1,44 mg/l, 48 hours
Acute Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic Acute Crustacea 12.2. Persistence and	-4-methyl- (CA EC50 No data is av	S 128-37-0) Water flea (Dap	ohnia pulex)	1,44 mg/l, 48 hours
Acute Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic Acute Crustacea 12.2. Persistence and degradability 12.3. Bioaccumulative potential Partition coefficient	-4-methyl- (CA EC50 No data is av	S 128-37-0) Water flea (Dap	ohnia pulex)	1,44 mg/l, 48 hours
Acute Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic Acute Crustacea 12.2. Persistence and degradability 12.3. Bioaccumulative potential Partition coefficient n-octanol/water (log Kow)	-4-methyl- (CA EC50 No data is av	S 128-37-0) Water flea (Dap	ohnia pulex) radability of any ingredier	1,44 mg/l, 48 hours
Acute Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic Acute Crustacea 12.2. Persistence and degradability 12.3. Bioaccumulative potential Partition coefficient	-4-methyl- (CA EC50 No data is av	S 128-37-0) Water flea (Dap	ohnia pulex)	1,44 mg/l, 48 hours
Acute Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic Acute Crustacea 12.2. Persistence and degradability 12.3. Bioaccumulative potential Partition coefficient n-octanol/water (log Kow) 2,6-Dimethyl-7-octen-2-ol Acetic acid ethenyl ester AHTN	-4-methyl- (CA EC50 No data is av	S 128-37-0) Water flea (Dap ailable on the deg	ohnia pulex) radability of any ingredier 3,25 0,73 5,4	1,44 mg/l, 48 hours
Acute Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic Acute Crustacea 12.2. Persistence and degradability 12.3. Bioaccumulative potential Partition coefficient n-octanol/water (log Kow) 2,6-Dimethyl-7-octen-2-ol Acetic acid ethenyl ester AHTN Benzoic acid, 2,4-dihydroxy-3	-4-methyl- (CA EC50 No data is av	S 128-37-0) Water flea (Dap ailable on the deg	ohnia pulex) radability of any ingredier 3,25 0,73 5,4 2,6	1,44 mg/l, 48 hours
Acute Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic Acute Crustacea 12.2. Persistence and degradability 12.3. Bioaccumulative potential Partition coefficient n-octanol/water (log Kow) 2,6-Dimethyl-7-octen-2-ol Acetic acid ethenyl ester AHTN Benzoic acid, 2,4-dihydroxy-3 Benzyl salicylate	-4-methyl- (CA EC50 No data is av	S 128-37-0) Water flea (Dap ailable on the deg	ohnia pulex) radability of any ingredier 3,25 0,73 5,4 2,6 4	1,44 mg/l, 48 hours
Acute Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic Acute Crustacea 12.2. Persistence and degradability 12.3. Bioaccumulative potential Partition coefficient n-octanol/water (log Kow) 2,6-Dimethyl-7-octen-2-ol Acetic acid ethenyl ester AHTN Benzoic acid, 2,4-dihydroxy-3 Benzyl salicylate Coumarin Cyclamen aldehyde	-4-methyl- (CA EC50 No data is av	S 128-37-0) Water flea (Dap ailable on the deg	ohnia pulex) radability of any ingredier 3,25 0,73 5,4 2,6 4 1,39 3,4	1,44 mg/l, 48 hours
Acute Fish Phenol, 2,6-bis(1,1-dimethylethyl) Aquatic Acute Crustacea 12.2. Persistence and degradability 12.3. Bioaccumulative potential Partition coefficient n-octanol/water (log Kow) 2,6-Dimethyl-7-octen-2-ol Acetic acid ethenyl ester AHTN Benzoic acid, 2,4-dihydroxy-3 Benzyl salicylate Coumarin	-4-methyl- (CA EC50 No data is av	S 128-37-0) Water flea (Dap ailable on the deg	ohnia pulex) radability of any ingredier 3,25 0,73 5,4 2,6 4 1,39	1,44 mg/l, 48 hours

Linalyl acetate	3,9	
Pentyl-2-hydroxybenzoate Phenol, 2,6-bis(1,1-dimethylet	3,93 4,4 hyl)-4-methyl- 5,1 5,2	
Bioconcentration factor (BCF)	Not available.	
12.4. Mobility in soil	No data available.	
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances asses (EC) No 1907/2006, Annex XIII.	sed to be vPvB / PBT according to Regulation
12.6. Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.	
12.7. Other adverse effects	No other adverse environmental effects (e.g. ozo potential, endocrine disruption, global warming p	

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.


SECTION 14: Transport information

ADR

ADF	2	
	14.1. UN number	UN3077
	14.2. UN proper shipping	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	name	
	14.3. Transport hazard class	(es)
	Class	9
	Subsidiary risk	-
	Label(s)	9
	Hazard No. (ADR)	90
	Tunnel restriction code	E
	14.4. Packing group	III
	14.5. Environmental hazards	Yes
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
RID		
	14.1. UN number	UN3077
	14.2. UN proper shipping	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	name	
	14.3. Transport hazard class	(es)
	Class	9
	Subsidiary risk	-
	Label(s)	9
	14.4. Packing group	III
	14.5. Environmental hazards	Yes
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
ADN	1	
	14.1. UN number	UN3077
	14.2. UN proper shipping	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	name	
	14.3. Transport hazard class	(es)
	Class	9
	Subsidiary risk	-
	Label(s)	9

14.4. Packing group 14.5. Environmental hazards 14.6. Special precautions for user IATA	III Yes Read safety instructions, SDS and emergency procedures before handling.
14.1. UN number	Not regulated as dangerous goods.
14.2. UN proper shipping	Not regulated as dangerous goods.
name	
14.3. Transport hazard class	(es)
Class	Not assigned.
Subsidiary risk	-
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
14.6. Special precautions	Not assigned.
for user	
IMDG	
14.1. UN number	Not regulated as dangerous goods.
14.2. UN proper shipping name	Not regulated as dangerous goods.
14.3. Transport hazard class	(es)
Class	Not assigned.
Subsidiary risk	-
14.4. Packing group	Not assigned.
14.5. Environmental hazards	
Marine pollutant	No.
EmS	Not assigned.
14.6. Special precautions	Not assigned.
for user	
14.7. Maritime transport in bulk according to IMO instruments	Not applicable.

ADN; ADR; RID



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.
- Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Carbon black (CAS 1333-86-4)
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

UFI:

Austria: MV74-F393-600V-GS21 Belgium: MV74-F393-600V-GS21 Bulgaria: MV74-F393-600V-GS21 Croatia: MV74-F393-600V-GS21 Cyprus: MV74-F393-600V-GS21 Czech Republic: MV74-F393-600V-GS21 Denmark: MV74-F393-600V-GS21 Estonia: MV74-F393-600V-GS21 FU: MV74-F393-600V-GS21 Finland: MV74-F393-600V-GS21 France: MV74-F393-600V-GS21 Germany: MV74-F393-600V-GS21 Great Britain: MV74-F393-600V-GS21 Greece: MV74-F393-600V-GS21 Hungary: MV74-F393-600V-GS21 Iceland: MV74-F393-600V-GS21 Ireland: MV74-F393-600V-GS21 Italy: MV74-F393-600V-GS21 Latvia: MV74-F393-600V-GS21 Lithuania: MV74-F393-600V-GS21 Luxembourg: MV74-F393-600V-GS21 Malta: MV74-F393-600V-GS21 Netherlands: MV74-F393-600V-GS21 Norway: MV74-F393-600V-GS21 Poland: MV74-F393-600V-GS21 Portugal: MV74-F393-600V-GS21 Romania: MV74-F393-600V-GS21 Slovakia: MV74-F393-600V-GS21 Slovenia: MV74-F393-600V-GS21 Spain: MV74-F393-600V-GS21 Sweden: MV74-F393-600V-GS21

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Linalool (CAS 78-70-6)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Acetic acid ethenyl ester (CAS 108-05-4)

Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.
National regulations	Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.
15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
CAS: Chemical Abstract Service.
CEN: European Committee for Standardization.

References	 IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG: International Maritime Dangerous Goods. MAC: Maximum Allowed Concentration. MARPOL: International Convention for the Prevention of Pollution from Ships. PBT: Persistent, bioaccumulative and toxic. RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value. vPvB: Very persistent and very bioaccumulative. Not available.
Information on evaluation	The classification for health and environmental hazards is derived by a combination of calculation
method leading to the classification of mixture	methods and test data, if available.
Full text of any statements, which are not written out in full under sections 2 to 15	 H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.
Training information	Follow training instructions when handling this material.
Disclaimer	Home Fragrance Italia cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.