SAFETY DATA SHEET

Version #: 03

Issue date: 21-April-2023 Revision date: 19-October-2023 Supersedes date: 08-September-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

FRAGRANCE DIFFUSER 100ml - COLD WATER 7MDCW

of the mixture

Registration number

Synonyms None **Product code** 7MDCW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Air Care Products Uses advised against None known 1.3. Details of the supplier of the safety data sheet

Supplier

Company name Home Fragrance Italia S.r.L. Address Via del Commercio 28

Bernareggio (MB)

20881 IT

Division

Telephone

Not available. e-mail Not available. Contact person

1.4. Emergency telephone

number

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons Information Centre

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons Control Centre

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

Toxicological Information Centre

available for the Emergency Service.)

Czech Republic National Poisons Information Centre

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons Control Centre

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Estonia National Poisons Information Centre

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Centre

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Centre

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Hungary National Emergency Phone Number

36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus +370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

1.4. Emergency telephone number

Malta Accident and **Emergency Department** 2545 4030 (Hours of operation not provided. SDS/Product information may not be

available for the Emergency Service.)

Netherlands National Poisons Information Centre (NVIC)

030-274 88 88 (Only for the purpose of informing medical personnel in cases of

acute intoxications)

Norway Norwegian Poison

Information Centre

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Portugal Poison Centre 800 250 250 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

available for the Emergency Service.)

Slovakia National **Toxicological Information**

Centre

+421 2 5477 4166 (Available 24 hours a day, SDS/Product information may not be available for the Emergency Service.)

Sweden National Poison 112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

Information Centre Switzerland Tox Info information may not be available for the Emergency Service.) 145 (Available 24 hours a day, SDS/Product information may not be available for

Suisse the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids Category 2 H225 - Highly flammable liquid and

vapour.

Health hazards

Serious eye damage/eye irritation H319 - Causes serious eye Category 2

irritation.

Skin sensitisation Category 1B H317 - May cause an allergic skin

reaction.

Environmental hazards

Hazardous to the aquatic environment,

long-term aquatic hazard

Category 3

H412 - Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

1,6-Nonadien-3-ol, 3,7-dimethyl-, Citral, Citrus Aurantium Dulcis Flower Extract, Cyclamen Contains:

aldehyde, Isocyclemone E, Linalool, Linalyl acetate, Oils, cedarwood, Oils, geranium, Oils,

lavandin, Oils, lime, Oils, rosemary

Hazard pictograms





Signal word Danger

Hazard statements

Highly flammable liquid and vapour. H225 May cause an allergic skin reaction. H317 Causes serious eye irritation. H319

Harmful to aquatic life with long lasting effects. H412

Precautionary statements

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Keep out of reach of children. P102

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing.

If skin irritation or rash occurs: Ğet medical advice/attention. P333 + P313 If eye irritation persists: Get medical advice/attention. P337 + P313

IF ON SKIN: Wash with plenty of water. P302 + P352

Storage Not applicable.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or

Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	. REACH Registration No	o. Index No.	Notes
Ethanol	80 - 90	64-17-5 200-578-6	-	603-002-00-5	
Classific	ation: Flam. Liq.	2;H225, Eye Irrit. 2;I	H319		
1-Butanol, 3-methoxy-3-methyl-	3 - 5	56539-66-3 260-252-4	-	-	
Classific	ation: Eye Irrit. 2	;H319			
2,6-Dimethyl-7-octen-2-ol	3 - 5	18479-58-8 242-362-4	-	-	
Classific	ation: Skin Irrit. 2	2;H315, Eye Irrit. 2;H	319		
1,4-Dioxacyclohexadecane-5,16 e	6-dion ≤ 1	54982-83-1 259-423-6	-	-	
Classific	ation: Aquatic A	cute 1;H400(M=1), A	quatic Chronic 3;H412		
1,6-Nonadien-3-ol, 3,7-dimethyl	- ≤1	10339-55-6 233-732-6	-	-	
Classific	ation: Eye Irrit. 2	;H319, Skin Sens. 1	B;H317		
AHTN	≤ 1	21145-77-7 244-240-6	-	-	
Classific		. 4;H302;(ATE: 500 r hronic 1;H410(M=1)	ng/kg bw), Aquatic Acute 1	;H400(M=1),	
Citrus Aurantium Dulcis Flower Extract	≤ 1	8028-48-6 232-433-8	-	-	
Classific			H315, Eye Irrit. 2;H319, Sk uatic Chronic 2;H411	kin Sens.	
Isocyclemone E	≤ 1	54464-57-2 259-174-3	-	-	
Classific	ation: Skin Irrit. 2	2;H315, Skin Sens. 1	B;H317, Aquatic Chronic 2	2;H411	
Oils, lavandin	≤ 1	8022-15-9 617-009-6	-	-	
Classific	ation: Eye Dam. Chronic 3;		1B;H317, Asp. Tox. 1;H30	4, Aquatic	
Citral	≤ 0,3	5392-40-5 226-394-6	-	605-019-00-3	
Classific	ation: Skin Irrit. 2	2;H315, Eye Irrit. 2;H	319, Skin Sens. 1;H317		
Cyclamen aldehyde	≤ 0,2	103-95-7 203-161-7	01-2119970582-32	-	
Classific	ation: Skin Irrit. 2	2;H315, Skin Sens. 1	B;H317, Aquatic Chronic 3	3;H412	
Linalool	≤ 0,2	78-70-6 201-134-4	01-2119474016-42	603-235-00-2	
Classific	ation: Skin Irrit. 2	2;H315, Eye Irrit. 2;H	319, Skin Sens. 1B;H317		
Linalyl acetate	≤ 0,2	115-95-7 204-116-4	-	-	
Classific	ation: Skin Irrit. 2	2;H315, Eye Irrit. 2;H	319, Skin Sens. 1B;H317		
Oils, cedarwood	≤ 0,2	8000-27-9 616-769-6	-	-	
Classific	ation: Skin Irrit. 2 Chronic 2		B;H317, Asp. Tox. 1;H304	, Aquatic	

Chemical name		%	CAS-No. / EC N	o. REACH Registration N	lo. Index No.	Notes
Oils, geranium		≤ 0,2	8000-46-2 616-774-3	-	-	
	Classification:	Skin Irrit. 2 Chronic 2;		1;H318, Skin Sens. 1;H317	, Aquatic	
Oils, lime		≤ 0,2	8008-26-2 616-919-0	-	-	
	Classification:			2;H315, Eye Irrit. 2;H319, S Tox. 1;H304, Aquatic Chron		
Oils, rosemary		≤ 0,2	8000-25-7 616-767-5	-	-	
	Classification:			2;H315, Eye Irrit. 2;H319, S .sp. Tox. 1;H304, Aquatic C		
Other components	below reportable	3.64				

Other components below reportable levels

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. #: This substance has been assigned Union workplace exposure limit(s).

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

- 1

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Highly flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

so without risk.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

1000 mg/m3

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Ethanol (CAS 64-17-5)

Components	Туре	Value	
Ethanol (CAS 64-17-5)	Ceiling	3800 mg/m3	
		2000 ppm	
	MAK	1900 mg/m3	
		1000 ppm	
Belgium. Exposure Limit Values Components	Туре	Value	Form
Citral (CAS 5392-40-5)	TWA	32 mg/m3	Vapour and aerosol.
		5 ppm	Vapour and aerosol.
		э ррпп	vapour and acrosor.
Ethanol (CAS 64-17-5)	TWA	3 ррт 1907 mg/m3	vapour and aerosor.

TWA

Components		Туре	Value	
Ethanol (CAS 64-17-5)		MAC	1900 mg/m3	
			1000 ppm	
Czech Republic. OELs.				
Components		Туре	Value	
1-Butanol,	6	Ceiling	200 mg/m3	
3-methoxy-3-methyl- (CA: 56539-66-3)	5			
,		TWA	100 mg/m3	
Ethanol (CAS 64-17-5)		Ceiling	3000 mg/m3	
		TWA	1000 mg/m3	
Denmark. Exposure Lim	nit Values			
Components		Туре	Value	
Ethanol (CAS 64-17-5)		TLV	1900 mg/m3	
			1000 ppm	
Estonia. OELs. Occupat	ional Exposure Lin	nits of Hazardous Sul	ostances (Regulation No. 105/2	2001, Annex), as amen
Components	•	Туре	Value	-
Ethanol (CAS 64-17-5)		STEL	1900 mg/m3	
			1000 ppm	
		TWA	1000 mg/m3	
			500 ppm	
Finland. Workplace Exp	osure Limits			
Components		Туре	Value	
Ethanol (CAS 64-17-5)		STEL	2500 mg/m3	
			1300 ppm	
		TWA	1900 mg/m3	
			1000 ppm	
France. Threshold Limit	Values (VLEP) for	Occupational Exposu	ure to Chemicals in France, IN	RS ED 984
Components		Туре	Value	
Ethanol (CAS 64-17-5)		VLE	9500 mg/m3	
Regulatory status:	Indicative limit (VL)		
			5000 ppm	
Regulatory status:	Indicative limit (VL)		
		VME	1900 mg/m3	
Regulatory status:	Indicative limit (VL	.)	4000	
	Indicative limit (\/I	\	1000 ppm	
Pogulatory status:	Indicative limit (VL	•	woodination of Health Hearth	of Chamical Carre
Regulatory status:		commission for the li	ivestigation of Health Hazards	or Chemical Compou
Germany. DFG MAK List	i (auvisory UELS).			
Germany. DFG MAK List in the Work Area (DFG)		Туре	Value	Form
Germany. DFG MAK List in the Work Area (DFG) Components		Type TWA	Value 380 mg/m3	Form
-				Form
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS			380 mg/m3	Form Vapor and aerosol,
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS		TWA	380 mg/m3 200 ppm	
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin	mit Values in the Ar	TWA TWA mbient Air at the Worl	380 mg/m3 200 ppm 100 mg/m3 kplace	Vapor and aerosol, inhalable fraction.
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components	mit Values in the Ar	TWA TWA mbient Air at the Worl	380 mg/m3 200 ppm 100 mg/m3 kplace Value	Vapor and aerosol,
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components	mit Values in the Ar	TWA TWA mbient Air at the Worl	380 mg/m3 200 ppm 100 mg/m3 kplace Value 380 mg/m3	Vapor and aerosol, inhalable fraction.
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5)	mit Values in the Ar	TWA TWA mbient Air at the Worl	380 mg/m3 200 ppm 100 mg/m3 kplace Value	Vapor and aerosol, inhalable fraction.

Components	Туре	Value	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Hungary. OELs. Joint Decree on Ch	nemical Safety of Workplaces		
Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	3800 mg/m3	
	TWA	1900 mg/m3	
Iceland. OELs. Regulation 154/1999 Components		nits Value	
	Type		
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Ireland. Occupational Exposure Lin Components	nits Type	Value	Form
Citral (CAS 5392-40-5)	TWA	5 ppm	Inhalable fraction and vapour.
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
Italy. Occupational Exposure Limits	5		
Components	Туре	Value	Form
Citral (CAS 5392-40-5)	TWA	5 ppm	Inhalable fraction and vapour.
Ethanol (CAS 64-17-5)	STEL	1000 ppm	vapour.
Latvia. OELs. Occupational exposu	re limit values of chemical su	bstances in work environme	nt
Components	Туре	Value	
Ethanol (CAS 64-17-5)	TWA	1000 mg/m3	
Lithuania. OELs. Limit Values for C	Chemical Substances, Genera	I Requirements	
	Chemical Substances, Genera Type	l Requirements Value	
Components		· · · · · · · · · · · · · · · · · · ·	
Components	Туре	Value 1900 mg/m3 1000 ppm	
Components	Туре	Value 1900 mg/m3	
Components	Type STEL	Value 1900 mg/m3 1000 ppm	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding)	Type STEL TWA	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components	Type STEL TWA Type	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components	Type STEL TWA Type STEL	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components	Type STEL TWA Type	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components Ethanol (CAS 64-17-5) Norway. Administrative Norms for C	Type STEL TWA Type STEL TWA Contaminants in the Workplace	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3 260 mg/m3	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components Ethanol (CAS 64-17-5) Norway. Administrative Norms for Components	Type STEL TWA Type STEL TWA TWA Contaminants in the Workplace Type	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3 260 mg/m3	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components Ethanol (CAS 64-17-5) Norway. Administrative Norms for Components	Type STEL TWA Type STEL TWA Contaminants in the Workplace	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3 260 mg/m3 260 mg/m3 re Value 950 mg/m3	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components Ethanol (CAS 64-17-5) Norway. Administrative Norms for Components	Type STEL TWA Type STEL TWA TWA Contaminants in the Workplace Type	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3 260 mg/m3	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components Ethanol (CAS 64-17-5) Norway. Administrative Norms for Components Ethanol (CAS 64-17-5) Poland. Ordinance of the Minister of	Type STEL TWA Type STEL TWA Contaminants in the Workplace Type TLV of Labour and Social Policy or	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3 260 mg/m3 260 mg/m3 500 ppm 950 mg/m3 500 ppm	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components Ethanol (CAS 64-17-5) Norway. Administrative Norms for Components Ethanol (CAS 64-17-5) Poland. Ordinance of the Minister of concentrations and intensities of here	Type STEL TWA Type STEL TWA Contaminants in the Workplace Type TLV of Labour and Social Policy or armful health factors in the w	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3 260 mg/m3 260 mg/m3 500 ppm 950 mg/m3 500 ppm	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components Ethanol (CAS 64-17-5) Norway. Administrative Norms for Components Ethanol (CAS 64-17-5) Poland. Ordinance of the Minister of concentrations and intensities of his Components	Type STEL TWA Type STEL TWA Contaminants in the Workplac Type TLV of Labour and Social Policy or armful health factors in the w Type	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3 260 mg/m3 260 mg/m3 500 ppm 16 June 2014 on the maximulork environment, Journal of Value	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components Ethanol (CAS 64-17-5) Norway. Administrative Norms for Components Ethanol (CAS 64-17-5) Poland. Ordinance of the Minister of concentrations and intensities of his Components	Type STEL TWA Type STEL TWA Contaminants in the Workplace Type TLV of Labour and Social Policy or armful health factors in the w Type STEL	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3 260 mg/m3 260 mg/m3 500 ppm 4 6 June 2014 on the maximu ork environment, Journal of Value 54 mg/m3	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components Ethanol (CAS 64-17-5) Norway. Administrative Norms for Components Ethanol (CAS 64-17-5) Poland. Ordinance of the Minister of concentrations and intensities of his Components Citral (CAS 5392-40-5)	Type STEL TWA Type STEL TWA Contaminants in the Workplace Type TLV of Labour and Social Policy or armful health factors in the w Type STEL TWA	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3 260 mg/m3 260 mg/m3 500 ppm 4 6 June 2014 on the maximulork environment, Journal of Value 54 mg/m3 27 mg/m3	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components Ethanol (CAS 64-17-5) Norway. Administrative Norms for Components Ethanol (CAS 64-17-5) Poland. Ordinance of the Minister of concentrations and intensities of he Components Citral (CAS 5392-40-5) Ethanol (CAS 64-17-5)	Type STEL TWA Type STEL TWA Contaminants in the Workplace Type TLV of Labour and Social Policy or armful health factors in the water to the water	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3 260 mg/m3 260 mg/m3 500 ppm 16 June 2014 on the maximu ork environment, Journal of Value 54 mg/m3 27 mg/m3 1900 mg/m3	
Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components Ethanol (CAS 64-17-5) Norway. Administrative Norms for Components Ethanol (CAS 64-17-5) Poland. Ordinance of the Minister of concentrations and intensities of he Components Citral (CAS 5392-40-5) Ethanol (CAS 64-17-5) Portugal. VLEs. Norm on occupation	Type STEL TWA Type STEL TWA Contaminants in the Workplace Type TLV of Labour and Social Policy or armful health factors in the water to the water	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3 260 mg/m3 260 mg/m3 500 ppm 16 June 2014 on the maximu ork environment, Journal of Value 54 mg/m3 27 mg/m3 1900 mg/m3	
Lithuania. OELs. Limit Values for Components Ethanol (CAS 64-17-5) Netherlands. OELs (binding) Components Ethanol (CAS 64-17-5) Norway. Administrative Norms for Components Ethanol (CAS 64-17-5) Poland. Ordinance of the Minister of concentrations and intensities of his Components Citral (CAS 5392-40-5) Ethanol (CAS 64-17-5) Portugal. VLEs. Norm on occupation Components Citral (CAS 5392-40-5)	Type STEL TWA Type STEL TWA Contaminants in the Workplace Type TLV of Labour and Social Policy or armful health factors in the w Type STEL TWA TWA TWA TWA TWA TOTAL	Value 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm Value 1900 mg/m3 260 mg/m3 260 mg/m3 500 ppm Value 950 mg/m3 500 ppm a 6 June 2014 on the maximulork environment, Journal of Value 54 mg/m3 27 mg/m3 1900 mg/m3	Laws 2014, item 817

Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	9500 mg/m3	
		5000 ppm	
	TWA	1900 mg/m3	
		1000 ppm	
Slovakia. OELs. Regulation Components	n No. 300/2007 concerning protectior Type	of health in work with chemi Value	cal agents
Ethanol (CAS 64-17-5)	STEL	1920 mg/m3	
		1000 ppm	
	TWA	960 mg/m3	
		500 ppm	
(Official Gazette of the Rep	·		
Components	Туре	Value	Form
Ethanol (CAS 64-17-5)	TWA	960 mg/m3	
		500 ppm	
Propanol, oxybis- (CAS 25265-71-8)	TWA	100 mg/m3	Inhalable fraction.
Spain. Occupational Expos Components	sure Limits Type	Value	Form
Citral (CAS 5392-40-5)	TWA	5 ppm	Inhalable fraction and vapour.
Ethanol (CAS 64-17-5)	STEL	1910 mg/m3	
		1000 ppm	
Sweden. OELs. Work Envil Components	ronment Authority (AV), Occupationa Type	l Exposure Limit Values (AFS Value	2015:7)
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3	
		3	
		1000 ppm	
	TWA	•	
	TWA	1000 ppm	
Switzerland. SUVA Grenzw		1000 ppm 1000 mg/m3	
Switzerland. SUVA Grenzw Components		1000 ppm 1000 mg/m3	Form
	verte am Arbeitsplatz	1000 ppm 1000 mg/m3 500 ppm	Form
Components	verte am Arbeitsplatz Type	1000 ppm 1000 mg/m3 500 ppm Value	Form
Components	verte am Arbeitsplatz Type	1000 ppm 1000 mg/m3 500 ppm Value 1920 mg/m3	Form
Components	verte am Arbeitsplatz Type STEL	1000 ppm 1000 mg/m3 500 ppm Value 1920 mg/m3 1000 ppm	Form
Components	verte am Arbeitsplatz Type STEL	1000 ppm 1000 mg/m3 500 ppm Value 1920 mg/m3 1000 ppm 960 mg/m3	Form Vapor and aerosol, inhalable.
Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS	verte am Arbeitsplatz Type STEL TWA	1000 ppm 1000 mg/m3 500 ppm Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm	Vapor and aerosol,
Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS	verte am Arbeitsplatz Type STEL TWA STEL TWA	1000 ppm 1000 mg/m3 500 ppm Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm 280 mg/m3	Vapor and aerosol, inhalable. Vapor and aerosol,
Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) UK. EH40 Workplace Expo	verte am Arbeitsplatz Type STEL TWA STEL TWA STEL TWA STEL TWA	1000 ppm 1000 mg/m3 500 ppm Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm 280 mg/m3 140 mg/m3	Vapor and aerosol, inhalable. Vapor and aerosol,
Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) UK. EH40 Workplace Expo Components	verte am Arbeitsplatz Type STEL TWA STEL TWA STEL TWA STEL TWA PSUITE Limits (WELS) Type	1000 ppm 1000 mg/m3 500 ppm Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm 280 mg/m3 140 mg/m3	Vapor and aerosol, inhalable. Vapor and aerosol,
Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) UK. EH40 Workplace Expo Components Ethanol (CAS 64-17-5)	verte am Arbeitsplatz Type STEL TWA STEL TWA esure Limits (WELs) Type TWA	1000 ppm 1000 mg/m3 500 ppm Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm 280 mg/m3 140 mg/m3 Value 1920 mg/m3 1000 ppm	Vapor and aerosol, inhalable. Vapor and aerosol,
Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) UK. EH40 Workplace Expo Components	verte am Arbeitsplatz Type STEL TWA STEL TWA STEL TWA STEL TWA PSUITE Limits (WELS) Type	1000 ppm 1000 mg/m3 500 ppm Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm 280 mg/m3 140 mg/m3 Value 1920 mg/m3 1000 ppm 1900 mg/m3 1000 ppm	Vapor and aerosol, inhalable. Vapor and aerosol,
Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) UK. EH40 Workplace Expo Components Ethanol (CAS 64-17-5) ogical limit values ommended monitoring	verte am Arbeitsplatz Type STEL TWA STEL TWA osure Limits (WELs) Type TWA No biological exposure limits noted in	1000 ppm 1000 mg/m3 500 ppm Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm 280 mg/m3 140 mg/m3 Value 1920 mg/m3 1000 ppm 1900 mg/m3 1000 ppm	Vapor and aerosol, inhalable. Vapor and aerosol,

Exposure guidelines

Belgium OELs: Skin designation

Citral (CAS 5392-40-5)

Can be absorbed through the skin.

Italy OELs: Skin designation

Citral (CAS 5392-40-5) Danger of cutaneous absorption

Netherlands OELs (binding): Skin designation

Ethanol (CAS 64-17-5)

Can be absorbed through the skin.

Portugal VLEs Norm on Occupational Exposure: Skin designation

Citral (CAS 5392-40-5)

Can be absorbed through the skin.

Spain OELs: Skin designation

Citral (CAS 5392-40-5)

Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an

acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General informationUse personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquid.FormLiquid.ColourNot available.OdourNot available.

Melting point/freezing point -114,1 °C (-173,38 °F) estimated

Boiling point or initial boiling 78,29 °C (172,92 °F) estimated point and boiling range

Flammability Not applicable.

Flash point 13 °C (55,4 °F) estimated

Auto-ignition temperature 363 °C (685,4 °F) estimated

Decomposition temperatureNot available.pHNot available.Kinematic viscosityNot available.

Solubility

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water) (log value)

Vapour pressure 79,06 hPa estimated

Density and/or relative density

Density 0,801 g/cm3 estimated

Vapour density Not available.

Particle characteristics Not available.

9.2. Other information

9.2.1. Information with regard No relevant

to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

Percent volatile 86,73 % estimated Specific gravity 0,80079 estimated VOC 86,49 % estimated

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous

No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Coughing. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not known.

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitisationDue to partial or complete lack of data the classification is not possible.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicityDue to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

repeated exposure

Aspiration hazard

Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other information Not available.

SECTION 12: Ecological information

Harmful to aquatic life with long lasting effects. Based on available data, the classification criteria

are not met for hazardous to the aquatic environment, acute hazard.

Components Species Test Results

Ethanol (CAS 64-17-5)

12.1. Toxicity

Aquatic Acute

EC50 Crustacea Water flea (Daphnia magna) 7,7 - 11,2 mg/l, 48 hours

Fish LC50 Rainbow trout.donaldson trout 42 mg/l. 4 days

(Oncorhynchus mykiss)

12.2. Persistence and

No data is available on the degradability of any ingredients in the mixture.

degradability

12.3. Bioaccumulative potential

Partition coefficient

n-octanol/water (log Kow)

1,4-Dioxacyclohexadecane-5,16-dione 1,6-Nonadien-3-ol, 3,7-dimethyl- 2,6-Dimethyl-7-octen-2-ol AHTN Citral	3,65 3,3 3,25 5,4 2,76 3.45
Citrus Aurantium Dulcis Flower Extract Cyclamen aldehyde Ethanol Linalool Linalyl acetate	3,43 4,38 3,4 -0,31 2,97 3,9 3.93
Oils, cedarwood Oils, geranium Oils, rosemary	6,12 3,5 6,23

Bioconcentration factor (BCF)

Not available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation potential.

12.8. Additional information

Estonia Dangerous substances in soil Data

Ethanol (CAS 64-17-5) Chemical pesticides (As the total sum of the active substances)

0,5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20

mg/kg

Chemical pesticides (As the total sum of the active substances) 5

mg/kg

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

The Waste code should be assigned in discussion between the user, the producer and the waste EU waste code

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow Disposal methods/information

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

Material name: FRAGRANCE DIFFUSER 100ml - COLD WATER 7MDCW 7MDCW Version #: 03 Revision date: 19-October-2023 Issue date: 21-April-2023

SECTION 14: Transport information

```
ADR
```

14.1. UN number UN1170 ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) 14.2. UN proper shipping (Ethanol) name 14.3. Transport hazard class(es) Class 3 Subsidiary risk 3 Label(s) 33 Hazard No. (ADR) **Tunnel restriction code** D/E Ш 14.4. Packing group 14.5. Environmental hazards No. 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user **RID** 14.1. UN number UN1170 14.2. UN proper shipping ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) name (Ethanol) 14.3. Transport hazard class(es) 3 Class Subsidiary risk 3 Label(s) 14.4. Packing group Ш 14.5. Environmental hazards No. Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user ADN 14.1. UN number UN1170 14.2. UN proper shipping ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) name (Ethanol) 14.3. Transport hazard class(es) 3 Class Subsidiary risk 3 Label(s) 14.4. Packing group П 14.5. Environmental hazards No. 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user IATA 14.1. UN number UN1170 Ethanol solution (Ethanol) 14.2. UN proper shipping name 14.3. Transport hazard class(es) Class 3 Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards No. **ERG Code** 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user Other information Allowed with restrictions. Passenger and cargo aircraft Cargo aircraft only Allowed with restrictions. **IMDG** UN1170 14.1. UN number ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) 14.2. UN proper shipping (Ethanol), MARINE POLLUTANT 14.3. Transport hazard class(es) **Class** 3 Subsidiary risk 14.4. Packing group Ш 14.5. Environmental hazards Yes Marine pollutant F-E. S-D **EmS**

14.6. Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk according to IMO instruments

Not established.

ADN; ADR; IATA; IMDG; RID



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Ethanol (CAS 64-17-5)

Linalool (CAS 78-70-6)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended Ethanol (CAS 64-17-5)

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as

amended

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

Not available.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H371 May cause damage to organs.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

Revision information

Training information

None.

Disclaimer

Follow training instructions when handling this material.

Home Fragrance Italia S.r.L. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.