SAFETY DATA SHEET



Version #: 03

Issue date: 23-May-2022 Revision date: 14-October-2022 Supersedes date: 10-June-2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

FRAGRANCE FOR DIFFUSER 250ml MELA & CANNELLA

Registration number

Synonyms None.

Product code 7REMMC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses General Public Use
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name Home Fragrance Italia **Address** Via A. Tonale 26

Milano 20125 IT

Division

Telephone

e-mail Not available.

Contact person Not available.

1.4. Emergency telephone

number

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons Information Centre +431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National Toxicological Information

Centre

0

+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Czech Republic National Poisons Information

Centre

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons Control Center +45 82 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons Information Centre

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Hungary National Emergency Phone Number 36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and Emergency Department 2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Material name: FRAGRANCE FOR DIFFUSER 250ml MELA & CANNELLA

7REMMC Version #: 03 Revision date: 14-October-2022 Issue date: 23-May-2022

1.4. Emergency telephone number

Netherlands National Poisons Information Center (NVIC)

030-274 88 88 (Only for the purpose of informing medical personnel in cases of

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Portugal Poison Centre 800 250 250 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

available for the Emergency Service.)

Slovakia National

Toxicological Information Centre

+421 2 5477 4166 (Available 24 hours a day, SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info 145 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.) Suisse

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids H225 - Highly flammable liquid and Category 2

vapour.

Health hazards

Serious eye damage/eye irritation H319 - Causes serious eye Category 2

irritation.

Skin sensitisation Category 1A H317 - May cause an allergic skin

reaction.

Environmental hazards

Hazardous to the aquatic environment, Category 3 H412 - Harmful to aquatic life with long-term aquatic hazard

long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

alpha-Pinene, beta-Pinene, Cinnamal, Citral, Citrus Aurantium Dulcis Flower Extract, Coumarin, Contains:

Eugenol, Methyl cinnamate, Methylcinnamic aldehyde, Oils, clove, Oils, lemon

Hazard pictograms



Signal word Danger

Hazard statements

Highly flammable liquid and vapour. H225 May cause an allergic skin reaction. H317 Causes serious eye irritation. H319

Harmful to aquatic life with long lasting effects. H412

Precautionary statements

Prevention

Keep out of reach of children. P102

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Keep container tightly closed. P233

Response

IF ON SKIN: Wash with plenty of water. P302 + P352

If skin irritation or rash occurs: Get medical advice/attention. P333 + P313

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. P337 + P313

Storage

Store in a well-ventilated place. P403

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

None.

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

| Chemical name | | % | | o. REACH Registr | | Notes |
|--|----------------------------|----------------------------|---|--|--|-------|
| Ethanol | | 80 - 90 | 64-17-5 200-578-6 | - | 603-002-00-5 | |
| | Classification: | Flam. Liq. | 2;H225, Eye Irrit. 2 | :H319 | | |
| Methylcinnamic aldeh | yde | 3 - 5 | 101-39-3 202-938-8 | - | - | |
| | Classification: | Skin Sens | . 1B;H317 | | | |
| Propanol, 1(or 2)-(2-methoxymethyle | thoxy)- Classification: | 3 - 5 | 34590-94-8 252-104-2 | - | - | # |
| Benzyl alcohol | Classification. | 1 - 3 | 100-51-6 202-859-9 | - | 603-057-00-5 | |
| | | Acute Tox Eye Irrit. 2 | . 4;H302;(ATE: 500 | mg/kg), Acute Tox. | 4;H332;(ATE: 11 mg/l), | |
| Eugenol | | 1 - 3 | 97-53-0 202-589-1 | - | - | |
| | | Eye Irrit. 2 Chronic 4; | 2;H319, Skin Sens. :H413 | 1;H317, Asp. Tox. 1 | ;H304, Aquatic | |
| Vanillin | | 1 - 3 | 121-33-5 204-465-2 | - | - | |
| | Classification: | Eye Irrit. 2 | ;H319 | | | |
| Cinnamal | | ≤ 1 | 104-55-2 203-213-9 | - | - | |
| | Classification: | Acute Tox 2;H319, S | . 4;H312;(ATE: 1100 kin Sens. 1A;H317, |) mg/kg), Skin Irrit. Aquatic Chronic 3;l | 2;H315, Eye Irrit. H412 | |
| Citrus Aurantium Dulc Extract | is Flower | ≤ 1 | 8028-48-6 232-433-8 | - | - | |
| | | | 2;H225, Skin Irrit. 2 sp. Tox. 1;H304, Aq | | | |
| Coumarin | | ≤ 1 | 91-64-5 202-086-7 | - | - | |
| | Classification: | Acute Tox | . 4;H302;(ATE: 500 | mg/kg), Skin Sens. | 1B;H317 | |
| Oils, clove | | ≤ 1 | 8000-34-8 616-772-2 | - | - | |
| | Classification: | Eye Irrit. 2 | ;H319, Skin Sens. | 1B;H317, Asp. Tox. | 1;H304 | |
| Oils, lemon | | ≤ 1 | 8008-56-8 616-925-3 | - | - | |
| | | | 2;H225, Skin Irrit. 2 epr. 2;H361, Asp. T | | | |
| alpha-Pinene | | ≤ 0,2 | 80-56-8 201-291-9 | - | - | |
| | | 2;H315, S | 3;H226, Acute Tox. kin Sens. 1B;H317, hronic 1;H410 | | mg/kg), Skin Irrit. Aquatic Acute 1;H400, | |
| beta-Pinene | | ≤ 0,2 | 127-91-3 204-872-5 | - | - | |
| | | | 3;H226, Skin Irrit. 2 quatic Acute 1;H400 | | | |
| Citral | | ≤ 0,2 | 5392-40-5 226-394-6 | - | 605-019-00-3 | |
| | Classification: | Skin Irrit. 2 | 2;H315, Eye Irrit. 2;I | H319, Skin Sens. 1; | H317 | |

Chemical name CAS-No. / EC No. REACH Registration No. Index No. **Notes**

Methyl cinnamate ≤ 0.2 103-26-4

203-093-8

Classification: Skin Sens. 1B;H317

< -0.1

Other components below reportable levels

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. #: This

substance has been assigned Union workplace exposure limit(s).

The full text for all H-statements is displayed in section 16. Composition comments

SECTION 4: First aid measures

General information Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves. Wash contaminated clothing

before reuse.

4.1. Description of first aid measures

Move to fresh air. Call a physician if symptoms develop or persist. Inhalation

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

delayed

Eye contact

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Highly flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate

protective clothing.

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during For emergency responders

clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection

recommended in Section 8 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all 6.2. Environmental precautions

environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into

drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| Austria. MAK List, OEL Ordinance (Components | Type | Value | |
|--|-----------------------------|-------------------------------|----------------------|
| Ethanol (CAS 64-17-5) | Ceiling | 3800 mg/m3 | |
| | | 2000 ppm | |
| | MAK | 1900 mg/m3 | |
| | | 1000 ppm | |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | Ceiling | 614 mg/m3 | |
| | | 100 ppm | |
| | MAK | 307 mg/m3 | |
| | | 50 ppm | |
| Belgium. Exposure Limit Values Components | Туре | Value | Form |
| alpha-Pinene (CAS 80-56-8) | TWA | 20 ppm | |
| beta-Pinene (CAS 127-91-3) | TWA | 20 ppm | |
| Citral (CAS 5392-40-5) | TWA | 32 mg/m3 | Vapour and aerosol. |
| | | 5 ppm | Vapour and aerosol. |
| Ethanol (CAS 64-17-5) | TWA | 1907 mg/m3 | |
| | | 1000 ppm | |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | TWA | 308 mg/m3 | |
| , | | 50 ppm | |
| Bulgaria. OELs. Regulation No 13 o | n protection of workers aga | inst risks of exposure to che | mical agents at work |
| Components | Туре | Value | |
| Benzyl alcohol (CAS 100-51-6) | TWA | 5 mg/m3 | |

| Bulgaria. OELs. Regulation No 13 on p | protection of workers a Type | gainst risks of exposure to chemical agents at work Value |
|--|---------------------------------|--|
| Ethanol (CAS 64-17-5) | TWA | 1000 mg/m3 |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | TWA | 308 mg/m3 |
| , | | 50 ppm |
| Croatia. Dangerous Substance Exposi Components | ure Limit Values in the Type | Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Value |
| Ethanol (CAS 64-17-5) | MAC | 1900 mg/m3 |
| | | 1000 ppm |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | MAC | 308 mg/m3 |
| | | 50 ppm |
| Czech Republic. OELs. Government De Components | ecree 361 Type | Value |
| Benzyl alcohol (CAS 100-51-6) | Ceiling | 80 mg/m3 |
| | TWA | 40 mg/m3 |
| Ethanol (CAS 64-17-5) | Ceiling | 3000 mg/m3 |
| | TWA | 1000 mg/m3 |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | Ceiling | 550 mg/m3 |
| | TWA | 270 mg/m3 |
| Denmark. Exposure Limit Values Components | Туре | Value |
| alpha-Pinene (CAS 80-56-8) | TLV | 25 ppm |
| beta-Pinene (CAS 127-91-3) | TLV | 25 ppm |
| Ethanol (CAS 64-17-5) | TLV | 1900 mg/m3 |
| | | 1000 ppm |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | TLV | 309 mg/m3 |
| | | 50 ppm |
| Estonia. OELs. Occupational Exposure Components | e Limits of Hazardous Type | Substances (Regulation No. 105/2001, Annex), as amended Value |
| alpha-Pinene (CAS | STEL | 300 mg/m3 |
| 80-56-8) | | 50 ppm |
| | TWA | 150 mg/m3 |
| | | 25 ppm |
| beta-Pinene (CAS | STEL | 300 mg/m3 |
| 127-91-3) | | - |
| | T\A/A | 50 ppm |
| | TWA | 150 mg/m3 |
| Ethanol (CAS 64-17-5) | STEL | 25 ppm 1900 mg/m3 |
| Luianoi (CAS 04-17-3) | SIEL | 1900 mg/m3 1000 ppm |
| | TWA | 1000 mg/m3 |
| | 1 **/ 1 | 500 ppm |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) | TWA | 308 mg/m3 |
| - (CAS 34590-94-8) | | 50 ppm |

| Finland. Workplace Exposure Limits | | | |
|--|------|------------|--|
| Components | Туре | Value | |
| Benzyl alcohol (CAS 100-51-6) | TWA | 45 mg/m3 | |
| | | 10 ppm | |
| Ethanol (CAS 64-17-5) | STEL | 2500 mg/m3 | |
| | | 1300 ppm | |
| | TWA | 1900 mg/m3 | |
| | | 1000 ppm | |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | TWA | 310 mg/m3 | |
| · | | 50 ppm | |

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Components Type Value

| Ethanol (CAS 64-17-5) | VLE | 9500 mg/m3 | |
|--------------------------|-----------------------|------------|--|
| Regulatory status: | Indicative limit (VL) | | |
| | | 5000 ppm | |
| Regulatory status: | Indicative limit (VL) | | |
| | VME | 1900 mg/m3 | |
| Regulatory status: | Indicative limit (VL) | | |
| | | 1000 ppm | |
| Regulatory status: | Indicative limit (VL) | | |
| Propanol, 1(or | VME | 308 mg/m3 | |
| 2)-(2-methoxymethylethox | xy) | | |
| - (CAS 34590-94-8) | | | |

Regulatory status: Regulatory binding (VRC)

50 ppm

Regulatory status: Regulatory binding (VRC)

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

| Components | Туре | Value | Form |
|--|--------------------------------|-----------|--|
| Benzyl alcohol (CAS 100-51-6) | TWA | 22 mg/m3 | Vapour and aerosol. |
| | | 5 ppm | Vapour and aerosol. |
| Ethanol (CAS 64-17-5) | TWA | 380 mg/m3 | |
| | | 200 ppm | |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | TWA | 310 mg/m3 | Vapour. |
| | | 50 ppm | Vapour. |
| Propanol, oxybis- (CAS 25265-71-8) | TWA | 100 mg/m3 | Vapor and aerosol, inhalable fraction. |
| Germany. TRGS 900, Limit Values | in the Ambient Air at the Worl | | |
| Components | Туре | Value | Form |
| Benzyl alcohol (CAS 100-51-6) | AGW | 22 mg/m3 | Vapour and aerosol. |
| | | 5 ppm | Vapour and aerosol. |
| Ethanol (CAS 64-17-5) | AGW | 380 mg/m3 | |
| | | 200 ppm | |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | AGW | 310 mg/m3 | Vapour and aerosol. |
| | | 50 ppm | Vapour and aerosol. |
| Propanol, oxybis- (CAS | | | |

| Ethanol (CAS 64-17-5) | TWA | 1000 mg/m2 | |
|--|------------------------------------|--------------------------------------|--------------------------------|
| | | 1900 mg/m3 | |
| | | 1000 ppm | |
| ropanol, 1(or)-(2-methoxymethylethoxy) (CAS 34590-94-8) | STEL | 900 mg/m3 | |
| (6.16 6.1886 6.1 8) | | 150 ppm | |
| | TWA | 600 mg/m3 | |
| | | 100 ppm | |
| lungary. OELs. Joint Decree on Cher | nical Safety of Workplaces Type | | |
| Ethanol (CAS 64-17-5) | STEL | 3800 mg/m3 | |
| | TWA | 1900 mg/m3 | |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) (CAS 34590-94-8) | TWA | 308 mg/m3 | |
| celand. OELs. Regulation 154/1999 o Components | n occupational exposure l Type | imits Value | |
| Ethanol (CAS 64-17-5) | TWA | 1900 mg/m3 | |
| , | | 1000 ppm | |
| Propanol, 1(or P)-(2-methoxymethylethoxy) (CAS 34590-94-8) | TWA | 300 mg/m3 | |
| | | 50 ppm | |
| reland. Occupational Exposure Limit Components | s Type | Value | Form |
| Citral (CAS 5392-40-5) | TWA | 5 ppm | Inhalable fraction and vapour. |
| thanol (CAS 64-17-5) | STEL | 1000 ppm | |
| Propanol, 1(or P)-(2-methoxymethylethoxy) (CAS 34590-94-8) | TWA | 308 mg/m3 | |
| | | 50 ppm | |
| taly. Occupational Exposure Limits | Tuna | Value | Form |
| Components | Type | | |
| lpha-Pinene (CAS 0-56-8) | TWA | 20 ppm | |
| eta-Pinene (CAS 27-91-3) | TWA | 20 ppm | |
| Citral (CAS 5392-40-5) | TWA | 5 ppm | Inhalable fraction and vapour. |
| Ethanol (CAS 64-17-5) | STEL | 1000 ppm | • |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) (CAS 34590-94-8) | TWA | 308 mg/m3 | |
| | | 50 ppm | |
| atvia. OELs. Occupational exposure components | limit values of chemical s Type | ubstances in work environme Value | nt |
| Benzyl alcohol (CAS 100-51-6) | TWA | 5 mg/m3 | |
| Ethanol (CAS 64-17-5) | TWA | 1000 mg/m3 | |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) | TWA | 308 mg/m3 | |
| (CAS 34590-94-8) | | | |

| Lithuania. OELs. Limit Values for (Components | Type | Value |
|--|--|---|
| alpha-Pinene (CAS 80-56-8) | STEL | 300 mg/m3 |
| | | 50 ppm |
| | TWA | 150 mg/m3 |
| | | 25 ppm |
| Benzyl alcohol (CAS | TWA | 5 mg/m3 |
| 100-51-6) beta-Pinene (CAS 127-91-3) | STEL | 300 mg/m3 |
| , | | 50 ppm |
| | TWA | 150 mg/m3 |
| | | 25 ppm |
| Ethanol (CAS 64-17-5) | STEL | 1900 mg/m3 |
| | | 1000 ppm |
| | TWA | 1000 mg/m3 |
| | | 500 ppm |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) | STEL | 450 mg/m3 |
| - (CAS 34590-94-8) | | 75 ppm |
| | TWA | 308 mg/m3 |
| | IVVA | - |
| | | 50 ppm |
| Malta. OELs. Occupational Exposu Schedules I and V) | re Limit Values (L.N. 227. of | Occupational Health and Safety Authority Act (CAP. 424 |
| Components | Туре | Value |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | TWA | 308 mg/m3 |
| | | 50 ppm |
| Netherlands. OELs (binding) Components | Туре | Value |
| Ethanol (CAS 64-17-5) | STEL | 1900 mg/m3 |
| | TWA | 260 mg/m3 |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | TWA | 300 mg/m3 |
| Norway. Administrative Norms for | Contaminants in the Workpla | 200 |
| | | |
| Components | Туре | Value |
| alpha-Pinene (CAS | = | |
| alpha-Pinene (CAS | Туре | Value |
| alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS | Туре | Value 140 mg/m3 |
| alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS | Type TLV | Value 140 mg/m3 25 ppm |
| alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) | Type TLV | Value 140 mg/m3 25 ppm 140 mg/m3 |
| alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) | Type TLV TLV | Value 140 mg/m3 25 ppm 140 mg/m3 25 ppm 950 mg/m3 |
| alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) | Type TLV TLV | Value 140 mg/m3 25 ppm 140 mg/m3 25 ppm |
| Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | Type TLV TLV | Value 140 mg/m3 25 ppm 140 mg/m3 25 ppm 950 mg/m3 500 ppm |
| alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Poland. Ordinance of the Minister of concentrations and intensities of h | TLV TLV TLV TLV TLV TLV The state of Labour and Social Policy of Labour and factors in the state of the | Value 140 mg/m3 25 ppm 140 mg/m3 25 ppm 950 mg/m3 500 ppm 300 mg/m3 50 ppm on 6 June 2014 on the maximum permissible work environment, Journal of Laws 2014, item 817 |
| alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Poland. Ordinance of the Minister concentrations and intensities of h | Type TLV TLV TLV TLV of Labour and Social Policy of Lamful health factors in the start type | Value 140 mg/m3 25 ppm 140 mg/m3 25 ppm 950 mg/m3 500 ppm 300 mg/m3 50 ppm on 6 June 2014 on the maximum permissible work environment, Journal of Laws 2014, item 817 Value |
| alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Poland. Ordinance of the Minister of | TLV TLV TLV TLV TLV TLV The state of Labour and Social Policy of Labour and factors in the state of the | Value 140 mg/m3 25 ppm 140 mg/m3 25 ppm 950 mg/m3 500 ppm 300 mg/m3 50 ppm on 6 June 2014 on the maximum permissible work environment, Journal of Laws 2014, item 817 |

| Citral (CAS 5392-40-5) | Туре | work environment, Journal of Value | • |
|--|---|--|--------------------------------|
| nii ai (OAO 3332- 4 0-3) | STEL | 54 mg/m3 | |
| , | | 0 ppm | |
| | TWA | 27 mg/m3 | |
| | | 0 ppm | |
| Ethanol (CAS 64-17-5) | TWA | 1900 mg/m3 | |
| | | 0 ppm | |
| Propanol, 1(or | STEL | 480 mg/m3 | |
| 2)-(2-methoxymethylethoxy) · (CAS 34590-94-8) | | .co mg.mc | |
| | | 0 ppm | |
| | TWA | 240 mg/m3 | |
| | | 0 ppm | |
| Portugal. OELs. Decree-Law n. 290 Components | 0/2001 (Journal of the Republ Type | ic - 1 Series A, n.266) Value | |
| Propanol, 1(or | TWA | 308 mg/m3 | |
| 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | | ooo mg/me | |
| | | 50 ppm | |
| Portugal. VLEs. Norm on occupation Components | onal exposure to chemical aç Type | gents (NP 1796) Value | Form |
| alpha-Pinene (CAS 30-56-8) | TWA | 20 ppm | |
| oeta-Pinene (CAS 127-91-3) | TWA | 20 ppm | |
| Citral (CAS 5392-40-5) | TWA | 5 ppm | Inhalable fraction and vapour. |
| Ethanol (CAS 64-17-5) | TWA | 1000 ppm | |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) · (CAS 34590-94-8) | STEL | 150 ppm | |
| (0.10 0.1000 0.10) | TWA | 100 ppm | |
| | | cal agents at the workplace Value | |
| | Туре | value | |
| Components | Type STEL | | |
| Components | Type STEL | 9500 mg/m3 | |
| Components | STEL | 9500 mg/m3 5000 ppm | |
| Components | - | 9500 mg/m3 5000 ppm 1900 mg/m3 | |
| Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) | STEL | 9500 mg/m3 5000 ppm | |
| Romania. OELs. Protection of worl Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | STEL | 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 308 mg/m3 | |
| Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) | STEL TWA TWA | 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 308 mg/m3 | cal agents |
| Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Slovakia. OELs. Regulation No. 300 Components | STEL TWA TWA 0/2007 concerning protection | 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 308 mg/m3 50 ppm | cal agents |
| Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Slovakia. OELs. Regulation No. 300 Components | STEL TWA TWA 0/2007 concerning protection Type | 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 308 mg/m3 50 ppm n of health in work with chemic | cal agents |
| Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Slovakia. OELs. Regulation No. 300 Components | STEL TWA TWA 0/2007 concerning protection Type | 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 308 mg/m3 50 ppm n of health in work with chemic Value 1920 mg/m3 | cal agents |
| Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Slovakia. OELs. Regulation No. 300 Components | STEL TWA TWA 0/2007 concerning protection Type STEL | 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 308 mg/m3 50 ppm n of health in work with chemic Value 1920 mg/m3 1000 ppm | cal agents |
| Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Slovakia. OELs. Regulation No. 306 | STEL TWA TWA 0/2007 concerning protection Type STEL | 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm 308 mg/m3 50 ppm n of health in work with chemic Value 1920 mg/m3 1000 ppm 960 mg/m3 | cal agents |

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Туре

Components

Form

Value

| Components | rype | value | 1 01111 |
|---|---|--|--------------------------------|
| Benzyl alcohol (CAS 100-51-6) | TWA | 22 mg/m3 | |
| 100 01 0) | | 5 ppm | |
| Ethanol (CAS 64-17-5) | TWA | 960 mg/m3 | |
| | | 500 ppm | |
| Propanol, 1(or | TWA | 308 mg/m3 | |
| 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | TWA | 300 mg/mo | |
| , | | 50 ppm | |
| Propanol, oxybis- (CAS | TWA | 100 mg/m3 | Inhalable fraction. |
| 25265-71-8) | | · · | |
| Spain. Occupational Exposure Limits Components | Туре | Value | Form |
| alpha-Pinene (CAS | TWA | 113 mg/m3 | |
| 30-56-8) | | 110 1119/1110 | |
| | | 20 ppm | |
| beta-Pinene (CAS | TWA | 113 mg/m3 | |
| 127-91-3) | | •• | |
| | | 20 ppm | |
| Citral (CAS 5392-40-5) | TWA | 5 ppm | Inhalable fraction and vapour. |
| Ethanol (CAS 64-17-5) | STEL | 1910 mg/m3 | vapoui. |
| (| | 1000 ppm | |
| Propanol, 1(or | TWA | 308 mg/m3 | |
| 2)-(2-methoxymethylethoxy) | TWA | 300 mg/m3 | |
| - (CAS 34590-94-8) | | | |
| - (CAS 34590-94-8) | | 50 ppm | |
| Sweden. OELs. Work Environment Auth | ority (AV), Occupational Exposure L Type | | 015:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS | | imit Values (AFS 2 | 015:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS | Туре | imit Values (AFS 20 Value 300 mg/m3 | 015:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS | Type STEL | imit Values (AFS 20 Value 300 mg/m3 50 ppm | 015:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS | Туре | imit Values (AFS 20 Value 300 mg/m3 50 ppm 150 mg/m3 | 015:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS 80-56-8) | Type STEL TWA | imit Values (AFS 20 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm | 015:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS 80-56-8) | Type STEL | imit Values (AFS 20 Value 300 mg/m3 50 ppm 150 mg/m3 | 015:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS 80-56-8) | Type STEL TWA | imit Values (AFS 20 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm | 015:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS 80-56-8) | Type STEL TWA | imit Values (AFS 20 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 | 015:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS 80-56-8) | Type STEL TWA STEL | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 | 015:7) |
| Sweden. OELs. Work Environment Authomponents alpha-Pinene (CAS 80-56-8) Deta-Pinene (CAS 127-91-3) | Type STEL TWA STEL | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 250 ppm 150 mg/m3 25 ppm | 015:7) |
| Sweden. OELs. Work Environment Authomponents alpha-Pinene (CAS 80-56-8) Deta-Pinene (CAS 127-91-3) | Type STEL TWA STEL TWA | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 1900 mg/m3 | 015:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) | Type STEL TWA STEL TWA STEL | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm | 015:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) | Type STEL TWA STEL TWA | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm 1000 mg/m3 | 015:7) |
| Sweden. OELs. Work Environment Auth-Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) | Type STEL TWA STEL TWA STEL TWA | imit Values (AFS 26 Value 300 mg/m3 500 ppm 150 mg/m3 500 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm | 015:7) |
| Sweden. OELs. Work Environment Auth-Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) | Type STEL TWA STEL TWA STEL | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm 1000 mg/m3 | 015:7) |
| Sweden. OELs. Work Environment Auth-Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) | Type STEL TWA STEL TWA STEL TWA | imit Values (AFS 26 Value 300 mg/m3 500 ppm 150 mg/m3 500 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm | 015:7) |
| Sweden. OELs. Work Environment Auth-Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) | Type STEL TWA STEL TWA STEL TWA | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm 450 mg/m3 | 015:7) |
| Sweden. OELs. Work Environment Auth-Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) | Type STEL TWA STEL TWA STEL TWA STEL | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm 450 mg/m3 | 015:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | Type STEL TWA STEL TWA STEL TWA STEL TWA STEL | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm 450 mg/m3 | 015:7) |
| Sweden. OELs. Work Environment Authomponents alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Switzerland. SUVA Grenzwerte am Arbei | Type STEL TWA STEL TWA STEL TWA STEL TWA STEL | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm 450 mg/m3 | |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Switzerland. SUVA Grenzwerte am Arbei Components | Type STEL TWA STEL TWA STEL TWA STEL TWA STEL TWA STEL TYPA | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm 450 mg/m3 75 ppm 300 mg/m3 50 ppm | D15:7) |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Switzerland. SUVA Grenzwerte am Arbei Components alpha-Pinene (CAS | Type STEL TWA STEL TWA STEL TWA STEL TWA STEL | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm 450 mg/m3 | |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Switzerland. SUVA Grenzwerte am Arbei Components alpha-Pinene (CAS | Type STEL TWA STEL TWA STEL TWA STEL TWA STEL TWA STEL TYPA | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm 450 mg/m3 75 ppm 300 mg/m3 50 ppm | |
| Sweden. OELs. Work Environment Auth Components alpha-Pinene (CAS 80-56-8) beta-Pinene (CAS 127-91-3) Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Switzerland. SUVA Grenzwerte am Arbei Components alpha-Pinene (CAS 80-56-8) | Type STEL TWA STEL TWA STEL TWA STEL TWA STEL TWA STEL TYPA | imit Values (AFS 26 Value 300 mg/m3 50 ppm 150 mg/m3 25 ppm 300 mg/m3 50 ppm 150 mg/m3 25 ppm 1900 mg/m3 1000 ppm 1000 mg/m3 500 ppm 450 mg/m3 75 ppm 300 mg/m3 50 ppm Value 224 mg/m3 | |

| Benzyl alcohol (CAS 100-51-6) 5 p | ppm mg/m3 ppm 4 mg/m3 ppm 2 mg/m3 ppm 20 mg/m3 00 ppm 0 mg/m3 0 mg/m3 | Vapour and aerosol. Vapour and aerosol. |
|--|--|--|
| Benzyl alcohol (CAS TWA 22 100-51-6) 5 p | mg/m3 ppm 4 mg/m3 ppm 2 mg/m3 ppm 20 mg/m3 0 ppm 0 mg/m3 0 ppm 0 mg/m3 | Vapour and aerosol. |
| beta-Pinene (CAS 127-91-3) beta-Pinene (CAS 224 127-91-3) TWA 112 20 Ethanol (CAS 64-17-5) STEL 199 TWA 960 TWA 960 TWA 960 TWA 300 Propanol, 1(or STEL 300 CAS 34590-94-8) TWA 300 TWA 140 UK. EH40 Workplace Exposure Limits (WELs) Components Type Val Ethanol (CAS 64-17-5) TWA 199 Propanol, 1(or TWA 300 Propanol, 1(or TWA 300 TWA 300 TWA 199 TWA 199 TWA 199 TWA 199 TWA 300 TWA 199 TWA 199 | ppm 2 mg/m3 ppm 20 mg/m3 00 ppm 0 mg/m3 0 ppm 0 mg/m3 0 ppm | |
| beta-Pinene (CAS 127-91-3) | ppm 2 mg/m3 ppm 20 mg/m3 00 ppm 0 mg/m3 0 ppm 0 mg/m3 0 ppm | |
| 127-91-3) TWA TWA 112 20 Ethanol (CAS 64-17-5) STEL 196 TWA 966 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) TWA 306 TWA 307 TWA 308 Propanol, oxybis- (CAS STEL 286 TWA 146 UK. EH40 Workplace Exposure Limits (WELs) Components Type Val Propanol, (CAS 64-17-5) TWA 196 TWA 308 | ppm 2 mg/m3 ppm 20 mg/m3 00 ppm 0 mg/m3 0 ppm 0 mg/m3 0 ppm | |
| TWA | 2 mg/m3 ppm 20 mg/m3 00 ppm 0 mg/m3 0 ppm 0 mg/m3 | |
| Ethanol (CAS 64-17-5) Ethanol (CAS 64-17-5) STEL 192 TWA 960 Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Fropanol, oxybis- (CAS 25265-71-8) TWA 300 TWA 50 Propanol, oxybis- (CAS 25265-71-8) TWA 140 UK. EH40 Workplace Exposure Limits (WELs) Components Type Vai Ethanol (CAS 64-17-5) TWA 192 Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | ppm 20 mg/m3 00 ppm 0 mg/m3 0 ppm 0 mg/m3 | |
| Ethanol (CAS 64-17-5) Ethanol (CAS 64-17-5) TWA 960 Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) TWA 300 Propanol, oxybis- (CAS STEL 280 25265-71-8) TWA 140 UK. EH40 Workplace Exposure Limits (WELs) Components Type Val Ethanol (CAS 64-17-5) TWA 192 Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | 20 mg/m3 00 ppm 0 mg/m3 0 ppm 0 mg/m3 | |
| TWA 966 20)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Propanol, 1(or STEL 300 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) TWA 300 50 Propanol, oxybis- (CAS STEL 280 25265-71-8) TWA 140 UK. EH40 Workplace Exposure Limits (WELs) Components Type Val Ethanol (CAS 64-17-5) TWA 192 Propanol, 1(or TWA 308 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | 00 ppm 0 mg/m3 0 ppm 0 mg/m3 | |
| TWA 960 Propanol, 1(or STEL 300 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) TWA 300 Propanol, oxybis- (CAS STEL 280 25265-71-8) TWA 140 UK. EH40 Workplace Exposure Limits (WELs) Components Type Val Ethanol (CAS 64-17-5) TWA 192 Propanol, 1(or TWA 308 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | 0 mg/m3 0 ppm 0 mg/m3 | |
| Propanol, 1(or STEL 300 | 0 ppm 0 mg/m3 | |
| Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | 0 mg/m3 | |
| 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) TWA 50 Propanol, oxybis- (CAS 25265-71-8) TWA 140 UK. EH40 Workplace Exposure Limits (WELs) Components Type Val Ethanol (CAS 64-17-5) TWA 192 Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | · · | |
| TWA 300 Propanol, oxybis- (CAS STEL 280 25265-71-8) TWA 140 UK. EH40 Workplace Exposure Limits (WELs) Components Type Val Ethanol (CAS 64-17-5) TWA 192 100 Propanol, 1(or TWA 308 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | nnm | Vapour and aerosol. |
| TWA 300 50 Propanol, oxybis- (CAS STEL 280 25265-71-8) TWA 140 UK. EH40 Workplace Exposure Limits (WELs) Components Type Val Ethanol (CAS 64-17-5) TWA 192 100 Propanol, 1(or TWA 308 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | | Vapour and aerosol. |
| Propanol, oxybis- (CAS STEL 280 25265-71-8) TWA 140 | 0 mg/m3 | Vapour and aerosol. |
| Propanol, oxybis- (CAS STEL 280 25265-71-8) TWA 140 UK. EH40 Workplace Exposure Limits (WELs) Components Type Val Ethanol (CAS 64-17-5) TWA 192 Propanol, 1(or TWA 308 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) - (CAS 34590-94-8) | o | Vapour and aerosol. Vapour and aerosol. |
| 25265-71-8) TWA 140 UK. EH40 Workplace Exposure Limits (WELs) Components Type Val Ethanol (CAS 64-17-5) TWA 192 Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | ppm 0 mg/m3 | Vapour and aerosol. |
| UK. EH40 Workplace Exposure Limits (WELs) Components Type Val Ethanol (CAS 64-17-5) TWA 192 Propanol, 1(or TWA 308 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | · · | inhalable. |
| Components Type Val Ethanol (CAS 64-17-5) TWA 192 Propanol, 1(or TWA 308 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) - (CAS 34590-94-8) | 0 mg/m3 | Vapor and aerosol, inhalable. |
| Components Type Val Ethanol (CAS 64-17-5) TWA 192 Propanol, 1(or TWA 308 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) - (CAS 34590-94-8) | | |
| Propanol, 1(or TWA 308 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | lue | |
| Propanol, 1(or TWA 308 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | 20 mg/m3 | |
| 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | 00 ppm | |
| , | 8 mg/m3 | |
| 50 | ppm | |
| EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006 | | 61/EU, 2017/164/EU |
| <u> </u> | lue | |
| Propanol, 1(or TWA 308 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) | 8 mg/m3 | |
| | ppm | |
| logical limit values No biological exposure limits noted for the ingredient(s | • | |
| commended monitoring Follow standard monitoring procedures. | , | |
| cedures | | |
| ived no effect levels Not available. ELs) | | |
| dicted no effect Not available. centrations (PNECs) | | |
| osure guidelines | | |
| Austria MAK: Skin designation | | |
| Propanol, 1(or 2)-(2-methoxymethylethoxy)- (CAS 34590-94-8) Belgium OELs: Skin designation | gh the skin. | |
| Citral (CAS 5392-40-5) Propanol, 1(or 2)-(2-methoxymethylethoxy)- (CAS 34590-94-8) Can be absorbed throu Can be absorbed throu | | |
| Bulgaria OELs: Skin designation | | |
| Propanol, 1(or 2)-(2-methoxymethylethoxy)- (CAS 34590-94-8) Can be absorbed throu | ah tho ekin | |
| Croatia ELVs: Skin designation Proposed 1/or 2) /2 methoxy/methylothoxy/ Can be absorbed through | gir tile skill. | |
| Propanol, 1(or 2)-(2-methoxymethylethoxy)- (CAS 34590-94-8) Can be absorbed throu | | |

Czech Republic PELs: Skin designation Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin. (CAS 34590-94-8) Denmark GV: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin. (CAS 34590-94-8)

Estonia OELs: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin. (CAS 34590-94-8)

EU Exposure Limit Values: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin.

(CAS 34590-94-8)

Finland Exposure Limit Values: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin.

(CAS 34590-94-8)

France INRS: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin.

(CAS 34590-94-8)

Germany DFG MAK (advisory): Skin designation

Benzyl alcohol (CAS 100-51-6) Can be absorbed through the skin.

Germany TRGS 900 Limit Values: Skin designation

Benzyl alcohol (CAS 100-51-6) Can be absorbed through the skin.

Greece OEL: Skin designation

Iceland OELs: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin.

(CAS 34590-94-8)

Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin.

(CAS 34590-94-8)

Ireland Exposure Limit Values: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin.

(CAS 34590-94-8) Italy OELs: Skin designation

> Citral (CAS 5392-40-5) Danger of cutaneous absorption Propanol, 1(or 2)-(2-methoxymethylethoxy)-Danger of cutaneous absorption

(CAS 34590-94-8)

Latvia OELs: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin. (CAS 34590-94-8)

Lithuania OELs: Skin designation

Benzyl alcohol (CAS 100-51-6) Can be absorbed through the skin. Can be absorbed through the skin.

Propanol, 1(or 2)-(2-methoxymethylethoxy)-(CAS 34590-94-8)

Luxembourg OELs: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin.

(CAS 34590-94-8)

Malta OELs: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin. (CAS 34590-94-8)

Netherlands OELs (binding): Skin designation

Ethanol (CAS 64-17-5) Can be absorbed through the skin.

Norway Exposure Limit Values: Skin designation

alpha-Pinene (CAS 80-56-8) Can be absorbed through the skin. Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin.

(CAS 34590-94-8)

Portugal OELs: Skin designation Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin.

(CAS 34590-94-8)

Portugal VLEs Norm on Occupatioinal Exposure: Skin designation

Citral (CAS 5392-40-5) Can be absorbed through the skin. Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin.

(CAS 34590-94-8)

Romania OELs: Skin designation Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin.

(CAS 34590-94-8)

Slovakia OELs: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)-Can be absorbed through the skin.

(CAS 34590-94-8)

Material name: FRAGRANCE FOR DIFFUSER 250ml MELA & CANNELLA

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Benzyl alcohol (CAS 100-51-6)

Can be absorbed through the skin.

Propanol, 1(or 2)-(2-methoxymethylethoxy)
Can be absorbed through the skin.

(CAS 34590-94-8)

Spain OELs: Skin designation

Citral (CAS 5392-40-5)

Propanol, 1(or 2)-(2-methoxymethylethoxy)
Can be absorbed through the skin.

Can be absorbed through the skin.

(CAS 34590-94-8)

Sweden Threshold Limit Values: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)- Can be absorbed through the skin.

(CAS 34590-94-8)

Switzerland SUVA Limit Values at the Workplace: Skin designation

alpha-Pinene (CAS 80-56-8)

Benzyl alcohol (CAS 100-51-6)

beta-Pinene (CAS 127-91-3)

Can be absorbed through the skin.

Can be absorbed through the skin.

UK EH40 WEL: Skin designation

Propanol, 1(or 2)-(2-methoxymethylethoxy)- Can be absorbed through the skin.

(CAS 34590-94-8)

8.2. Exposure controls

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

- Hand protection Wear protective gloves.

- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable

levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid.
Form Liquid.

ColourNot available.OdourNot available.

Melting point/freezing point -114,1 °C (-173,38 °F) estimated

Boiling point or initial boiling 78,29 °C (172,92 °F) estimated

point and boiling range

Flammability (solid, gas) Not applicable.

Flash point 13 °C (55,4 °F) estimated

Auto-ignition temperature 363 °C (685,4 °F) estimated

Decomposition temperature Not available. **pH** Not available.

Solubility(ies)

Solubility (water) Not available.

Material name: FRAGRANCE FOR DIFFUSER 250ml MELA & CANNELLA

Partition coefficient Not available.

(n-octanol/water)

Vapour pressure 79,06 hPa estimated

Vapour densityNot available.Relative densityNot available.Particle characteristicsNot available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

Density 0,819 g/cm3 estimated

Explosive properties

Oxidising properties

Not explosive.

Not oxidising.

Percent volatile

Specific gravity

VOC

Not explosive.

Not explo

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous

No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Coughing. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on toxicological effects

Acute toxicity No data available.

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitisationDue to partial or complete lack of data the classification is not possible.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

IARC Monographs. Overall Evaluation of Carcinogenicity

Coumarin (CAS 91-64-5)

3 Not classifiable as to carcinogenicity to humans.

Eugenol (CAS 97-53-0)

3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicityDue to partial or complete lack of data the classification is not possible. **Specific target organ toxicity -**Due to partial or complete lack of data the classification is not possible.

single exposure

iigie exposuie

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance information

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

Other information

Not available.

SECTION 12: Ecological information

Harmful to aquatic life with long lasting effects. Based on available data, the classification criteria 12.1. Toxicity

are not met for hazardous to the aquatic environment, acute hazard.

| Components | | Species | Test Results |
|------------------------------|------|---|---------------------------------|
| Benzyl alcohol (CAS 100-51-6 |) | | |
| Aquatic | | | |
| Acute | | | |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | 10 mg/l, 96 hours |
| Coumarin (CAS 91-64-5) | | | |
| Aquatic | | | |
| Acute | | | |
| Fish | LC50 | Guppy (Poecilia reticulata) | >= 32 - <= 100 mg/l, 96 hours |
| Ethanol (CAS 64-17-5) | | | |
| Aquatic | | | |
| <i>Acute</i> | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | >= 7,7 - <= 11,2 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 42 mg/l, 4 days |
| Eugenol (CAS 97-53-0) | | | |
| Aquatic | | | |
| Acute | | | |
| Fish | LC50 | Fathead minnow (Pimephales prome | elas) 24 mg/l, 96 hours |
| Vanillin (CAS 121-33-5) | | | |
| Aquatic | | | |
| Acute | | | |

12.2. Persistence and

Fish

No data is available on the degradability of any ingredients in the mixture.

1 03

Fathead minnow (Pimephales promelas) >= 53 - <= 61,3 mg/l, 96 hours

degradability

12.3. Bioaccumulative potential

Partition coefficient

| n-octanol/water | (log | Kow) | |
|-----------------|------|------|--|
| alala a Dia aa | _ | | |

| aipha-Pinene | 4,00 |
|--|-------|
| Benzyl alcohol | 1,1 |
| beta-Pinene | 4,16 |
| Cinnamal | 1,9 |
| | 2,1 |
| | 2,107 |
| Citral | 2,76 |
| | 3,45 |
| Citrus Aurantium Dulcis Flower Extract | 4,38 |
| Coumarin | 1,39 |
| Ethanol | -0,31 |
| Eugenol | 2,49 |
| Methyl cinnamate | 2,68 |
| Methylcinnamic aldehyde | 2,319 |
| Vanillin | 1,37 |
| | |

LC50

Bioconcentration factor (BCF)

Not available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

assessment

12.6. Endocrine disrupting properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation potential.

Material name: FRAGRANCE FOR DIFFUSER 250ml MELA & CANNELLA

7REMMC Version #: 03 Revision date: 14-October-2022 Issue date: 23-May-2022

12.8. Additional information

Estonia Dangerous substances in soil Data

Benzyl alcohol (CAS 100-51-6) Chemical pesticides (As the total sum of the active substances)

0,5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20

ma/ka

Chemical pesticides (As the total sum of the active substances) 5

mg/kg

Ethanol (CAS 64-17-5) Chemical pesticides (As the total sum of the active substances)

0.5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20

mg/kg

Chemical pesticides (As the total sum of the active substances) 5

mg/kg

Eugenol (CAS 97-53-0) Chemical pesticides (As the total sum of the active substances)

0,5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20

mg/kg

Chemical pesticides (As the total sum of the active substances) 5

mg/kg

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

The Waste code should be assigned in discussion between the user, the producer and the waste EU waste code

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow Disposal methods/information

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Special precautions

SECTION 14: Transport information

ADR

14.1. UN number UN1170

ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) 14.2. UN proper shipping

(Ethanol) name

14.3. Transport hazard class(es)

Class 3 Subsidiary risk 3 Label(s) Hazard No. (ADR) 33 Tunnel restriction code D/E Ш 14.4. Packing group

14.5. Environmental hazards No.

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

RID

ADN

UN1170 14.1. UN number

14.2. UN proper shipping ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

name (Ethanol)

14.3. Transport hazard class(es)

Class 3 Subsidiary risk 3 Label(s) 14.4. Packing group Ш 14.5. Environmental hazards No.

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

UN1170 14.1. UN number

> 14.2. UN proper shipping ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

name (Ethanol) 14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
14.4. Packing group ||
14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1170

14.2. UN proper shipping Ethanol solution (Ethanol)

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk
14.4. Packing group ||

14.5. Environmental hazards Yes
ERG Code 3L

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN1170

14.2. UN proper shipping ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

name (Ethanol), MARINE POLLUTANT

14.3. Transport hazard class(es)

Class 3
Subsidiary risk 14.4. Packing group II
14.5. Environmental hazards

Marine pollutant Yes
EmS F-E, S-D

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user alpha-Pinene alpha-Pinene

alpha-rinene

4.7. Maritime transport in bulk Not established.

14.7. Maritime transport in bulk according to IMO instruments

ADN; ADR; IATA; IMDG; RID



Marine pollutant



General information IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Ethanol (CAS 64-17-5)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Ethanol (CAS 64-17-5)

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Young people under 18 years old are not allowed to work with this product according to EU

Directive 94/33/EC on the protection of young people at work, as amended Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References Not available.

Information on evaluation method leading to the classification of mixture

Full text of any H-statements not written out in full under Sections 2 to 15 The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Revision information

Training information

Disclaimer

Follow training instructions when handling this material.

Home Fragrance Italia cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Material name: FRAGRANCE FOR DIFFUSER 250ml MELA & CANNELLA