

SAFETY DATA SHEET

Version #: 01 Issue date: 08-June-2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

	of the substance/mixture and of the company/undertaking
1.1. Product identifier	
Trade name or designation of the mixture	NEW HOME SPRAY 150ml MELA & CANNELLA
Registration number	-
Synonyms	None.
Product code	7SRMC
1.2. Relevant identified uses of t Identified uses	he substance or mixture and uses advised against General Public
Uses advised against	None known.
1.3. Details of the supplier of the	e safety data sheet
Supplier	·····, ·····
Company name Address	Home Fragrance Italia Via A. Tonale 26 Milano 20125 IT
Division	
Telephone	
e-mail	Not available.
Contact person	Not available.
1.4. Emergency telephone number	
1.4. Emergency telephone numb	
General in EU	112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Austria National Poisons Information Centre	+431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Belgium National Poisons Control Center	070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Bulgaria National Toxicological Information Centre	+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Czech Republic National Poisons Information Centre	+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Denmark National Poisons Control Center	+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Estonia National Poisons Information Centre	16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)
Finland National Poison Information Center	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
France National Poisons Control Center	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Hungary National Emergency Phone Number	36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Lithuania Neatidėliotina informacija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

1.4. Emergency telephone numb Netherlands National Poisons Information Center (NVIC)	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)
Norway Norwegian Poison Information Center	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Portugal Poison Centre	800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Romania Biroul RSI si Informare Toxicologica	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)
Slovakia National Toxicological Information Centre	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Sweden National Poison Information Center	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Switzerland Tox Info Suisse	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards Flammable liquids	Category 2	H225 - Highly flammable liquid and vapour.
Health hazards Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Skin sensitisation	Category 1A	H317 - May cause an allergic skin reaction.

2.2. Label elements

Contains:

Label according to Regulation (EC) No. 1272/2008 as amended

Cinnamal, Citrus Aurantium Dulcis Flower Extract, Coumarin, Eugenol, Methylcinnamic aldehyde, Oils, clove, Oils, lemon

Hazard pictograms



Signal word

Hazard statements

H225	
H317	
H319	

Highly flammable liquid and vapour. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statements

Prevention	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P235	Keep cool.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist/vapours.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Response	
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 P362 + P364 P370 + P378	If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.
Storage	
P403 + P235	Store in a well-ventilated place. Keep cool.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental label information	None.
2.3. Other hazards	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General	information

Chemical name	%	CAS-No. / EC No.	REACH Registration No	. Index No.	Notes
Ethanol	80 - 90	64-17-5 200-578-6	-	603-002-00-5	
Class	ification: Flam. Liq.	2;H225, Eye Irrit. 2;H	1319		
Eugenol	1 - 3	97-53-0 202-589-1	-	-	
Class	ification: Eye Irrit. 2 Chronic 4;		H317, Asp. Tox. 1;H304, A	quatic	
Methylcinnamic aldehyde	1 - 3	101-39-3 202-938-8	-	-	
Class	ification: Skin Sens	. 1B;H317			
Propanol, 1(or 2)-(2-methoxymethylethoxy)	1 - 3 - ification: -	34590-94-8 252-104-2	-	-	#
Citrus Aurantium Dulcis Flov Extract		8028-48-6 232-433-8	-	-	
Class		2;H225, Skin Irrit. 2;I sp. Tox. 1;H304, Aqu	H315, Eye Irrit. 2;H319, Ski atic Chronic 2;H411	n Sens.	
Oils, lemon	≤ 1	8008-56-8 616-925-3	-	-	
Class			H315, Eye Irrit. 2;H319, Ski x. 1;H304, Aquatic Chronic		
Cinnamal	≤ 0,3	104-55-2 203-213-9	-	-	
Class			mg/kg), Skin Irrit. 2;H315, l quatic Chronic 3;H412	Eye Irrit.	
Coumarin	≤ 0,3	91-64-5 202-086-7	-	-	
Class	ification: Acute Tox	. 4;H302;(ATE: 500 n	ng/kg), Skin Sens. 1B;H317	7	
Oils, clove	≤ 0,3	8000-34-8 616-772-2	-	-	
Class	ification: Eye Irrit. 2	;H319, Skin Sens. 1	3;H317, Asp. Tox. 1;H304		
Other components below replevels	portable 4.69				
st of abbreviations and symb	ools that may be use	ed above			
ATE: Acute toxicity estimate M: M-factor PBT: persistent, bioaccumul vPvB: very persistent and ve	ative and toxic subst ary bioaccumulative s	substance.	Cae concontrations are in	porcont by volume	#. This
All concentrations are in per substance has been assigned			Gas concentrations are in	percent by volume.	#. 1111S
omposition comments	•	I H-statements is dis	played in section 16.		
ECTION 4: First aid mea	asures				
eneral information	Take off all conta		ediately. Ensure that media ons to protect themselves.		

Material name: NEW HOME SPRAY 150ml MELA & CANNELLA 7SRMC Version #: 01 Issue date: 08-June-2022

before reuse.

4.1. Description of first aid measures

Description of mist ald meas	50165
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
4.2. Most important symptoms and effects, both acute and delayed	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. May cause an allergic skin reaction. Dermatitis. Rash.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	Highly flammable liquid and vapour.
5.1. Extinguishing media Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.		
For emergency responders	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.		
6.2. Environmental precautions	Avoid discharge into drains, water courses or onto the ground.		
6.3. Methods and material for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.		
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.		
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.		
	Never return spills to original containers for re-use.		
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.		

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Not available.

7.3. Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001

Components	Туре	Value
Ethanol (CAS 64-17-5)	Ceiling	3800 mg/m3
		2000 ppm
	MAK	1900 mg/m3
		1000 ppm
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	Ceiling	614 mg/m3
		100 ppm
	MAK	307 mg/m3
		50 ppm
Belgium. Exposure Limit Values		
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1907 mg/m3
		1000 ppm
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	308 mg/m3
(0/10/04/04/07		50 ppm
Bulgaria OFLs Regulation No 13	on protection of workers agai	nst risks of exposure to chemical agents at work
Components	Type	Value
Ethanol (CAS 64-17-5)	TWA	1000 mg/m3
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm
Croatia. Dangerous Substance Ex	posure Limit Values in the Wo	rkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/0
Components	Туре	Value
Ethanol (CAS 64-17-5)		
	MAC	1900 mg/m3
	MAC	1900 mg/m3 1000 ppm
Propanol, 1(or 2)-(2-methoxymethylethoxy)	MAC	-
Propanol, 1(or		1000 ppm
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	MAC	1000 ppm 308 mg/m3
Propanol, 1(or 2)-(2-methoxymethylethoxy)	MAC	1000 ppm 308 mg/m3
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Czech Republic. OELs. Governme	MAC nt Decree 361	1000 ppm 308 mg/m3 50 ppm
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Czech Republic. OELs. Governme Components	MAC nt Decree 361 Type	1000 ppm 308 mg/m3 50 ppm Value 3000 mg/m3
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Czech Republic. OELs. Governmet Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy)	MAC nt Decree 361 Type Ceiling	1000 ppm 308 mg/m3 50 ppm Value
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Czech Republic. OELs. Governmet Components Ethanol (CAS 64-17-5) Propanol, 1(or	MAC nt Decree 361 Type Ceiling TWA	1000 ppm 308 mg/m3 50 ppm Value 3000 mg/m3 1000 mg/m3
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Czech Republic. OELs. Governmen Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	MAC nt Decree 361 Type Ceiling TWA Ceiling	1000 ppm 308 mg/m3 50 ppm Value 3000 mg/m3 1000 mg/m3 550 mg/m3
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Czech Republic. OELs. Governmet Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy)	MAC nt Decree 361 Type Ceiling TWA Ceiling	1000 ppm 308 mg/m3 50 ppm Value 3000 mg/m3 1000 mg/m3 550 mg/m3
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Czech Republic. OELs. Governme Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Denmark. Exposure Limit Values	MAC nt Decree 361 Type Ceiling TWA Ceiling TWA	1000 ppm 308 mg/m3 50 ppm Value 3000 mg/m3 1000 mg/m3 550 mg/m3 270 mg/m3

Components	nit Values Type	Value	
Propanol, 1(or 2)-(2-methoxymethyletho - (CAS 34590-94-8)	TLV	309 mg/m3	
		50 ppm	
Estonia. OELs. Occupa Components	tional Exposure Limits of Hazardous Su Type	bstances (Regulation No. 105/20 Value	001, Annex), as amended
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3	
· · · · · · · · · · · · · · · · · · ·		1000 ppm	
	TWA	1000 mg/m3	
		500 ppm	
Propanol, 1(or 2)-(2-methoxymethyletho (CAS 34590-94-8)	TWA ×y)	308 mg/m3	
(0//0 0+030-0+-0)		50 ppm	
Finland. Workplace Exp		Malaas	
Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	2500 mg/m3	
		1300 ppm	
	TWA	1900 mg/m3	
		1000 ppm	
Propanol, 1(or 2)-(2-methoxymethyletho (CAS 34590-94-8)	TWA xy)	310 mg/m3	
· · · ·		50 ppm	
France, Threshold I imi	t Values (VLEP) for Occupational Expos	ure to Chemicals in France, INR	S FD 984
Components	Туре	Value	
Ethanol (CAS 64-17-5)	VLE	9500 mg/m3	
Regulatory status:	Indicative limit (VL)	-	
		5000 ppm	
Regulatory status:	Indicative limit (VL)		
	VME	1900 mg/m3	
Regulatory status:	Indicative limit (VL)		
		1000 ppm	
	Indicative limit (VL)		
Regulatory status:			
Propanol, 1(or 2)-(2-methoxymethyletho	VME	308 mg/m3	
Regulatory status: Propanol, 1(or 2)-(2-methoxymethyletho - (CAS 34590-94-8) Regulatory status:	VME	308 mg/m3	
Propanol, 1(or 2)-(2-methoxymethyletho - (CAS 34590-94-8)	VME xy) Regulatory binding (VRC)	308 mg/m3 50 ppm	
Propanol, 1(or 2)-(2-methoxymethyletho - (CAS 34590-94-8)	VME xy)	Ĵ	
Propanol, 1(or 2)-(2-methoxymethyletho - (CAS 34590-94-8) Regulatory status: Regulatory status: Germany. DFG MAK Lis	VME xy) Regulatory binding (VRC)	50 ppm	of Chemical Compounds
Propanol, 1(or 2)-(2-methoxymethyletho (CAS 34590-94-8) Regulatory status: Regulatory status: Germany. DFG MAK Lis n the Work Area (DFG)	VME xy) Regulatory binding (VRC) Regulatory binding (VRC)	50 ppm	of Chemical Compounds Form
Propanol, 1(or 2)-(2-methoxymethyletho (CAS 34590-94-8) Regulatory status: Regulatory status: Germany. DFG MAK Lis n the Work Area (DFG) Components	VME xy) Regulatory binding (VRC) Regulatory binding (VRC) it (advisory OELs). Commission for the I	50 ppm	-
Propanol, 1(or 2)-(2-methoxymethyletho (CAS 34590-94-8) Regulatory status: Regulatory status: Germany. DFG MAK Lis n the Work Area (DFG) Components	VME xy) Regulatory binding (VRC) Regulatory binding (VRC) at (advisory OELs). Commission for the I Type	50 ppm Investigation of Health Hazards Value	-
Propanol, 1(or 2)-(2-methoxymethyletho (CAS 34590-94-8) Regulatory status: Regulatory status: Germany. DFG MAK Lis n the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethyletho	VME xy) Regulatory binding (VRC) Regulatory binding (VRC) at (advisory OELs). Commission for the I Type TWA	50 ppm Investigation of Health Hazards Value 380 mg/m3	-
Propanol, 1(or 2)-(2-methoxymethyletho (CAS 34590-94-8) Regulatory status: Regulatory status: Germany. DFG MAK Lis n the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethyletho	VME xy) Regulatory binding (VRC) Regulatory binding (VRC) at (advisory OELs). Commission for the I Type TWA	50 ppm Investigation of Health Hazards Value 380 mg/m3 200 ppm	Form
Propanol, 1(or 2)-(2-methoxymethyletho (CAS 34590-94-8) Regulatory status: Regulatory status: Germany. DFG MAK Lis n the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethyletho (CAS 34590-94-8) Germany. TRGS 900, Li	VME xy) Regulatory binding (VRC) Regulatory binding (VRC) at (advisory OELs). Commission for the l Type TWA xy) mit Values in the Ambient Air at the Wor	50 ppm Investigation of Health Hazards Value 380 mg/m3 200 ppm 310 mg/m3 50 ppm	Form Vapour. Vapour.
Propanol, 1(or 2)-(2-methoxymethyletho (CAS 34590-94-8) Regulatory status: Regulatory status: Germany. DFG MAK Lis n the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethyletho (CAS 34590-94-8) Germany. TRGS 900, Li Components	VME xy) Regulatory binding (VRC) Regulatory binding (VRC) at (advisory OELs). Commission for the l Type TWA xy) TWA xy) mit Values in the Ambient Air at the Wor Type	50 ppm Investigation of Health Hazards Value 380 mg/m3 200 ppm 310 mg/m3 50 ppm rkplace Value	Form Vapour.
Propanol, 1(or 2)-(2-methoxymethyletho - (CAS 34590-94-8) Regulatory status: Regulatory status: Germany. DFG MAK Liss in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethyletho - (CAS 34590-94-8)	VME xy) Regulatory binding (VRC) Regulatory binding (VRC) at (advisory OELs). Commission for the l Type TWA xy) mit Values in the Ambient Air at the Wor	50 ppm Investigation of Health Hazards Value 380 mg/m3 200 ppm 310 mg/m3 50 ppm	Form Vapour. Vapour.

Germany. TRGS 900, Limit Values in the Components	e Ambient Air at the Workplace Type	Value	Form
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	AGW	310 mg/m3	Vapour and aerosol.
		50 ppm	Vapour and aerosol.
Greece. OELs (Decree No. 90/1999, as a Components	imended) Type	Value	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	STEL	900 mg/m3	
		150 ppm	
	TWA	600 mg/m3	
		100 ppm	
Hungary. OELs. Joint Decree on Chemic Components	cal Safety of Workplaces Type	Value	
Ethanol (CAS 64-17-5)	STEL	3800 mg/m3	
	TWA	1900 mg/m3	
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	308 mg/m3	
Iceland. OELs. Regulation 154/1999 on Components	occupational exposure limits Type	Value	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	300 mg/m3	
````		50 ppm	
Ireland. Occupational Exposure Limits Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	308 mg/m3	
		50 ppm	
Italy. Occupational Exposure Limits Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	308 mg/m3	
		50 ppm	
Latvia. OELs. Occupational exposure lin Components	mit values of chemical substances Type	in work environme Value	nt
Ethanol (CAS 64-17-5)	TWA	1000 mg/m3	
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	308 mg/m3	
		50 ppm	
Lithuania. OELs. Limit Values for Chen Components	nical Substances, General Require Type	ments Value	
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3	
	TWA	1000 ppm 1000 mg/m3	
		i soo mg/mo	

# Lithuania. OELs. Limit Values for Chemical Substances, General RequirementsComponentsTypeValuePropanol, 1(or<br/>2)-(2-methoxymethylethoxy)<br/>- (CAS 34590-94-8)STEL500 ppmTWA75 ppmTWA308 mg/m350 ppm

# Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)

Schedules I and V)		
Components	Туре	Value
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm
Netherlands. OELs (binding)		
Components	Туре	Value
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3
	TWA	260 mg/m3
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	300 mg/m3
Norway. Administrative Norms for	Contaminants in the Workp	lace
Components	Туре	Value
Ethanol (CAS 64-17-5)	TLV	950 mg/m3
		500 ppm
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TLV	300 mg/m3
(0/(0 04030 34 0)		50 ppm
Poland Ordinance of the Minister	of Labour and Social Policy	on 6 June 2014 on the maximum permissible
		work environment, Journal of Laws 2014, item 817
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3
		0 ppm
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	STEL	480 mg/m3
- (CAS 34590-94-8)		
- (CAS 34590-94-8)		0 ppm
- (CAS 34590-94-8)	TWA	0 ppm 240 mg/m3
- (CAS 34590-94-8)	TWA	
		240 mg/m3 0 ppm
Portugal. OELs. Decree-Law n. 290		240 mg/m3 0 ppm
Portugal. OELs. Decree-Law n. 290 Components Propanol, 1(or 2)-(2-methoxymethylethoxy)	)/2001 (Journal of the Reput	240 mg/m3 0 ppm Dic - 1 Series A, n.266)
Portugal. OELs. Decree-Law n. 290 Components Propanol, 1(or 2)-(2-methoxymethylethoxy)	)/2001 (Journal of the Reput Type	240 mg/m3 0 ppm Dic - 1 Series A, n.266) Value
Portugal. OELs. Decree-Law n. 290 Components Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	0/2001 (Journal of the Reput Type TWA	240 mg/m3 0 ppm Dic - 1 Series A, n.266) Value 308 mg/m3 50 ppm
Portugal. OELs. Decree-Law n. 290 Components Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Portugal. VLEs. Norm on occupatio	0/2001 (Journal of the Reput Type TWA	240 mg/m3 0 ppm Dic - 1 Series A, n.266) Value 308 mg/m3 50 ppm
Portugal. OELs. Decree-Law n. 290 Components Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Portugal. VLEs. Norm on occupatio Components	0/2001 (Journal of the Reput Type TWA onal exposure to chemical a	240 mg/m3 0 ppm blic - 1 Series A, n.266) Value 308 mg/m3 50 ppm sgents (NP 1796)
Portugal. OELs. Decree-Law n. 290 Components Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Portugal. VLEs. Norm on occupation Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy)	0/2001 (Journal of the Reput Type TWA onal exposure to chemical a Type	240 mg/m3 0 ppm blic - 1 Series A, n.266) Value 308 mg/m3 50 ppm bgents (NP 1796) Value
Portugal. OELs. Decree-Law n. 290 Components Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Portugal. VLEs. Norm on occupation Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy)	0/2001 (Journal of the Reput Type TWA onal exposure to chemical a Type TWA	240 mg/m3 0 ppm blic - 1 Series A, n.266) Value 308 mg/m3 50 ppm bgents (NP 1796) Value 1000 ppm
Portugal. OELs. Decree-Law n. 290 Components Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Portugal. VLEs. Norm on occupation Components Ethanol (CAS 64-17-5) Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8) Romania. OELs. Protection of work	0/2001 (Journal of the Reput Type TWA onal exposure to chemical a Type TWA STEL TWA Kers from exposure to chem	240 mg/m3 0 ppm olic - 1 Series A, n.266) Value 308 mg/m3 50 ppm bgents (NP 1796) Value 1000 ppm 150 ppm 100 ppm 100 ppm
<ul> <li>- (CAS 34590-94-8)</li> <li>Portugal. OELs. Decree-Law n. 290 Components</li> <li>Propanol, 1(or 2)-(2-methoxymethylethoxy)</li> <li>- (CAS 34590-94-8)</li> <li>Portugal. VLEs. Norm on occupation Components</li> <li>Ethanol (CAS 64-17-5)</li> <li>Propanol, 1(or 2)-(2-methoxymethylethoxy)</li> <li>- (CAS 34590-94-8)</li> <li>Romania. OELs. Protection of work Components</li> <li>Ethanol (CAS 64-17-5)</li> </ul>	0/2001 (Journal of the Reput TWA TWA onal exposure to chemical a Type TWA STEL TWA	240 mg/m3 0 ppm blic - 1 Series A, n.266) Value 308 mg/m3 50 ppm 50 ppm 1000 ppm 150 ppm 100 ppm 100 ppm

# Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Туре	Value	
		5000 ppm	
	TWA	1900 mg/m3	
		1000 ppm	
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	308 mg/m3	
		50 ppm	

# Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1920 mg/m3	
		1000 ppm	
	TWA	960 mg/m3	
		500 ppm	
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	308 mg/m3	
		50 ppm	

# Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Туре	Value	
Ethanol (CAS 64-17-5)	TWA	960 mg/m3	
		500 ppm	
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	308 mg/m3	
		50 ppm	
Spain. Occupational Exposure Lim	its		
Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1910 mg/m3	
		1000 ppm	
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	TWA	308 mg/m3	
		50 ppm	
Sweden. OELs. Work Environment	Authority (AV), Occupation	al Exposure Limit Values (AFS	2015:7)
Components	Туре	Value	,
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3	
		1000 ppm	
	TWA	1000 mg/m3	
		500 ppm	
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	STEL	450 mg/m3	
		75 ppm	
	TWA	300 mg/m3	
		50 ppm	
Switzerland. SUVA Grenzwerte am	Arbeitsplatz		
Components	Туре	Value	Form
Ethanol (CAS 64-17-5)	STEL	1920 mg/m3	
		1000 ppm	
	TWA	960 mg/m3	
		500 ppm	
Propanol, 1(or 2)-(2-methoxymethylethoxy) - (CAS 34590-94-8)	STEL	300 mg/m3	Vapour and aerosol.

# Switzerland. SUVA Grenzwerte am Arbeitsplatz

TWA ure Limits (WELs) Type TWA TWA TWA	50 ppm 300 mg/m3 50 ppm <b>Value</b> 1920 mg/m 1000 ppm 308 mg/m3	Vapour and aerosol.
ure Limits (WELs) Type TWA TWA	50 ppm <b>Value</b> 1920 mg/m 1000 ppm 308 mg/m3	Vapour and aerosol.
Type TWA TWA	Value 1920 mg/m 1000 ppm 308 mg/m3	13
Type TWA TWA	1920 mg/m 1000 ppm 308 mg/m3	
TWA TWA	1000 ppm 308 mg/m3	
TWA it Values in Directives 91/	1000 ppm 308 mg/m3	
it Values in Directives 91/⊧	308 mg/m3	
	50 ppm	
	322/EEC, 2000/39/EC, 2006/15/EC, 2 Value	2009/161/EU, 2017/164/EU
TWA	308 mg/m3	
	50 ppm	
No biological exposure lim		
•	<b>e</b> ()	
	-	
Not available.		
Not available.		
on		
	Can be absorbed through the s	kin.
	Can be absorbed through the s	kin.
oxymethylethoxy)-	Can be absorbed through the s	kin.
ion		
oxymethylethoxy)-	Can be absorbed through the s	kin.
oxymethylethoxy)-	Can be absorbed through the s	kin.
on		
	Can be absorbed through the s	kin.
tion		
	Can be absorbed through the s	kin.
	-	
-	Can be absorbed through the el	kin
	oun so assorsou unough the s	
-		1.4
oxymetnylethoxy)-	Can be absorbed through the s	KIN.
on		
oxymethylethoxy)-	Can be absorbed through the s	kin.
on		
	Can be absorbed through the s	kin.
ion		
	Can be absorbed through the s	kin.
	Type         TWA         No biological exposure lime         Follow standard monitoring         Not available.         Not available.         Not available.         on         oxymethylethoxy)-         ation         oxymethylethoxy)-         ation	TypeValueTWA308 mg/m350 ppm50 ppmNo biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures.50 ppmNot available.Not available.Not available.Can be absorbed through the siteon oxymethylethoxy)-Can be absorbed through the siteation oxymethylethoxy)-Can be absorbed through the siteoxymethylethoxy)-Can be absorbed through the siteation oxymethylethoxy)-Can be absorbed through the siteoxymethylethoxy)-Can be absorbed through the sitecosymethylethoxy)-Can be absorbed through the sitecon oxymethylethoxy)-Can be absorbed through the si

7SRMC Version #: 01 Issue date: 08-June-2022

Ireland Exposure Limit Valu	es: Skin designation	
Propanol, 1(or 2)-(2-meth (CAS 34590-94-8)	-	Can be absorbed through the skin.
Italy OELs: Skin designation	n	
Propanol, 1(or 2)-(2-meth (CAS 34590-94-8)		Danger of cutaneous absorption
Latvia OELs: Skin designat		
Propanol, 1(or 2)-(2-meth (CAS 34590-94-8)		Can be absorbed through the skin.
Lithuania OELs: Skin desig	nation	
Propanol, 1(or 2)-(2-meth (CAS 34590-94-8)	noxymethylethoxy)-	Can be absorbed through the skin.
Luxembourg OELs: Skin de	signation	
Propanol, 1(or 2)-(2-meth (CAS 34590-94-8)	noxymethylethoxy)-	Can be absorbed through the skin.
Malta OELs: Skin designation	on	
Propanol, 1(or 2)-(2-meth (CAS 34590-94-8)	noxymethylethoxy)-	Can be absorbed through the skin.
Netherlands OELs (binding)	): Skin designation	
Ethanol (CAS 64-17-5) Norway Exposure Limit Val	-	Can be absorbed through the skin.
Propanol, 1(or 2)-(2-meth	-	Can be absorbed through the skin.
(CAS 34590-94-8) Portugal OELs: Skin design		
Propanol, 1(or 2)-(2-meth (CAS 34590-94-8)		Can be absorbed through the skin.
	cupatioinal Exposure: Skin d	esignation
Propanol, 1(or 2)-(2-metr (CAS 34590-94-8)		Can be absorbed through the skin.
Romania OELs: Skin desigr	nation	
Propanol, 1(or 2)-(2-meth (CAS 34590-94-8)		Can be absorbed through the skin.
Slovakia OELs: Skin design		
Propanol, 1(or 2)-(2-meth (CAS 34590-94-8)		Can be absorbed through the skin.
(Official Gazette of the Repu	ublic of Slovenia)	vorkers against risks due to exposure to chemicals while working
Propanol, 1(or 2)-(2-meth (CAS 34590-94-8) Spain OELs: Skin designati		Can be absorbed through the skin.
Propanol, 1(or 2)-(2-meth (CAS 34590-94-8)		Can be absorbed through the skin.
Sweden Threshold Limit Va	lues: Skin designation	
Propanol, 1(or 2)-(2-metł (CAS 34590-94-8)		Can be absorbed through the skin.
UK EH40 WEL: Skin design Propanol, 1(or 2)-(2-meth		Can be absorbed through the skin.
(CAS 34590-94-8)		
2. Exposure controls		
opropriate engineering ontrols	Ventilation rates should be n exhaust ventilation, or other exposure limits. If exposure	local exhaust ventilation. Good general ventilation should be used. natched to conditions. If applicable, use process enclosures, local engineering controls to maintain airborne levels below recommended limits have not been established, maintain airborne levels to an ewash station and safety shower.
dividual protection measures, General information	Use personal protective equ	e equipment ipment as required. Personal protection equipment should be chosen ards and in discussion with the supplier of the personal protective
Eye/face protection		le shields (or goggles). Face shield is recommended.
		· · · · · · · · · · · · · · · · · · ·
Skin protection - Hand protection	Wear appropriate chemical r	resistant gloves.
- Other		esistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If engineering controls do no	t maintain airborne concentrations below recommended exposure
Thermal becards	been established), an appro	o an acceptable level (in countries where exposure limits have not ved respirator must be worn.
Thermal hazards	wear appropriate thermal pr	otective clothing, when necessary.

Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

3.1. Information on basic physic	al and chemical properties
Physical state	Liquid.
Form	Liquid.
Colour	Not available.
Odour	Not available.
Melting point/freezing point	-114,1 °C (-173,38 °F) estimated
Boiling point or initial boiling point and boiling range	78,29 °C (172,92 °F) estimated
Flammability (solid, gas)	Not applicable.
Flash point	13 °C (55,4 °F) estimated
Auto-ignition temperature	363 °C (685,4 °F) estimated
Decomposition temperature	Not available.
рН	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Vapour pressure	79,06 hPa estimated
Vapour density	Not available.
Relative density	Not available.
Particle characteristics	Not available.
9.2. Other information	
9.2.1. Information with regard to physical hazard classes	No relevant additional information available.
9.2.2. Other safety characteristic	S
Density	0,812 g/cm3 estimated
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
Percent volatile	93,46 % estimated
Specific gravity	0,81235 estimated
VOC	90,7 % estimated
SECTION 10: Stability and	-
10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.
SECTION 11: Toxicologica	I information

# **SECTION 11: Toxicological information**

General information	Occupational exposure to the substance or mixture may cause adverse effects.	
Information on likely routes of exposure		
Inhalation	Prolonged inhalation may be harmful.	
Skin contact	May cause an allergic skin reaction.	
Eye contact	Causes serious eye irritation.	

Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. May cause an allergic skin reaction. Dermatitis. Rash.
11.1. Information on toxicologic	al effects
Acute toxicity	No data available.
Skin corrosion/irritation	Due to partial or complete lack of data the classification is not possible.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory sensitisation	Due to partial or complete lack of data the classification is not possible.
Skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.
Carcinogenicity	Due to partial or complete lack of data the classification is not possible.
Hungary. 26/2000 EüM Ordir (as amended)	nance on protection against and preventing risk relating to exposure to carcinogens at work
Not listed.	
	Evaluation of Carcinogenicity
Coumarin (CAS 91-64-5) Eugenol (CAS 97-53-0)	<ul><li>3 Not classifiable as to carcinogenicity to humans.</li><li>3 Not classifiable as to carcinogenicity to humans.</li></ul>
Reproductive toxicity	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - repeated exposure	Due to partial or complete lack of data the classification is not possible.
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.
Mixture versus substance information	No information available.
11.2. Information on other hazar	ds
Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Other information	Not available.
SECTION 12: Ecological ir	Iformation

# **SECTION 12: Ecological information**

12.1. Toxicity

Based on available data, the classification criteria are not met for hazardous to the aquatic environment.

	onvironnie		
Components		Species	Test Results
Coumarin (CAS 91-64-5)			
Aquatic			
Acute			
Fish	LC50	Guppy (Poecilia reticulata)	>= 32 - <= 100 mg/l, 96 hours
Ethanol (CAS 64-17-5)			
Aquatic			
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	>= 7,7 - <= 11,2 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	42 mg/l, 4 days
Eugenol (CAS 97-53-0)			
Aquatic			
Acute			
Fish	LC50	Fathead minnow (Pimephales prom	elas) 24 mg/l, 96 hours
12.2. Persistence and degradability	No data is	available on the degradability of any ingre	edients in the mixture.
12.3. Bioaccumulative poten	ntial		
Partition coefficient n-octanol/water (log Kow)			
Cinnamal		1,9	
		2,1	
Citrus Aurantium Dulcis F	lower Extract	2,107 4,38	
		4,00	

Coumarin Ethanol Eugenol Methylcinnamic aldehyde	1,39 -0,31 2,49 2,319
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.
12.6. Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7. Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.
12.8. Additional information	
Estonia Dangerous substan	ces in soil Data
Ethanol (CAS 64-17-5)	Chemical pesticides (As the total sum of the active substances) 0,5 mg/kg Chemical pesticides (As the total sum of the active substances) 20 mg/kg Chemical pesticides (As the total sum of the active substances) 5 mg/kg
Eugenol (CAS 97-53-0)	Chemical pesticides (As the total sum of the active substances) 0,5 mg/kg Chemical pesticides (As the total sum of the active substances) 20 mg/kg Chemical pesticides (As the total sum of the active substances) 5 mg/kg

# **SECTION 13: Disposal considerations**

13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

# **SECTION 14: Transport information**

ADR	
14.1. UN number	UN1993
14.2. UN proper shipping	FLAMMABLE LIQUID, N.O.S. (vapour pressure at
name	50 °C more than 110 kPa) (Ethanol, Eugenol)
14.3. Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Hazard No. (ADR)	33
Tunnel restriction code	D/E
14.4. Packing group	II
14.5. Environmental hazards	s No.
14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
for user	
RID	
14.1. UN number	UN1993
14.2. UN proper shipping	FLAMMABLE LIQUID, N.O.S. (vapour pressure at 50 °C not more than 110 kPa) (Ethanol,
name	Eugenol)
14.3. Transport hazard class	e(es)
Class	3
Subsidiary risk	-
Label(s)	3
14.4. Packing group	II
14.5. Environmental hazards	s No.

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions for user ADN 14.1. UN number UN1993 14.2. UN proper shipping FLAMMABLE LIQUID, N.O.S. (Ethanol, Eugenol) name 14.3. Transport hazard class(es) Class 3 Subsidiary risk _ Label(s) 3 Ш 14.4. Packing group 14.5. Environmental hazards No. 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user ΙΑΤΑ 14.1. UN number UN1993 Flammable liquid, n.o.s. (Ethanol, Eugenol) 14.2. UN proper shipping name 14.3. Transport hazard class(es) 3 Class Subsidiary risk _ Ш 14.4. Packing group 14.5. Environmental hazards Yes ERG Code 3H 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user Other information Allowed with restrictions. Passenger and cargo aircraft Allowed with restrictions. Cargo aircraft only IMDG 14.1. UN number UN1993 14.2. UN proper shipping FLAMMABLE LIQUID, N.O.S. (Ethanol, Eugenol), MARINE POLLUTANT name 14.3. Transport hazard class(es) Class 3 Subsidiary risk -14.4. Packing group Ш 14.5. Environmental hazards Marine pollutant Yes EmS F-E, S-E 14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling. for user alpha-Pinene alpha-Pinene 14.7. Maritime transport in bulk Not established. according to IMO instruments

# ADN; ADR; IATA; IMDG; RID



Marine pollutant



IMDG Regulated Marine Pollutant.

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.
- Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

# Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

# Restrictions on use

- Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Ethanol (CAS 64-17-5)
- Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.
  - Not listed.

# Other EU regulations

# Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Ethanol (CAS 64-17-5)

Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.
National regulations	Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.
15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out.

# **SECTION 16: Other information**

List of abbreviations	
	ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
	AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
	CAS: Chemical Abstract Service.
	CEN: European Committee for Standardization.
	IATA: International Air Transport Association.
	IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
	IMDG: International Maritime Dangerous Goods.

	MAC: Maximum Allowed Concentration. MARPOL: International Convention for the Prevention of Pollution from Ships. PBT: Persistent, bioaccumulative and toxic. RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value. vPvB: Very persistent and very bioaccumulative.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any H-statements not written out in full under	
Sections 2 to 15	<ul> <li>H225 Highly flammable liquid and vapour.</li> <li>H302 Harmful if swallowed.</li> <li>H304 May be fatal if swallowed and enters airways.</li> <li>H312 Harmful in contact with skin.</li> <li>H315 Causes skin irritation.</li> <li>H317 May cause an allergic skin reaction.</li> <li>H319 Causes serious eye irritation.</li> <li>H361 Suspected of damaging fertility or the unborn child.</li> <li>H411 Toxic to aquatic life with long lasting effects.</li> <li>H412 Harmful to aquatic life with long lasting effects.</li> <li>H413 May cause long lasting harmful effects to aquatic life.</li> </ul>
Revision information	None.
Training information	Follow training instructions when handling this material.
Disclaimer	Home Fragrance Italia cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.