SAFETY DATA SHEET

Version #: 01

Issue date: 28-September-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

FRAGRANCE DIFFUSER 100ml - SOFT LEATHER 41MDSF

Registration number

of the mixture

Synonyms None **Product code** 41MDSF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses General Public Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Supplier

Company name Home Fragrance Italia S.r.L. Address Via del Commercio 28

Bernareggio (MB)

20881 IT

Division Telephone

Not available. e-mail Not available. Contact person

1.4. Emergency telephone

number

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons Information Centre

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons Control Centre

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

Toxicological Information

Centre

+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Czech Republic National Poisons Information

Centre

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons Control Centre

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Estonia National Poisons Information Centre

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Centre

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Centre

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Hungary National Emergency Phone Number

36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus +370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

1.4. Emergency telephone number

Malta Accident and 2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.) **Emergency Department**

Netherlands National Poisons Information Centre (NVIC)

030-274 88 88 (Only for the purpose of informing medical personnel in cases of

acute intoxications)

Norway Norwegian Poison

Information Centre

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

800 250 250 (Available 24 hours a day. SDS/Product information may not be **Portugal Poison Centre**

available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

available for the Emergency Service.)

Slovakia National **Toxicological Information**

Centre

+421 2 5477 4166 (Available 24 hours a day, SDS/Product information may not be available for the Emergency Service.)

Sweden National Poison Information Centre

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info Suisse

145 (Available 24 hours a day, SDS/Product information may not be available for

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids Category 2 H225 - Highly flammable liquid and

vapour.

Health hazards

Serious eye damage/eye irritation H319 - Causes serious eye Category 2

irritation.

Skin sensitisation Category 1B H317 - May cause an allergic skin

reaction.

Environmental hazards

Hazardous to the aquatic environment,

long-term aquatic hazard

Category 2 H411 - Toxic to aquatic life with

long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

UFI:

Austria: EGWM-AEM2-R91S-KM2D Belgium: EGWM-AEM2-R91S-KM2D Bulgaria: EGWM-AEM2-R91S-KM2D Croatia: EGWM-AEM2-R91S-KM2D Cyprus: EGWM-AEM2-R91S-KM2D

Cyprus. EGWM-AEM2-R913-RM2D
Czech Republic: EGWM-AEM2-R91S-KM2D
Denmark: EGWM-AEM2-R91S-KM2D
Estonia: EGWM-AEM2-R91S-KM2D
EU: EGWM-AEM2-R91S-KM2D
Finland: EGWM-AEM2-R91S-KM2D
France: EGWM-AEM2-R91S-KM2D
Germany: FGWM-AEM2-R91S-KM2D

Germany: EGWM-AEMZ-R91S-KMZD
Great Britain: EGWM-AEMZ-R91S-KMZD
Greece: EGWM-AEMZ-R91S-KMZD
Hungary: EGWM-AEMZ-R91S-KMZD
Iceland: EGWM-AEMZ-R91S-KMZD
Ireland: EGWM-AEMZ-R91S-KMZD
Italy: EGWM-AEMZ-R91S-KMZD
Latvia: EGWM-AEMZ-R91S-KMZD
Lithuania: EGWM-AEMZ-R91S-KMZD

Luxembourg: EGWM-AEM2-R91S-KM2D Malta: EGWM-AEM2-R91S-KM2D Netherlands: EGWM-AEM2-R91S-KM2D Norway: EGWM-AEM2-R91S-KM2D Poland: EGWM-AEM2-R91S-KM2D Portugal: EGWM-AEM2-R91S-KM2D Romania: EGWM-AEM2-R91S-KM2D

Slovakia: EGWM-AEM2-R91S-KM2D Slovenia: EGWM-AEM2-R91S-KM2D Spain: EGWM-AEM2-R91S-KM2D Sweden: EGWM-AEM2-R91S-KM2D

Contains: Alpha-isomethyl ionone, Cyclamen aldehyde, Ethyl 2,2-dimethylhydrocinnamal,

g-Methoxycedrane, Isocyclemone E, Linalool, Linalyl acetate, Oils, cedarwood, Oils, lavandin,

Oils, mandarin

Hazard pictograms







Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

Storage Not applicable.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or

Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name		70.00		REACH Registration No		Notes
Ethanol		70 - 80	64-17-5 200-578-6	-	603-002-00-5	
	Classification:	Flam. Liq.	2;H225, Eye Irrit. 2;H	1319		
Isocyclemone E		1 - 3	54464-57-2 259-174-3	-	-	
	Classification:	Skin Irrit. 2	2;H315, Skin Sens. 1	B;H317, Aquatic Chronic 2	;H411	
Linalool		1 - 3	78-70-6 201-134-4	01-2119474016-42	603-235-00-2	
	Classification:	Skin Irrit. 2	2;H315, Eye Irrit. 2;H	319, Skin Sens. 1B;H317		
Linalyl acetate		1 - 3	115-95-7 204-116-4	-	-	
	Classification:	Skin Irrit. 2	2;H315, Eye Irrit. 2;H	319, Skin Sens. 1B;H317		
g-Methoxycedrane		≤ 1	19870-74-7 243-384-7	-	-	
	Classification:	Skin Sens Chronic 1;		cute 1;H400(M=1), Aquatic	:	
Oils, mandarin		≤ 1	8008-31-9 616-920-6	-	-	
	Classification:		3;H226, Skin Irrit. 2; 1;H304, Aquatic Chr	H315, Skin Sens. 1;H317, F onic 2;H411	Repr. 2;H361,	
2-Buten-1-ol, 2-methyl-4-(2,2,3-trim ten-1-yl)-	nethyl-3-cycloper	≤ 0,3	28219-60-5 248-907-2	-	-	
	Classification:	Skin Irrit. 2	2;H315, Eye Irrit. 2;H	319, Aquatic Acute 1;H400	(M=1)	
Oils, lavandin		≤ 0,3	8022-15-9 617-009-6	-	-	
	Classification:	Eye Dam. Chronic 3;		1B;H317, Asp. Tox. 1;H304	, Aquatic	
Alpha-isomethyl ionoi	ne	≤ 0,2	127-51-5 204-846-3	-	-	
	Classification:	Skin Sens	. 1B;H317, Aquatic C	Chronic 2;H411		
Cyclamen aldehyde		≤ 0,2	103-95-7 203-161-7	01-2119970582-32	-	
	Classification:	Skin Irrit. 2	2;H315, Skin Sens. 1	B;H317, Aquatic Chronic 3;	H412	
Ethyl 2,2-dimethylhyd	Irocinnamal	≤ 0,2	67634-15-5 266-819-2	-	-	
	Classification:		2;H315, Skin Sens. 1 hronic 2;H411	B;H317, Aquatic Acute 1;H	400(M=1),	
Oils, cedarwood		≤ 0,2	8000-27-9 616-769-6	-	-	
	Classification:	Skin Irrit. 2 Chronic 2		B;H317, Asp. Tox. 1;H304,	Aquatic	
delta-Damascone		≤ 0,1	57378-68-4 260-709-8	-	-	
	Classification:			ng/kg bw), Skin Irrit. 2;H315 0, Aquatic Chronic 1;H410	5, Skin Sens.	
Oxacycloheptadec-10)-en-2-one	≤ 0,1	28645-51-4 249-120-7	-	-	
	Classification:	Aquatic A	cute 1;H400(M=10), A	Aquatic Chronic 1;H410(M=	:10)	
-		≤ 0,1	23696-85-7 245-833-2	-	-	
Rose Ketone-4			240-000-2			

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The full text for all H-statements is displayed in section 16. **Composition comments**

SECTION 4: First aid measures

General information Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves. Wash contaminated clothing

before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eve contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

4.2. Most important symptoms and effects, both acute and

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing, May cause an allergic skin reaction. Dermatitis, Rash.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation.

Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Highly flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing

media

delayed

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

5.2. Special hazards arising from the substance or mixture Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Special fire fighting procedures

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate

protective clothing.

For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Material name: FRAGRANCE DIFFUSER 100ml - SOFT LEATHER 41MDSF 41MDSF Version #: 01 Issue date: 28-September-2023

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001

8.1. Control parameters

Occupational exposure limits

Components	Туре	Value
Ethanol (CAS 64-17-5)	Ceiling	3800 mg/m3
		2000 ppm
	MAK	1900 mg/m3
		1000 ppm
Belgium. Exposure Limit Values		
Components	Туре	Value
Ethanol (CAS 64-17-5)	TWA	1907 mg/m3
		1000 ppm
Bulgaria. OELs. Regulation No 1	_	
Components	Туре	Value
	Type TWA	1000 mg/m3
Components Ethanol (CAS 64-17-5)	TWA	
Components Ethanol (CAS 64-17-5) Croatia. Dangerous Substance E	TWA Exposure Limit Values in the Wo	1000 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09
Components Ethanol (CAS 64-17-5) Croatia. Dangerous Substance E Components	TWA Exposure Limit Values in the Wo Type	1000 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Value
Components Ethanol (CAS 64-17-5) Croatia. Dangerous Substance E Components	TWA Exposure Limit Values in the Wo Type MAC	1000 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Value 1900 mg/m3
Components Ethanol (CAS 64-17-5) Croatia. Dangerous Substance E Components Ethanol (CAS 64-17-5)	TWA Exposure Limit Values in the Wo Type MAC	1000 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Value 1900 mg/m3
Components Ethanol (CAS 64-17-5) Croatia. Dangerous Substance E Components Ethanol (CAS 64-17-5) Czech Republic. OELs. Governm	TWA Exposure Limit Values in the Wo Type MAC nent Decree 361	1000 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Value 1900 mg/m3 1000 ppm
Components Ethanol (CAS 64-17-5) Croatia. Dangerous Substance E Components Ethanol (CAS 64-17-5) Czech Republic. OELs. Governn Components	TWA Exposure Limit Values in the Wo Type MAC ment Decree 361 Type	1000 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Value 1900 mg/m3 1000 ppm Value
Components Ethanol (CAS 64-17-5) Croatia. Dangerous Substance E Components Ethanol (CAS 64-17-5) Czech Republic. OELs. Governn Components	TWA Exposure Limit Values in the Wo Type MAC ment Decree 361 Type Ceiling TWA	1000 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Value 1900 mg/m3 1000 ppm Value 3000 mg/m3
Components Ethanol (CAS 64-17-5) Croatia. Dangerous Substance E Components Ethanol (CAS 64-17-5) Czech Republic. OELs. Governn Components Ethanol (CAS 64-17-5) Denmark. Exposure Limit Values	TWA Exposure Limit Values in the Wo Type MAC ment Decree 361 Type Ceiling TWA	1000 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Value 1900 mg/m3 1000 ppm Value 3000 mg/m3
Components Ethanol (CAS 64-17-5) Croatia. Dangerous Substance E Components Ethanol (CAS 64-17-5) Czech Republic. OELs. Governm Components Ethanol (CAS 64-17-5)	TWA Exposure Limit Values in the Wo Type MAC ment Decree 361 Type Ceiling TWA	1000 mg/m3 orkplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09 Value 1900 mg/m3 1000 ppm Value 3000 mg/m3 1000 mg/m3

Components	tional Exposure Limits of Hazardous Substances (Type	Value	,,, 20 3
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3	
,		1000 ppm	
	TWA	1000 mg/m3	
		500 ppm	
Finland. Workplace Exp	osure Limits		
Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	2500 mg/m3	
		1300 ppm	
	TWA	1900 mg/m3	
		1000 ppm	
France, Threshold Limit	: Values (VLEP) for Occupational Exposure to Che	emicals in France. IN	IRS FD 984
Components	Type	Value	LD 00-
Ethanol (CAS 64-17-5)	VLE	9500 mg/m3	
Regulatory status:	Indicative limit (VL)	-	
		5000 ppm	
Regulatory status:	Indicative limit (VL)		
	VME	1900 mg/m3	
Regulatory status:	Indicative limit (VL)		
		1000 ppm	
Regulatory status:	Indicative limit (VL)		
	,		
Germany. DFG MAK List	t (advisory OELs). Commission for the Investigati	on of Health Hazard	s of Chemical Compoun
Germany. DFG MAK List n the Work Area (DFG)	,	on of Health Hazard Value	s of Chemical Compoun
Germany. DFG MAK List n the Work Area (DFG) Components	t (advisory OELs). Commission for the Investigati		•
Germany. DFG MAK List in the Work Area (DFG) Components	t (advisory OELs). Commission for the Investigati	Value	•
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS	t (advisory OELs). Commission for the Investigati	Value 380 mg/m3	•
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8)	Type TWA TWA	Value 380 mg/m3 200 ppm	Form Vapor and aerosol,
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin	t (advisory OELs). Commission for the Investigati Type TWA	Value 380 mg/m3 200 ppm	Form Vapor and aerosol,
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace	Value 380 mg/m3 200 ppm 100 mg/m3	Form Vapor and aerosol, inhalable fraction.
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type	Value 380 mg/m3 200 ppm 100 mg/m3 Value	Form Vapor and aerosol, inhalable fraction.
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lir Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3	Form Vapor and aerosol, inhalable fraction.
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lir Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type AGW	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm	Form Vapor and aerosol, inhalable fraction. Form
Germany. DFG MAK List n the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Greece. OELs (Decree N	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type AGW AGW Io. 90/1999, as amended)	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm 100 mg/m3	Form Vapor and aerosol, inhalable fraction. Form
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Greece. OELs (Decree Nomponents	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type AGW AGW Io. 90/1999, as amended) Type	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm 100 mg/m3 Value	Form Vapor and aerosol, inhalable fraction. Form
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8)	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type AGW AGW Io. 90/1999, as amended)	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm 100 mg/m3 Value 1900 mg/m3	Form Vapor and aerosol, inhalable fraction. Form
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lincomponents Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Greece. OELs (Decree Nomponents	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type AGW AGW Io. 90/1999, as amended) Type	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm 100 mg/m3 Value	Form Vapor and aerosol, inhalable fraction. Form
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lincomponents Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Greece. OELs (Decree Nomponents Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decree Nomponents	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type AGW AGW AGW TWA TWA TYPE AGW AGW AGW AGW TYPE TWA TWA	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm 100 mg/m3 Value 1900 mg/m3 1000 ppm	Form Vapor and aerosol, inhalable fraction. Form
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Greece. OELs (Decree No Components Ethanol (CAS 64-17-5) Hungary. OELs. Joint De Components	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type AGW AGW AGW TWA TWA Type Type Type AGW AGW AGW AGW AGW AGW Type TWA TWA	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm 100 mg/m3 Value 1900 mg/m3 1000 ppm Value	Form Vapor and aerosol, inhalable fraction. Form
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Greece. OELs (Decree N Components Ethanol (CAS 64-17-5) Hungary. OELs. Joint De Components	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type AGW AGW AGW TWA TWA Type TYPE AGW AGW So. 90/1999, as amended) Type TWA TWA TWA STEL	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm 100 mg/m3 Value 1900 mg/m3 1000 ppm Value 3800 mg/m3	Form Vapor and aerosol, inhalable fraction. Form
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Greece. OELs (Decree N Components Ethanol (CAS 64-17-5) Hungary. OELs. Joint De Components Ethanol (CAS 64-17-5)	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type AGW AGW AGW TWA TWA TWA AGW TYPE TWA TWA TWA AGW TYPE TWA TWA TWA	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm 100 mg/m3 Value 1900 mg/m3 1000 ppm Value	Form Vapor and aerosol, inhalable fraction. Form
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Greece. OELs (Decree N Components Ethanol (CAS 64-17-5) Hungary. OELs. Joint Decomponents Ethanol (CAS 64-17-5)	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type AGW AGW AGW TWA TWA TWA AGW AGW TYPE TWA TWA TWA TYPE TWA TWA TYPE TWA TWA TWA TYPE TWA TWA TYPE TWA TWA TYPE TWA TYPE STEL TWA TWA TWA TYPE STEL TWA TWA TYPE STEL TWA TWA TYPE TWA TYPE STEL TWA	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm 100 mg/m3 Value 1900 mg/m3 1000 ppm Value 3800 mg/m3	Form Vapor and aerosol, inhalable fraction. Form
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Greece. OELs (Decree N Components Ethanol (CAS 64-17-5) Hungary. OELs. Joint De Components Ethanol (CAS 64-17-5) Hungary. OELs. Regulation Components Ethanol (CAS 64-17-5)	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type AGW AGW AGW TWA TWA TWA TOWA Type Type TYPE TOWA TO	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm 100 mg/m3 Value 1900 mg/m3 1000 ppm Value 3800 mg/m3 1900 mg/m3 1900 mg/m3	Form Vapor and aerosol, inhalable fraction. Form
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Greece. OELs (Decree N Components Ethanol (CAS 64-17-5) Hungary. OELs. Joint De Components Ethanol (CAS 64-17-5) Hungary. OELs. Regulation Components Ethanol (CAS 64-17-5)	Type TWA TWA TWA mit Values in the Ambient Air at the Workplace Type AGW AGW AGW TWA TWA TWA AGW AGW TYPE TWA TWA TWA TYPE TWA TWA TYPE TWA TWA TWA TYPE TWA TWA TYPE TWA TWA TYPE TWA TYPE STEL TWA TWA TWA TYPE STEL TWA TWA TYPE STEL TWA TWA TYPE TWA TYPE STEL TWA	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm 100 mg/m3 Value 1900 mg/m3 1000 ppm Value 3800 mg/m3 1900 mg/m3 1900 mg/m3	Form Vapor and aerosol, inhalable fraction. Form
Germany. DFG MAK List in the Work Area (DFG) Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Germany. TRGS 900, Lin Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Greece. OELs (Decree N Components Ethanol (CAS 64-17-5) Hungary. OELs. Joint De Components Ethanol (CAS 64-17-5)	Type TWA TWA mit Values in the Ambient Air at the Workplace Type AGW AGW AGW TWA TWA TWA TWA AGW AGW TYPE TWA TWA TWA TWA TWA AGW TYPE TWA TWA TWA TWA TWA TWA TWA TWA	Value 380 mg/m3 200 ppm 100 mg/m3 Value 380 mg/m3 200 ppm 100 mg/m3 Value 1900 mg/m3 1000 ppm Value 3800 mg/m3 1900 mg/m3 1900 mg/m3	Form Vapor and aerosol, inhalable fraction. Form

STEL

Ethanol (CAS 64-17-5)

1000 ppm

Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
Latvia. OELs. Occupational expo Components	osure limit values of chemical s Type	substances in work environm Value	ent
Ethanol (CAS 64-17-5)	TWA	1000 mg/m3	
Lithuania. OELs. Limit Values fo	or Chemical Substances, Gener	ral Requirements	
Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3	
		1000 ppm	
	TWA	1000 mg/m3	
		500 ppm	
Netherlands. OELs (binding)			
Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3	
	TWA	260 mg/m3	
Norway. Administrative Norms for Components	or Contaminants in the Workpla Type	ace Value	
Ethanol (CAS 64-17-5)	TLV	950 mg/m3	
	124	500 ppm	
Poland. Ordinance of the Ministo	or of Labour and Social Policy	on 6 June 2014 on the maxim	um normiesiblo
concentrations and intensities of			
Components	Туре	Value	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
Portugal. VLEs. Norm on occupa	ational exposure to chemical a	gents (NP 1796)	
Components	Туре	Value	
Ethanol (CAS 64-17-5)	TWA	1000 ppm	
Romania. OELs. Protection of w Components	orkers from exposure to chemi Type	ical agents at the workplace Value	
Ethanol (CAS 64-17-5)	STEL	9500 mg/m3	
		5000 ppm	
	TWA	1900 mg/m3	
		1000 ppm	
Slovakia. OELs. Regulation No.	300/2007 concerning protection	n of health in work with chem	ical agents
Components	Туре	Value	•
Ethanol (CAS 64-17-5)	STEL	1920 mg/m3	
		1000 ppm	
	TWA	960 mg/m3	
		500 ppm	
Slovenia. OELs. Regulations co	ncerning protection of workers	against risks due to exposur	e to chemicals while work
Official Gazette of the Republic	of Slovenia)	-	
	Typo	Value	Form
Components	Туре		
<u> </u>	TWA	960 mg/m3	
<u> </u>		960 mg/m3 500 ppm	
Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS		· ·	Inhalable fraction.
Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Spain. Occupational Exposure L	TWA	500 ppm	Inhalable fraction.
Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Spain. Occupational Exposure L	TWA	500 ppm	Inhalable fraction.
Components Ethanol (CAS 64-17-5) Propanol, oxybis- (CAS 25265-71-8) Spain. Occupational Exposure L Components Ethanol (CAS 64-17-5)	TWA TWA	500 ppm 100 mg/m3	Inhalable fraction.

1000 ppm

Components	ironment Authority (AV), Occupational E Type	Value			
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3			
		1000 ppm			
	TWA	1000 mg/m3			
		500 ppm			
Switzerland. SUVA Grenzy	werte am Arbeitsplatz				
Components	Туре	Value	Form		
Ethanol (CAS 64-17-5)	STEL	1920 mg/m3			
		1000 ppm			
	TWA	960 mg/m3			
		500 ppm			
Propanol, oxybis- (CAS 25265-71-8)	STEL	280 mg/m3	Vapor and aerosol, inhalable.		
	TWA	140 mg/m3	Vapor and aerosol, inhalable.		
UK. EH40 Workplace Expo Components	osure Limits (WELs) Type	Value			
Ethanol (CAS 64-17-5)	TWA	1920 mg/m3			
		1000 ppm			
logical limit values	No biological exposure limits noted for	the ingredient(s).			
commended monitoring cedures	Follow standard monitoring procedure	S.			
rived no effect levels IELs)	Not available.				
dicted no effect ncentrations (PNECs)	Not available.				
oosure guidelines					
Netherlands OELs (bindin Ethanol (CAS 64-17-5)	•	a absorbed through the skin			
Exposure controls	Can be absorbed through the skin.				
propriate engineering atrols	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommende exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.				
ividual protection measure	s, such as personal protective equipme				
General information	Use personal protective equipment as according to the CEN standards and ir	required. Personal protection			

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Wear safety glasses with side shields (or goggles). Face shield is recommended. Eye/face protection

Skin protection

Wear appropriate chemical resistant gloves. - Hand protection

- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquid.FormLiquid.ColourNot available.OdourNot available.

Melting point/freezing point -114,1 °C (-173,38 °F) estimated

Boiling point or initial boiling 78,29 °C (172,92 °F) estimated

point and boiling range

Flammability Not applicable.

Flash point 13 °C (55,4 °F) estimated

Auto-ignition temperature 363 °C (685,4 °F) estimated

Decomposition temperatureNot available.pHNot available.Kinematic viscosityNot available.

Solubility

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water) (log value)

Vapour pressure 60,910366 hPa estimated

Density and/or relative density

Density 0,801 g/cm3 estimated

Vapour densityNot available.Particle characteristicsNot available.

9.2. Other information

9.2.1. Information with regard No relevant additional information available. **to physical hazard classes**

9.2.2. Other safety characteristics

Percent volatile 78,27 % estimated
Specific gravity 0,8014 estimated
VOC 77,78 % estimated

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stabilityMaterial is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Coughing. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity No data available.

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Due to partial or complete lack of data the classification is not possible. Respiratory sensitisation

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Carcinogenicity

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Specific target organ toxicity -

single exposure

Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Due to partial or complete lack of data the classification is not possible. **Aspiration hazard**

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

Not available. Other information

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects. Based on available data, the classification criteria are

not met for hazardous to the aquatic environment, acute hazard.

Components Species **Test Results**

Ethanol (CAS 64-17-5)

Aquatic

Acute Crustacea

EC50 Water flea (Daphnia magna) 7,7 - 11,2 mg/l, 48 hours

LC50 Fish Rainbow trout, donaldson trout 42 mg/l, 4 days

(Oncorhynchus mykiss)

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Alpha-isomethyl ionone	4,288
Cyclamen aldehyde	3,4
delta-Damascone	3,4
	4,2
Ethanol	-0,31
Ethyl 2,2-dimethylhydrocinnamal	3,6
Linalool	2,97
Linalyl acetate	3,9
	3,93
Oils, cedarwood	6,12
Oils, mandarin	4,38
Oxacycloheptadec-10-en-2-one	6,7
Rose Ketone-4	4,8

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

12.8. Additional information

Estonia Dangerous substances in soil Data

Ethanol (CAS 64-17-5) Chemical pesticides (As the total sum of the active substances)

0,5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20

mg/kg

Chemical pesticides (As the total sum of the active substances) 5

mg/kg

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code

The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1170

14.2. UN proper shipping ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

name (Ethanol)

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Hazard No. (ADR) 33
Tunnel restriction code D/E
14.4. Packing group ||

14.5. Environmental hazards Yes14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

RID

14.1. UN number UN1170

14.2. UN proper shipping ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

name (Ethanol)

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
14.4. Packing group ||
14.5. Environmental hazards Yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN1170

14.2. UN proper shipping ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

name (Ethanol)

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
14.4. Packing group ||
14.5. Environmental hazards Yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1170

14.2. UN proper shipping Ethanol solution (Ethanol)

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk
14.4. Packing group ||

14.5. Environmental hazards Yes
ERG Code 3L

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

ioi usei

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN1170

14.2. UN proper shipping ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

name (Ethanol), MARINE POLLUTANT

14.3. Transport hazard class(es)

Class 3
Subsidiary risk 14.4. Packing group ||
14.5. Environmental hazards
Marine pollutant Yes

EmS F-E, S-D

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk according to IMO instruments

Not established.

ADN; ADR; IATA; IMDG; RID



Marine pollutant



General information IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

UFI:

Austria: EGWM-AEM2-R91S-KM2D Belgium: EGWM-AEM2-R91S-KM2D Bulgaria: EGWM-AEM2-R91S-KM2D Croatia: EGWM-AEM2-R91S-KM2D Cyprus: EGWM-AEM2-R91S-KM2D Czech Republic: EGWM-AEM2-R91S-KM2D Denmark: EGWM-AEM2-R91S-KM2D Estonia: EGWM-AEM2-R91S-KM2D FU: FGWM-AFM2-R91S-KM2D Finland: EGWM-AEM2-R91S-KM2D France: EGWM-AEM2-R91S-KM2D Germany: EGWM-AEM2-R91S-KM2D Great Britain: EGWM-AEM2-R91S-KM2D Greece: EGWM-AEM2-R91S-KM2D Hungary: EGWM-AEM2-R91S-KM2D Iceland: EGWM-AEM2-R91S-KM2D Ireland: EGWM-AEM2-R91S-KM2D Italy: EGWM-AEM2-R91S-KM2D Latvia: EGWM-AEM2-R91S-KM2D Lithuania: EGWM-AEM2-R91S-KM2D Luxembourg: EGWM-AEM2-R91S-KM2D Malta: EGWM-AEM2-R91S-KM2D Netherlands: EGWM-AEM2-R91S-KM2D Norway: EGWM-AEM2-R91S-KM2D Poland: EGWM-AEM2-R91S-KM2D Portugal: EGWM-AEM2-R91S-KM2D Romania: EGWM-AEM2-R91S-KM2D Slovakia: EGWM-AEM2-R91S-KM2D Slovenia: EGWM-AEM2-R91S-KM2D Spain: EGWM-AEM2-R91S-KM2D

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed

Sweden: EGWM-AEM2-R91S-KM2D

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Ethanol (CAS 64-17-5) Linalool (CAS 78-70-6)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Ethanol (CAS 64-17-5)

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as

amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland

Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

Revision information

Product and Company Identification: Product and Company Identification

SECTION 2: Hazards identification: Storage

Training information

Disclaimer

Follow training instructions when handling this material.

Home Fragrance Italia S.r.L. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.