SAFETY DATA SHEET



Version #: 02

Issue date: 07-November-2021 Revision date: 05-October-2022 Supersedes date: 07-November-2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

MILLEFIORI FRAGRANCE DIFFUSER 100 ml MELA & CANNELLA 7MDMC

Registration number

Synonyms None. 7MDMC **Product code**

1.2. Relevant identified uses of the substance or mixture and uses advised against

General Public Use Identified uses Uses advised against None known 1.3. Details of the supplier of the safety data sheet

Company name Home Fragrance Italia **Address** Via A. Tonale 26

> Milano 20125 IT

Division

Telephone

Not available. e-mail Not available. Contact person

1.4. Emergency telephone

number

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons Information Centre

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons

Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Bulgaria National Toxicological Information

Centre

+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Czech Republic National Poisons Information

Centre

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

Control Center

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Estonia National Poisons Information Centre

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Hungary National Emergency Phone Number

36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department** 2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

1.4. Emergency telephone number

Netherlands National Poisons Information Center (NVIC) 030-274 88 88 (Only for the purpose of informing medical personnel in cases of

acute intoxications)

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Portugal Poison Centre 800 250 250 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica $021.318.36.06 \ (Available \ 8:00AM-3:00PM. \ SDS/Product \ information \ may \ not \ be$

available for the Emergency Service.)

Slovakia National

Toxicological Information Centre

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info 145 (Available 24 hours a day. SDS/Product information may not be available for

Suisse the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids Category 2 H225 - Highly flammable liquid and

vapour.

Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.
Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Skin sensitisation Category 1A H317 - May cause an allergic skin

reaction.

Environmental hazards

Hazardous to the aquatic environment, Category 2 H411 - Toxic to aquatic life with

long-term aguatic hazard long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: 3,4-Dimethoxy benzaldehyde, alpha-Pinene, beta-Caryophyllene, beta-Pinene, Cinnamal,

Cinnamyl alcohol, Citral, Coumarin, d-Limonene, Eugenol, Hexyl Cinnamal, Linalool

Hazard pictograms



Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P235 Keep cool.

P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist/vapours.
P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 P280	Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Response	
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Ğet medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.
P391	Collect spillage.
Storage	

Storage

Store in a well-ventilated place. P403

Store in a well-ventilated place. Keep cool. P403 + P235

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information

5,91 % of the mixture consists of component(s) of unknown acute oral toxicity. 5,91 % of the mixture consists of component(s) of unknown acute dermal toxicity. 5,91 % of the mixture consists of component(s) of unknown acute inhalation toxicity. 5,91 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 5,91 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Ethanol		60 - 70	64-17-5 200-578-6	-	603-002-00-5	
	Classification: F	lam. Liq.	2;H225, Eye Irrit. 2;H	319		
Cinnamal		10 - 20	104-55-2 203-213-9	-	-	
				mg/kg), Skin Irrit. 2;H315, E quatic Chronic 3;H412	ye Irrit.	
Benzyl alcohol		5 - 10	100-51-6 202-859-9	-	603-057-00-5	
		Acute Tox Eye Irrit. 2		ng/kg), Acute Tox. 4;H332;(ATE: 11 mg/l),	
beta-Caryophyllene		1 - 3	87-44-5 201-746-1	-	-	
	Classification: E	ye Irrit. 2 Chronic 1;	;H319, Skin Sens. 1; H410	H317, Asp. Tox. 1;H304, Aq	uatic	
Coumarin		1 - 3	91-64-5 202-086-7	-	-	
	Classification: A	Acute Tox	. 4;H302;(ATE: 500 m	ıg/kg), Skin Sens. 1B;H317		
d-Limonene		1 - 3	5989-27-5 227-813-5	-	601-029-00-7	
				H315, Skin Sens. 1;H317, A Aquatic Chronic 1;H410	sp. Tox.	С
Eugenol		1 - 3	97-53-0 202-589-1	-	-	
		ye Irrit. 2 Chronic 4;		H317, Asp. Tox. 1;H304, Aq	uatic	
Resin acids and Rosir hydrogenated, Me est		1 - 3	8050-15-5 232-476-2	-	-	
	Classification: A	Aquatic Cl	nronic 3;H412			
Vanillin		1 - 3	121-33-5 204-465-2	-	-	
	Classification: E	Eye Irrit. 2	;H319			

alpha-Pinene		≤ 1	80-56-8 201-291-9	-	-	
	Classification	2;H315, S		4;H302;(ATE: 500 mg/kg Asp. Tox. 1;H304, Aquati		
Benzyl benzoate		≤ 1	120-51-4 204-402-9	-	607-085-00-9	
	Classification	on: Acute Tox. Chronic 2;		ng/kg), Aquatic Acute 1;h	H400, Aquatic	
beta-Pinene		≤ 1	127-91-3 204-872-5	-	-	
	Classification			H315, Skin Sens. 1B;H3 Aquatic Chronic 1;H410		
1,4-Cyclohexadiene, 1-methyl-4-(1-methyle	thyl)-	≤ 0,2	99-85-4 202-794-6	-	-	
	Classification	on: Flam. Liq.	3;H226, Repr. 2;H36	61, Asp. Tox. 1;H304		
3,4-Dimethoxy benzal	dehyde	≤ 0,2	120-14-9 204-373-2	-	-	
	Classification	n: Acute Tox.	4;H302;(ATE: 500 n	ng/kg), Skin Sens. 1B;H3	317	
Cinnamyl alcohol		≤ 0,2	104-54-1 203-212-3	-	-	
	Classification	n: Acute Tox.	4;H302;(ATE: 500 n	ng/kg), Skin Sens. 1B;H3	317	
Citral		≤ 0,2	5392-40-5 226-394-6	-	605-019-00-3	
	Classification	n: Skin Irrit. 2	;H315, Eye Irrit. 2;H	319, Skin Sens. 1;H317		
Hexyl Cinnamal		≤ 0,2	101-86-0 202-983-3	-	-	
	Classification	n: Skin Sens	. 1B;H317, Aquatic A	cute 1;H400, Aquatic Ch	ronic 2;H411	
Linalool		≤ 0,2	78-70-6 201-134-4	-	603-235-00-2	
	Classification	on: Skin Irrit. 2	;H315, Eye Irrit. 2;H	319, Skin Sens. 1B;H317	7	
safrole; 5-allyl-1,3-ben	zodioxole	≤ 0,2	94-59-7 202-345-4	-	605-020-00-9	
	Classification	n: Acute Tox	4·H302·(ATF: 500 n	ng/kg), Muta. 2;H341, Ca	arc. 1B·H350	

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

levels

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. #: This substance has been assigned Union workplace exposure limit(s).

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves. Wash contaminated clothing

before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

4.2. Most important symptoms and effects, both acute and

delayed

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing, Skin irritation. May cause redness and pain. May cause an allergic skin

reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Highly flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

5.2. Special hazards arising

Do not use water jet as an extinguisher, as this will spread the fire.

from the substance or mixture

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (Gv Components	Type	Value	
Ethanol (CAS 64-17-5)	Ceiling	3800 mg/m3	
		2000 ppm	
	MAK	1900 mg/m3	
		1000 ppm	
Belgium. Exposure Limit Values Components	Туре	Value	Form
alpha-Pinene (CAS 30-56-8)	TWA	20 ppm	
peta-Pinene (CAS 127-91-3)	TWA	20 ppm	
Citral (CAS 5392-40-5)	TWA	32 mg/m3 5 ppm	Vapour and aerosol. Vapour and aerosol.
Ethanol (CAS 64-17-5)	TWA	1907 mg/m3	vapour and dorocor.
	1 7 7 7	1000 ppm	
Bulgaria. OELs. Regulation No 13 on Components	protection of workers again Type		nical agents at work
Benzyl alcohol (CAS 100-51-6)	TWA	5 mg/m3	
Ethanol (CAS 64-17-5)	TWA	1000 mg/m3	
Croatia. Dangerous Substance Expos Components	ure Limit Values in the Wor Type	rkplace (ELVs), Annexes 1 a Value	nd 2, Narodne Novine, 13/0
Ethanol (CAS 64-17-5)	MAC	1900 mg/m3	
		1000 ppm	
Czech Republic. OELs. Government D Components	ecree 361 Type	Value	
Benzyl alcohol (CAS 100-51-6)	Ceiling	80 mg/m3	
	TWA	40 mg/m3	
Ethanol (CAS 64-17-5)	Ceiling	3000 mg/m3	
	TWA	1000 mg/m3	
Denmark. Exposure Limit Values Components	Туре	Value	
alpha-Pinene (CAS 80-56-8)	TLV	25 ppm	
peta-Pinene (CAS 127-91-3)	TLV	25 ppm	
d-Limonene (CAS 5989-27-5)	TLV	25 ppm	
Ethanol (CAS 64-17-5)	TLV	1900 mg/m3	
		1000 ppm	
Estonia. OELs. Occupational Exposui Components	e Limits of Hazardous Sub Type	stances (Regulation No. 105 Value	3/2001, Annex), as amended
alpha-Pinene (CAS 80-56-8)	STEL	300 mg/m3	
		50 ppm	
	TWA	150 mg/m3	
		25 ppm	
beta-Pinene (CAS 127-91-3)	STEL	300 mg/m3	
		50 ppm	
	TWA	150 mg/m3	
		25 ppm	
		PP	

Components		Туре	Value	
			1000 ppm	
		TWA	1000 mg/m3	
			500 ppm	
Finland. Workplace Exp	osure Limits	T	Value	
Components		Туре	Value	
Benzyl alcohol (CAS 100-51-6)		TWA	45 mg/m3	
			10 ppm	
d-Limonene (CAS		STEL	280 mg/m3	
5989-27-5)				
			50 ppm	
		TWA	140 mg/m3	
			25 ppm	
Ethanol (CAS 64-17-5)		STEL	2500 mg/m3	
			1300 ppm	
		TWA	1900 mg/m3	
			1000 ppm	
France. Threshold Limit Components	: Values (VLEP) for	Occupational Exposure to Cl Type	nemicals in France, IN Value	RS ED 984
Ethanol (CAS 64-17-5)		VLE	9500 mg/m3	
Regulatory status:	Indicative limit (VL	_)		
			5000 ppm	
Regulatory status:	Indicative limit (VL	_)		
		VME	1900 mg/m3	
Regulatory status:	Indicative limit (VL		-	
	·	_)	1000 ppm	
Regulatory status:	Indicative limit (VI	-)	1000 ppm	
Regulatory status: Germany. DFG MAK List	Indicative limit (VI	_)	1000 ppm	s of Chemical Compou
Regulatory status: Germany. DFG MAK List in the Work Area (DFG)	Indicative limit (VI	-)	1000 ppm	s of Chemical Compou Form
Regulatory status: Germany. DFG MAK List n the Work Area (DFG) Components	Indicative limit (VI	-) -) Commission for the Investiga	1000 ppm tion of Health Hazards	
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS	Indicative limit (VI	-) -) Commission for the Investiga Type	1000 ppm tion of Health Hazards Value 22 mg/m3	Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6)	Indicative limit (VI	-) Commission for the Investiga Type TWA	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm	Form
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS	Indicative limit (VI	-) -) Commission for the Investiga Type	1000 ppm tion of Health Hazards Value 22 mg/m3	Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS	Indicative limit (VI	-) Commission for the Investiga Type TWA	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3	Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List In the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5)	Indicative limit (VI	-) Commission for the Investiga Type TWA	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm	Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5)	Indicative limit (VI	-) Commission for the Investiga Type TWA	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3	Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5)	Indicative limit (VI	-) Commission for the Investiga Type TWA TWA	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm	Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5) Germany. TRGS 900, Lir	Indicative limit (VI	-) Commission for the Investiga Type TWA TWA TWA TWA	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3 200 ppm	Form Vapour and aerosol. Vapour and aerosol.
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5) Germany. TRGS 900, Lir Components	Indicative limit (VI	Type TWA TWA TWA TWA TWA TWA TWA	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3 200 ppm Value	Form Vapour and aerosol. Vapour and aerosol. Form
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5) Germany. TRGS 900, Lir Components Benzyl alcohol (CAS	Indicative limit (VI	-) Commission for the Investiga Type TWA TWA TWA TWA	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3 200 ppm	Form Vapour and aerosol. Vapour and aerosol.
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5) Germany. TRGS 900, Lir Components Benzyl alcohol (CAS	Indicative limit (VI	Type TWA TWA TWA TWA TWA TWA TWA	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3 200 ppm Value	Form Vapour and aerosol. Vapour and aerosol. Form
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5) Germany. TRGS 900, Lir Components Benzyl alcohol (CAS 100-51-6)	Indicative limit (VI	Type TWA TWA TWA TWA TWA TWA TWA	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3 200 ppm Value 22 mg/m3	Form Vapour and aerosol. Vapour and aerosol. Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List In the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5) Germany. TRGS 900, Lir Components Benzyl alcohol (CAS 100-51-6)	Indicative limit (VI	Type TWA TWA TWA TWA Mbient Air at the Workplace Type AGW	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3 200 ppm Value 22 mg/m3 5 ppm 28 mg/m3	Form Vapour and aerosol. Vapour and aerosol. Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List In the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5) Germany. TRGS 900, Lir Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5)	Indicative limit (VI	Type TWA TWA TWA TWA Mbient Air at the Workplace Type AGW	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3 200 ppm Value 22 mg/m3 5 ppm	Form Vapour and aerosol. Vapour and aerosol. Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5) Germany. TRGS 900, Lir Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5)	Indicative limit (VI	Type TWA TWA TWA TWA Mbient Air at the Workplace Type AGW	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3 200 ppm Value 22 mg/m3 5 ppm 28 mg/m3	Form Vapour and aerosol. Vapour and aerosol. Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5) Germany. TRGS 900, Lir Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5)	Indicative limit (VI	Commission for the Investigaty Type TWA TWA TWA TWA Mathematical Air at the Workplace Type AGW AGW	tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3 200 ppm Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 35 ppm	Form Vapour and aerosol. Vapour and aerosol. Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5) Germany. TRGS 900, Lir Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5)	Indicative limit (VI	Commission for the Investigaty Type TWA TWA TWA TWA mbient Air at the Workplace Type AGW AGW	tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3 200 ppm Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3	Form Vapour and aerosol. Vapour and aerosol. Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List In the Work Area (DFG) Components Genzyl alcohol (CAS 100-51-6) G-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5) Germany. TRGS 900, Lir Components Genzyl alcohol (CAS 100-51-6) G-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5) Greece. OELs (Decree N	Indicative limit (VI	Commission for the Investigaty Type TWA TWA TWA TWA mbient Air at the Workplace Type AGW AGW	tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3 200 ppm Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3	Form Vapour and aerosol. Vapour and aerosol. Form Vapour and aerosol.
Regulatory status: Germany. DFG MAK List in the Work Area (DFG) Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5)	Indicative limit (VI	Commission for the Investigative Type TWA TWA TWA TWA TWA The Moreover Air at the Workplace Type AGW AGW AGW AGW AGW	1000 ppm tion of Health Hazards Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 380 mg/m3 200 ppm Value 22 mg/m3 5 ppm 28 mg/m3	Form Vapour and aerosol. Vapour and aerosol. Form Vapour and aerosol.

Hungary. OELs. Joint Decree on C Components	hemical Safety of Workplaces Type	S Value	
Ethanol (CAS 64-17-5)	STEL	3800 mg/m3	
	TWA	1900 mg/m3	
Iceland. OELs. Regulation 154/199 Components	9 on occupational exposure l Type	imits Value	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
lreland. Occupational Exposure Li Components	mits Type	Value	Form
Citral (CAS 5392-40-5)	TWA	5 ppm	Inhalable fraction and vapour.
Ethanol (CAS 64-17-5)	STEL	1000 ppm	vapoui.
Italy. Occupational Exposure Limit Components		Value	Form
	Туре		FOIIII
alpha-Pinene (CAS 80-56-8)	TWA	20 ppm	
beta-Pinene (CAS 127-91-3)	TWA	20 ppm	
Citral (CAS 5392-40-5)	TWA	5 ppm	Inhalable fraction and
Ethanol (CAS 64-17-5)	STEL	1000 ppm	vapour.
Latvia. OELs. Occupational expos			ent
Components	Type	Value	
Benzyl alcohol (CAS 100-51-6)	TWA	5 mg/m3	
Ethanol (CAS 64-17-5)	TWA	1000 mg/m3	
Lithuania. OELs. Limit Values for Components	Chemical Substances, Gener Type	al Requirements Value	
alpha-Pinene (CAS	STEL	300 mg/m3	
80-56-8)			
	T\A/A	50 ppm	
	TWA	150 mg/m3	
		25 ppm	
Benzyl alcohol (CAS 100-51-6)	TWA	5 mg/m3	
beta-Pinene (CAS 127-91-3)	STEL	300 mg/m3	
,		50 ppm	
	TWA	150 mg/m3	
		25 ppm	
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3	
,		1000 ppm	
	TWA	1000 mg/m3	
		500 ppm	
Netherlands. OELs (binding)			
Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3	
	TWA	260 mg/m3	
Norway. Administrative Norms for Components	Contaminants in the Workpla Type	ice Value	
alpha-Pinene (CAS	TLV	140 mg/m3	
80-56-8)		25 ppm	
		20 ppiii	
beta-Pinene (CAS	TLV	140 mg/m3	

Components	Туре	Value	
		25 ppm	
l-Limonene (CAS 989-27-5)	TLV	140 mg/m3	
		25 ppm	
Ethanol (CAS 64-17-5)	TLV	950 mg/m3	
		500 ppm	
Poland. Ordinance of the Ministe concentrations and intensities of			
Components	Type	Value	
Benzyl alcohol (CAS 100-51-6)	TWA	240 mg/m3	
		0 ppm	
Citral (CAS 5392-40-5)	STEL	54 mg/m3	
		0 ppm	
	TWA	27 mg/m3	
		0 ppm	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		0 ppm	
Portugal. VLEs. Norm on occupa Components	tional exposure to chemical aç Type	gents (NP 1796) Value	Form
alpha-Pinene (CAS 80-56-8)	TWA	20 ppm	
peta-Pinene (CAS 127-91-3)	TWA	20 ppm	
Citral (CAS 5392-40-5)	TWA	5 ppm	Inhalable fraction and vapour.
Ethanol (CAS 64-17-5)	TWA	1000 ppm	
	orkers from exposure to chemi Type	cal agents at the workplace Value	
Components	<u>-</u>		
Components	Туре	Value	
Components	Туре	Value 9500 mg/m3	
Components	Type STEL	Value 9500 mg/m3 5000 ppm	
Components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3	Type STEL TWA 500/2007 concerning protection	9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm	cal agents
Components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3 Components	Type STEL TWA 00/2007 concerning protection Type	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemical Value	cal agents
Components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3 Components	Type STEL TWA 500/2007 concerning protection	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemical Value 1920 mg/m3	cal agents
Components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3 Components	Type STEL TWA 00/2007 concerning protection Type STEL	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemical Value 1920 mg/m3 1000 ppm	cal agents
Components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3 Components	Type STEL TWA 00/2007 concerning protection Type	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemical Value 1920 mg/m3 1000 ppm 960 mg/m3	cal agents
Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3 Components Ethanol (CAS 64-17-5)	Type STEL TWA 00/2007 concerning protection Type STEL TWA cerning protection of workers	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemical Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm	
Romania. OELs. Protection of wo Components Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3 Components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations con (Official Gazette of the Republic of	Type STEL TWA 00/2007 concerning protection Type STEL TWA cerning protection of workers of Slovenia)	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemical Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm against risks due to exposure	
Ethanol (CAS 64-17-5) Blovakia. OELs. Regulation No. 3 Components Ethanol (CAS 64-17-5) Blovenia. OELs. Regulations con Official Gazette of the Republic of Components Benzyl alcohol (CAS	Type STEL TWA 00/2007 concerning protection Type STEL TWA cerning protection of workers	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemical Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm	
Ethanol (CAS 64-17-5) Blovakia. OELs. Regulation No. 3 Components Ethanol (CAS 64-17-5) Blovenia. OELs. Regulations con Official Gazette of the Republic of Components Benzyl alcohol (CAS	Type STEL TWA 000/2007 concerning protection Type STEL TWA cerning protection of workers of Slovenia) Type	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemical Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm against risks due to exposure Value 22 mg/m3	
Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3 Components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations con Official Gazette of the Republic of Components Benzyl alcohol (CAS	Type STEL TWA 000/2007 concerning protection Type STEL TWA cerning protection of workers of Slovenia) Type TWA	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemical Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm against risks due to exposure Value 22 mg/m3 5 ppm	
Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3 Components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations con Official Gazette of the Republic of Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS	Type STEL TWA 000/2007 concerning protection Type STEL TWA cerning protection of workers of Slovenia) Type	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemic Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm against risks due to exposure Value 22 mg/m3 5 ppm 28 mg/m3	
Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3 Components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations con Official Gazette of the Republic of Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5)	Type STEL TWA 00/2007 concerning protection Type STEL TWA cerning protection of workers of Slovenia) Type TWA TWA TWA	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemical Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm against risks due to exposure Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm	
Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3 Components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations con Official Gazette of the Republic of Components Benzyl alcohol (CAS 100-51-6) d-Limonene (CAS 5989-27-5)	Type STEL TWA 000/2007 concerning protection Type STEL TWA cerning protection of workers of Slovenia) Type TWA	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemic Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm against risks due to exposure Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 960 mg/m3	
Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3 Components Ethanol (CAS 64-17-5) Slovenia. OELs. Regulations components Components Benzyl alcohol (CAS 64-17-6) d-Limonene (CAS 6989-27-5) Ethanol (CAS 64-17-5)	Type STEL TWA 00/2007 concerning protection Type STEL TWA cerning protection of workers of Slovenia) Type TWA TWA TWA	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemical Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm against risks due to exposure Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm	
Ethanol (CAS 64-17-5) Slovakia. OELs. Regulation No. 3 Components Ethanol (CAS 64-17-5)	Type STEL TWA 00/2007 concerning protection Type STEL TWA cerning protection of workers of Slovenia) Type TWA TWA TWA	Value 9500 mg/m3 5000 ppm 1900 mg/m3 1000 ppm n of health in work with chemic Value 1920 mg/m3 1000 ppm 960 mg/m3 500 ppm against risks due to exposure Value 22 mg/m3 5 ppm 28 mg/m3 5 ppm 960 mg/m3	

Spain. Occupational Exposure Limits			_
Components	Туре	Value	Form
		20 ppm	
beta-Pinene (CAS 127-91-3)	TWA	113 mg/m3	
12. 3. 3,		20 ppm	
Citral (CAS 5392-40-5)	TWA	5 ppm	Inhalable fraction and
	T14/4	400 / 0	vapour.
d-Limonene (CAS 5989-27-5)	TWA	168 mg/m3	
,		30 ppm	
Ethanol (CAS 64-17-5)	STEL	1910 mg/m3	
		1000 ppm	
Sweden. OELs. Work Environment Aut	hority (AV), Occupational Exposure	Limit Values (AFS	2015:7)
Components	Туре	Value	
alpha-Pinene (CAS	STEL	300 mg/m3	
80-56-8)		50 nnm	
	TWA	50 ppm 150 mg/m3	
	1 777.	25 ppm	
beta-Pinene (CAS	STEL	300 mg/m3	
127-91-3)	- · 	ooo mg/mo	
		50 ppm	
	TWA	150 mg/m3	
		25 ppm	
Ethanol (CAS 64-17-5)	STEL	1900 mg/m3	
		1000 ppm	
	TWA	1000 mg/m3	
		500 ppm	
Switzerland. SUVA Grenzwerte am Arbo Components	eitsplatz Type	Value	Form
alpha-Pinene (CAS	STEL	224 mg/m3	-
80-56-8)	OTEL	22 1 mg/mo	
		40 ppm	
	TWA	112 mg/m3	
		20 ppm	
Benzyl alcohol (CAS 100-51-6)	TWA	22 mg/m3	Vapour and aerosol.
100-31-0)		5 ppm	Vapour and aerosol.
beta-Pinene (CAS	STEL	224 mg/m3	,
127-91-3)		-	
	TIA/A	40 ppm	
	TWA	112 mg/m3	
d Limonono (CAS	ete:	20 ppm	
d-Limonene (CAS 5989-27-5)	STEL	80 mg/m3	
		14 ppm	
	TWA	40 mg/m3	
		7 ppm	
Ethanol (CAS 64-17-5)	STEL	1920 mg/m3	
		1000 ppm	
	TWA	960 mg/m3	
		500 ppm	
UK. EH40 Workplace Exposure Limits (
Components	Туре	Value	
Ethanol (CAS 64-17-5)	TWA	1920 mg/m3	

UK. EH40 Workplace Exposure Limits (WELs)

Components Type Value

1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines

Belgium OELs: Skin designation

Citral (CAS 5392-40-5) Can be absorbed through the skin.

Germany DFG MAK (advisory): Skin designation

Benzyl alcohol (CAS 100-51-6) Can be absorbed through the skin. d-Limonene (CAS 5989-27-5) Can be absorbed through the skin.

Germany TRGS 900 Limit Values: Skin designation

Benzyl alcohol (CAS 100-51-6) Can be absorbed through the skin. d-Limonene (CAS 5989-27-5) Can be absorbed through the skin.

Italy OELs: Skin designation

Citral (CAS 5392-40-5) Danger of cutaneous absorption

Lithuania OELs: Skin designation

Benzyl alcohol (CAS 100-51-6) Can be absorbed through the skin.

Netherlands OELs (binding): Skin designation

Ethanol (CAS 64-17-5) Can be absorbed through the skin.

Norway Exposure Limit Values: Skin designation

alpha-Pinene (CAS 80-56-8) Can be absorbed through the skin.

Portugal VLEs Norm on Occupational Exposure: Skin designation

Citral (CAS 5392-40-5) Can be absorbed through the skin.

Slovenia, OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Benzyl alcohol (CAS 100-51-6)

Can be absorbed through the skin. d-Limonene (CAS 5989-27-5) Can be absorbed through the skin.

Spain OELs: Skin designation

Citral (CAS 5392-40-5) Can be absorbed through the skin. d-Limonene (CAS 5989-27-5) Can be absorbed through the skin.

Switzerland SUVA Limit Values at the Workplace: Skin designation

alpha-Pinene (CAS 80-56-8) Can be absorbed through the skin. Benzyl alcohol (CAS 100-51-6) Can be absorbed through the skin. beta-Pinene (CAS 127-91-3) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Use personal protective equipment as required. Personal protection equipment should be chosen **General information**

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Wear safety glasses with side shields (or goggles). Face shield is recommended. Eye/face protection

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. - Other

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

When using do not smoke. Always observe good personal hygiene measures, such as washing Hygiene measures

after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid. **Form** Liquid.

Colour Not available. Not available. Odour

Melting point/freezing point Boiling point or initial boiling point and boiling range

-114,1 °C (-173,38 °F) estimated 78,29 °C (172,92 °F) estimated

Flammability (solid, gas) Not applicable. > 13 °C (> 55,4 °F) Flash point

363 °C (685.4 °F) estimated **Auto-ignition temperature**

Not available. **Decomposition temperature** Not available. рΗ

Solubility(ies)

Not available Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

59.016565 hPa estimated Vapour pressure

Not available. Vapour density Not available. Relative density Not available. Particle characteristics

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

0,858 g/cm3 estimated **Density**

Explosive properties Not explosive. Oxidising properties Not oxidising. 77.92 % estimated Percent volatile 0.85796 estimated Specific gravity VOC 76,94 % estimated

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the 10.4. Conditions to avoid

flash point. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous

No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Coughing, Skin irritation. May cause redness and pain. May cause an allergic skin

reaction. Dermatitis. Rash.

11.1. Information on toxicological effects

Not known. **Acute toxicity**

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible.

Skin sensitisation May cause an allergic skin reaction.

Due to partial or complete lack of data the classification is not possible. Germ cell mutagenicity

Risk of cancer cannot be excluded with prolonged exposure. Carcinogenicity

Hungary, 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

safrole; 5-allyl-1,3-benzodioxole (CAS 94-59-7)

IARC Monographs. Overall Evaluation of Carcinogenicity

Coumarin (CAS 91-64-5) 3 Not classifiable as to carcinogenicity to humans. d-Limonene (CAS 5989-27-5) 3 Not classifiable as to carcinogenicity to humans. Eugenol (CAS 97-53-0) 3 Not classifiable as to carcinogenicity to humans. 2B Possibly carcinogenic to humans.

safrole; 5-allyl-1,3-benzodioxole (CAS 94-59-7)

Due to partial or complete lack of data the classification is not possible. Reproductive toxicity

Specific target organ toxicity -

single exposure

Aspiration hazard

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

Due to partial or complete lack of data the classification is not possible.

repeated exposure

Based on available data, the classification criteria are not met.

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

Other information Not available.

SECTION 12: Ecological information

Toxic to aquatic life with long lasting effects. Based on available data, the classification criteria are 12.1. Toxicity

not met for hazardous to the aquatic environment, acute hazard.

Components		Species	Test Results
Benzyl alcohol (CAS 100-5	51-6)		
Aquatic			
Acute			
Fish	LC50	Bluegill (Lepomis macrochirus)	10 mg/l, 96 hours
Coumarin (CAS 91-64-5)			
Aquatic			
Acute			
Fish	LC50	Guppy (Poecilia reticulata)	>= 32 - <= 100 mg/l, 96 hours
d-Limonene (CAS 5989-27	⁷ -5)		
Aquatic			
Acute			
Crustacea	EC50	Water flea (Daphnia pulex)	69,6 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales prom	elas) >= 0,619 - <= 0,796 mg/l, 96 hours
Ethanol (CAS 64-17-5)			
Aquatic			
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	>= 7,7 - <= 11,2 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	42 mg/l, 4 days

Components Species **Test Results**

Eugenol (CAS 97-53-0)

Aquatic

Acute

LC50 Fathead minnow (Pimephales promelas) 24 mg/l, 96 hours Fish

Vanillin (CAS 121-33-5)

Aquatic

Acute

LC50 Fathead minnow (Pimephales promelas) >= 53 - <= 61,3 mg/l, 96 hours Fish

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient

n-octanol/water (log Kow)

1,4-Cyclohexadiene, 1-methyl-4-(1-methylethyl)-	5,4
3,4-Dimethoxy benzaldehyde	0,8
alpha-Pinene	4,83
Benzyl alcohol	1,1
Benzyl benzoate	3,97
beta-Caryophyllene	6,23
beta-Pinene	4,16
Cinnamal	1,9
	2,1
	2,107
Cinnamyl alcohol	1,452
Citral	2,76
	3,45
Coumarin	1,39
d-Limonene	4,57
Ethanol	-0,31
Eugenol	2,49
Hexyl Cinnamal	4,686
Linalool	2,97
safrole; 5-allyl-1,3-benzodioxole	3,45
Vanillin	1,37

Bioconcentration factor (BCF)

12.4. Mobility in soil

12.5. Results of PBT and vPvB

assessment

12.6. Endocrine disrupting

properties

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

The product does not contain components considered to have endocrine disrupting properties

according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

The product contains volatile organic compounds which have a photochemical ozone creation 12.7. Other adverse effects

potential.

Not available.

No data available.

12.8. Additional information

Estonia Dangerous substances in soil Data

Eugenol (CAS 97-53-0)

Benzyl alcohol (CAS 100-51-6) Chemical pesticides (As the total sum of the active substances)

0,5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20

mg/kg

Chemical pesticides (As the total sum of the active substances) 5

mg/kg

Chemical pesticides (As the total sum of the active substances) Benzyl benzoate (CAS 120-51-4)

0,5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20

mg/kg

Chemical pesticides (As the total sum of the active substances) 5

mg/kg

Ethanol (CAS 64-17-5) Chemical pesticides (As the total sum of the active substances)

0,5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20

mg/kg

Chemical pesticides (As the total sum of the active substances) 5

mg/kg

Chemical pesticides (As the total sum of the active substances)

0,5 mg/kg

Chemical pesticides (As the total sum of the active substances) 20

mg/kg

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautionsDispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1993

14.2. UN proper shipping FLAMMABLE LIQUID, N.O.S. (vapour pressure at

name 50 °C more than 110 kPa) (Ethanol, 11-methyldodecan-1-ol)

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Hazard No. (ADR) 33
Tunnel restriction code D/E
14.4. Packing group II
14.5. Environmental hazards Yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

RID

14.1. UN number UN1993

14.2. UN proper shipping FLAMMABLE LIQUID, N.O.S. (vapour pressure at 50 °C not more than 110 kPa) (Ethanol,

name 11-methyldodecan-1-ol)

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
14.4. Packing group ||
14.5. Environmental hazards Yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN1993

14.2. UN proper shipping FLAMMABLE LIQUID, N.O.S. (Ethanol, 11-methyldodecan-1-ol)

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
14.4. Packing group II
14.5. Environmental hazards Yes

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1993

14.2. UN proper shipping Flammable liquid, n.o.s. (Ethanol, 11-methyldodecan-1-ol)

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk 14.4. Packing group II
14.5. Environmental hazards Yes
ERG Code 3H

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

Allowed with restrictions.

for user

Other information

Passenger and cargo

aircraft

Allowed with restrictions. Cargo aircraft only

IMDG

14.1. UN number UN1993

14.2. UN proper shipping

FLAMMABLE LIQUID, N.O.S. (Ethanol, 11-methyldodecan-1-ol), MARINE POLLUTANT

name

14.3. Transport hazard class(es)

Class 3 Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards

Yes Marine pollutant F-E, S-E_ **EmS**

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user d-Limonene alpha-Pinene

14.7. Maritime transport in bulk

Not established.

according to IMO instruments

ADN; ADR; IATA; IMDG; RID



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **EU regulations**

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Ethanol (CAS 64-17-5) Linalool (CAS 78-70-6)

safrole; 5-allyl-1,3-benzodioxole (CAS 94-59-7)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

safrole; 5-allyl-1,3-benzodioxole (CAS 94-59-7)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Benzyl benzoate (CAS 120-51-4) d-Limonene (CAS 5989-27-5) Ethanol (CAS 64-17-5)

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Young people under 18 years old are not allowed to work with this product according to EU

Directive 94/33/EC on the protection of young people at work, as amended Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

Not available.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eve irritation.

H332 Harmful if inhaled.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

Revision information Training information Disclaimer This document has undergone significant changes and should be reviewed in its entirety.

Follow training instructions when handling this material.

Home Fragrance Italia cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.